

RIF-RHM-1-H - Relay retaining bracket



2905985

<https://www.phoenixcontact.com/us/products/2905985>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Relay retaining bracket, wire model, suitable for RIF-1 relay base, for 25 mm high octal miniature power relays

Commercial data

Item number	2905985
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	C465
Product key	DK6546
GTIN	4055626013343
Weight per piece (including packing)	0.52 g
Weight per piece (excluding packing)	0.52 g
Customs tariff number	85389099
Country of origin	CN

RIF-RHM-1-H - Relay retaining bracket



2905985

<https://www.phoenixcontact.com/us/products/2905985>

Technical data

Product properties

Product type	Retaining bracket
Product family	RIFLINE complete

Material specifications

Material	Metal
----------	-------

Approvals

Corrosive gas test

Identification	ISA-S71.04. G3 Harsh Group
	EN 60068-2-60

RIF-RHM-1-H - Relay retaining bracket



2905985

<https://www.phoenixcontact.com/us/products/2905985>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2905985>

DNV

Approval ID: TAA000018V

RIF-RHM-1-H - Relay retaining bracket



2905985

<https://www.phoenixcontact.com/us/products/2905985>

Classifications

ECLASS

ECLASS-13.0	27371692
ECLASS-15.0	27371692

ETIM

ETIM 9.0	EC002586
----------	----------

UNSPSC

UNSPSC 21.0	39122300
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%