

# CUC-MP-J1ST-A/4R4LT - Modular RJ45 PCB connectors



1149851

<https://www.phoenixcontact.com/us/products/1149851>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Modular RJ45 PCB connectors, 1x4 multi-port, connection direction of the connector to the PCB: 90 °, Tab up, Shielded, shield springs, number of positions: 8, 10 Gbps, PoE++, THT, Wave, type of packaging: Tray



## Your advantages

- The right version for every application. Available with and without LED, single- and multi-port
- The extended temperature range from -40 °C to +85 °C enables use in demanding applications
- Through-hole technology (THT) provides high mechanical stability when connecting the female connector to the PCB

## Commercial data

Item number	1149851
Packing unit	30 pc
Minimum order quantity	30 pc
Sales key	AB12
Product key	ABNADA
GTIN	4063151145859
Weight per piece (including packing)	16.963 g
Weight per piece (excluding packing)	16.963 g
Customs tariff number	85366930
Country of origin	TW

# CUC-MP-J1ST-A/4R4LT - Modular RJ45 PCB connectors



1149851

<https://www.phoenixcontact.com/us/products/1149851>

## Technical data

### Product properties

Product type	Data connector (device side)
Slots	1x4 multi-port
Orientation to PCB	90.00 °
Type	THD
Number of positions	8 (8P8C)
Type of locking	Snap-in locking Tab up
Shielding	Shielded, shield springs
application range	Wave
Type of packaging	Tray
Transmission speed	10 Gbps
PoE/PoE+	PoE++
Power PSE	90 W (Class 8 in accordance with IEEE 802.3bt)
Power PD	71 W (Class 4 in accordance with IEEE 802.3bt)

### Electrical properties

Rated voltage	72 V DC
Rated surge voltage	1.5 kV DC (IEC 60664-1)
Rated current	1.5 A (IEC 60603-7)
Frequency range	10 Hz ... 500 Hz
Test voltage	1.5 kV DC IEC 60603-7 (Contact - contact) 1.5 kV DC IEC 60603-7 (Contact - shield)
Insulation resistance	> 500 MΩ (IEC 60603-7)
Transmission speed	10 Gbps
Transmission speed	10 Gbps
Power transmission	PoE++

### Connection data

#### Connection technology

Connection method	Female
-------------------	--------

### Signaling

Status display present	no
------------------------	----

### Dimensions

Width	68.8 mm
Height	19 mm
Length	15.9 mm
Installed height	13.68 mm
Orientation to PCB	90.00 °
Data pin length	2.54 mm

# CUC-MP-J1ST-A/4R4LT - Modular RJ45 PCB connectors



1149851

<https://www.phoenixcontact.com/us/products/1149851>

## Material specifications

Material Plug contact coating (top layer/selective)	Au (0,152 µm / 6 µ")
Material Plug contact coating (intermediate layer)	Ni (1.27 µm/50 µ")
Material Solder contact coating (top layer/selective)	Au (Flash)
Material Solder contact coating (intermediate layer)	Ni (1.27 µm/50 µ")
Material Housing	Ni
Material Contact	Phosphor bronze
Material Housing pin coating (top layer/selective)	Ni
Material Contact carrier	PA

## Cable/line

Shielding	Shielded, shield springs
Halogen-free	no
Flame resistance	UL 94 V0

## Mechanical properties

Mechanical data	
Insertion/withdrawal cycles	> 750 (IEC 60603-7)
Insertion force	< 20 N (IEC 60603-7)
Withdrawal force	< 20 N (IEC 60603-7)

## Environmental and real-life conditions

Test specification	
Frequency	10-500 Hz
Sweep speed	1 octave/min
Amplitude	0.35 mm
Acceleration	50.00 m/s <sup>2</sup>
Test duration	20.00 s

Test specification	
Specification	IEC60068-2-27
Acceleration	295.00 m/s <sup>2</sup>

Ambient conditions	
Degree of protection (when plugged in)	IP20 (IEC 60603-7)
Degree of protection (not plugged in)	IP20 (IEC 60603-7)
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

## Standards and regulations

Flame resistance	UL 94 V0
------------------	----------

## Mounting

Mounting type	THT
---------------	-----

# CUC-MP-J1ST-A/4R4LT - Modular RJ45 PCB connectors



1149851

<https://www.phoenixcontact.com/us/products/1149851>

## Processing notes

Classification temperature  $T_c$

260 °C

## Packaging specifications

Type of packaging

Tray

# CUC-MP-J1ST-A/4R4LT - Modular RJ45 PCB connectors




1149851

<https://www.phoenixcontact.com/us/products/1149851>

## Drawings

Diagram



Classification wave soldering profile

# CUC-MP-J1ST-A/4R4LT - Modular RJ45 PCB connectors



1149851

<https://www.phoenixcontact.com/us/products/1149851>

## Approvals

ⓘ To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1149851>



**cUL Recognized**

Approval ID: FILE E 335024



**UL Recognized**

Approval ID: FILE E 335024

# CUC-MP-J1ST-A/4R4LT - Modular RJ45 PCB connectors



1149851

<https://www.phoenixcontact.com/us/products/1149851>

## Classifications

### ECLASS

ECLASS-13.0	27460201
ECLASS-15.0	27460201

### ETIM

ETIM 9.0	EC002637
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# CUC-MP-J1ST-A/4R4LT - Modular RJ45 PCB connectors



1149851

<https://www.phoenixcontact.com/us/products/1149851>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

### China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

### EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)