

# QPD W3PE2,5 9-14 M25 0,5 BK - Panel feed-through



1423980

<https://www.phoenixcontact.com/us/products/1423980>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Panel feed-through, connection method: Single wires (Welded-on)/ IDC connection, number of positions: 3+PE, M25, Pin, 1 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>, 690 V, 20 A, PA, black, with QUICKON nut, coding: coded, external cable diameter: 9 mm ... 14 mm, 2.5 mm<sup>2</sup>, wires cut flat at the end, cable length: 0.5 m

## Your advantages

- Innovative and time saving - QUICKON fast connection for time saving of up to 80 % for on-site connection
- Robust throughout: housing with IP68/IP69K and IK07 protection for a wide range of applications
- Safer connection with mechanical coding to protect against mismatching, and touch-proof protection in accordance with DIN EN 0105
- Efficient - by using panel feed-throughs, devices no longer need to be opened in order to connect cables

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1423980       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | BF50          |
| Product key                          | AF6ABB        |
| GTIN                                 | 4055626365978 |
| Weight per piece (including packing) | 102.8 g       |
| Weight per piece (excluding packing) | 101.3 g       |
| Customs tariff number                | 85444290      |
| Country of origin                    | PL            |

# QPD W3PE2,5 9-14 M25 0,5 BK - Panel feed-through



1423980

<https://www.phoenixcontact.com/us/products/1423980>

## Technical data

### Product properties

|                                    |                    |
|------------------------------------|--------------------|
| Product type                       | Panel feed-through |
| Product family                     | QPD                |
| Type                               | QPD 4x2,5          |
| Number of positions                | 4                  |
| Connection profile                 | 3+PE               |
| Position marking                   | 1, 2, 3, PE        |
| Number of connections              | 10                 |
| Number of connections per position | 1                  |
| Coding                             | coded              |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Connection data


#### Connection technology

|                                                                       |                          |
|-----------------------------------------------------------------------|--------------------------|
| Connection method On the device side                                  | Single wires (Welded-on) |
| Connection method On the field side                                   | IDC connection           |
| Frequency of connections between conductors of the same cross section | max. 10                  |

#### Conductor connection

|                                  |                                           |
|----------------------------------|-------------------------------------------|
| Conductor cross section flexibel | 1 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Conductor cross section solid    | 1 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Connection cross section AWG     | 16 ... 14                                 |
| Tightening torque Union nut      | 10 Nm                                     |
| Tightening torque Locking nut    | 5 Nm                                      |

### Dimensions

|                     |                                                                                      |
|---------------------|--------------------------------------------------------------------------------------|
| Dimensional drawing |  |
| Width               | 30 mm                                                                                |
| Height              | 30 mm                                                                                |
| Length              | 62 mm                                                                                |
| Diameter            | 30 mm                                                                                |

### Electrical properties

|                             |      |
|-----------------------------|------|
| Rated surge voltage (II/2)  | 6 kV |
| Rated surge voltage (III/2) | 6 kV |

# QPD W3PE2,5 9-14 M25 0,5 BK - Panel feed-through



1423980

<https://www.phoenixcontact.com/us/products/1423980>

|                             |          |
|-----------------------------|----------|
| Rated surge voltage (III/3) | 6 kV     |
| Rated current               | 20 A     |
| Contact resistance          | < 3 mΩ   |
| rated voltage (II/2)        | 1000 V   |
| rated voltage (III/2)       | 690 V    |
| Rated voltage (III/3)       | 690 V    |
| Nominal voltage $U_N$       | 690 V AC |
|                             | 690 V DC |
| Nominal current $I_N$       | 20 A     |

## Mechanical properties

### Mechanical data

|                             |         |
|-----------------------------|---------|
| Insertion/withdrawal cycles | max. 50 |
|-----------------------------|---------|

## Material specifications

|                                        |                   |
|----------------------------------------|-------------------|
| Color                                  | black (RAL 9005)  |
| Material Housing                       | PA                |
| Material Contact                       | Cu                |
| Material Contact surface               | silver-plated     |
| Material Seal                          | NBR               |
| Flammability rating according to UL 94 | V0                |
| Material wire insulation               | PVC/PE/TPE/rubber |

## Cable/line

|                                                                             |                                    |
|-----------------------------------------------------------------------------|------------------------------------|
| Cable length                                                                | 0.5 m                              |
| Structure of individual litz in acc. with VDE 0295 / smallest wire diameter | VDE 0295 class 1 to 6/min. 0.15 mm |
| External cable diameter                                                     | 9 mm ... 14 mm                     |
| Wire diameter including insulation                                          | 2 mm ... 3.6 mm                    |
| Position marking                                                            | 1, 2, 3, PE                        |
| Cable cross section                                                         | 2.5 mm <sup>2</sup>                |
| Material wire insulation                                                    | PVC/PE/TPE/rubber                  |
| Halogen-free                                                                | yes                                |

## Mounting

|               |                    |
|---------------|--------------------|
| Mounting type | Front mounting M25 |
|---------------|--------------------|

## Environmental and real-life conditions

### Ambient conditions

|                      |                                        |
|----------------------|----------------------------------------|
| Degree of protection | IP66                                   |
|                      | IP68 (2 m / 24 h)                      |
|                      | IP69K                                  |
|                      | Touch-proof when not plugged in (IP2X) |
| Impact strength      | IK07                                   |

# QPD W3PE2,5 9-14 M25 0,5 BK - Panel feed-through




1423980

<https://www.phoenixcontact.com/us/products/1423980>


|                                         |                   |
|-----------------------------------------|-------------------|
| Ambient temperature (operation)         | -40 °C ... 100 °C |
| Temperature when conductor connected    | -5 °C ... 50 °C   |
| Ambient temperature (storage/transport) | -40 °C ... 100 °C |

## Drawings

Dimensional drawing




Dimensional drawing



Panel cutout

1423980

<https://www.phoenixcontact.com/us/products/1423980>



Derating diagram

# QPD W3PE2,5 9-14 M25 0,5 BK - Panel feed-through



1423980

<https://www.phoenixcontact.com/us/products/1423980>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1423980>



### IECEE CB Scheme

Approval ID: DE1-65875



### VDE Zeichengenehmigung

Approval ID: 40029149

|                          | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
| keine                    |                       |                       |                   |                             |
| Only flexible conductors | 400 V                 | 20 A                  | -                 | 1.5 - 2.5                   |
| Only rigid conductors    | 690 V                 | 20 A                  | -                 | 1.5 - 2.5                   |



### UL Listed

Approval ID: E468743

|       | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|-------|-----------------------|-----------------------|-------------------|-----------------------------|
| keine |                       |                       |                   |                             |
|       | 600 V                 | 15 A                  | - 14              | - 14                        |



### cUL Listed

Approval ID: E468743

|       | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|-------|-----------------------|-----------------------|-------------------|-----------------------------|
| keine |                       |                       |                   |                             |
|       | 600 V                 | 15 A                  | - 14              | -                           |



### DNV GL

Approval ID: TAE00003J5

# QPD W3PE2,5 9-14 M25 0,5 BK - Panel feed-through



1423980

<https://www.phoenixcontact.com/us/products/1423980>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27440602 |
| ECLASS-15.0 | 27440602 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002566 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121500 |
|-------------|----------|

# QPD W3PE2,5 9-14 M25 0,5 BK - Panel feed-through



1423980

<https://www.phoenixcontact.com/us/products/1423980>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)