

# SAC-5P-MSB/ 4,0-900/FSB SCO - Bus system cable



1577312

<https://www.phoenixcontact.com/us/products/1577312>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Bus system cable, INTERBUS, 5-position, PUR halogen-free, may green RAL 6017, shielded, Plug straight M12 SPEEDCON, coding: B, on Socket straight M12 SPEEDCON, coding: B, cable length: 4 m

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 1577312                        |
| Packing unit                         | 1 pc                           |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Sales key                            | BF04                           |
| Product key                          | AF1CKB                         |
| GTIN                                 | 4046356451413                  |
| Weight per piece (including packing) | 310.4 g                        |
| Weight per piece (excluding packing) | 310.4 g                        |
| Customs tariff number                | 85444290                       |
| Country of origin                    | PL                             |

## Technical data

### Product properties

|                      |                         |
|----------------------|-------------------------|
| Product type         | Data cable preassembled |
| Sensor type          | INTERBUS                |
| Number of positions  | 5                       |
| No. of cable outlets | 1                       |
| Shielded             | yes                     |
| Coding               | B                       |

### Insulation characteristics

|                      |    |
|----------------------|----|
| Overvoltage category | II |
| Degree of pollution  | 3  |

### Interfaces

|                      |          |
|----------------------|----------|
| Bus system           | INTERBUS |
| Signal type/category | INTERBUS |

### Signaling

|                        |    |
|------------------------|----|
| Status display         | no |
| Status display present | no |

### Electrical properties

|                       |                            |
|-----------------------|----------------------------|
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Nominal voltage $U_N$ | 60 V                       |
| Nominal current $I_N$ | 4 A                        |

### Material specifications

|                                        |                                             |
|----------------------------------------|---------------------------------------------|
| Flammability rating according to UL 94 | V0                                          |
| Seal material                          | NBR                                         |
| Material of grip body                  | TPU, hardly inflammable, self-extinguishing |
| Contact material                       | CuSn                                        |
| Contact surface material               | Ni/Au                                       |
| Contact carrier material               | PA 6.6                                      |
| Material for screw connection          | Zinc die-cast, nickel-plated                |

### Connector

#### Connection 1

|                     |                            |
|---------------------|----------------------------|
| Type                | Plug straight M12 SPEEDCON |
| Number of positions | 5                          |
| Locking type        | SPEEDCON                   |
| Coding type         | B (inverse)                |

#### Connection 2

# SAC-5P-MSB/ 4,0-900/FSB SCO - Bus system cable



1577312


<https://www.phoenixcontact.com/us/products/1577312>

|                     |                              |
|---------------------|------------------------------|
| Type                | Socket straight M12 SPEEDCON |
| Number of positions | 5                            |
| Locking type        | SPEEDCON                     |
| Coding type         | B                            |

## Cable/line

|              |     |
|--------------|-----|
| Cable length | 4 m |
|--------------|-----|

## INTERBUS [900]

|                                            |                                                                                    |
|--------------------------------------------|------------------------------------------------------------------------------------|
| Dimensional drawing                        |  |
| Cable weight                               | 70 kg/km                                                                           |
| Number of positions                        | 6                                                                                  |
| Shielded                                   | yes                                                                                |
| Cable type                                 | INTERBUS [900]                                                                     |
| Conductor structure                        | 3 x 2 x 0.22 mm <sup>2</sup>                                                       |
| Signal speed                               | 0.66 c                                                                             |
| Conductor structure signal line            | 32x 0.10 mm                                                                        |
| AWG signal line                            | 24                                                                                 |
| Conductor cross section                    | 3x 2x 0.22 mm <sup>2</sup>                                                         |
| External cable diameter                    | 8.00 mm                                                                            |
| Outer sheath, material                     | PUR                                                                                |
| External sheath, color                     | may green RAL 6017                                                                 |
| Conductor material                         | Bare Cu litz wires                                                                 |
| Material wire insulation                   | PE                                                                                 |
| Single wire, color                         | green-yellow, white-brown, gray-pink                                               |
| Twisted pairs                              | 2 cores to the pair                                                                |
| Overall twist                              | 3 pairs to the core                                                                |
| Insulation resistance                      | ≥ 5 GΩ*km                                                                          |
| Coupling resistance                        | < 250.00 mΩ/m (at 30 MHz)                                                          |
| Loop resistance                            | ≤ 159.80 Ω/km                                                                      |
| Wave impedance                             | 120 Ω ±20 % (at 64 kHz)<br>100 Ω ±15 % (with 1 MHz)                                |
| Cable capacity                             | ≤ 60 nF/km (At 800 Hz)                                                             |
| Nominal voltage, cable                     | 250 V (Peak value, not for high-power applications)                                |
| Test voltage Core/Core                     | 1500 V <sub>rms</sub>                                                              |
| Test voltage Core/Shield                   | 1000.00 V <sub>rms</sub>                                                           |
| Minimum bending radius, fixed installation | 7.5 x D                                                                            |

# SAC-5P-MSB/ 4,0-900/FSB SCO - Bus system cable



1577312

<https://www.phoenixcontact.com/us/products/1577312>

|                                               |                                                                                                                                           |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Minimum bending radius, flexible installation | 15 x D                                                                                                                                    |
| Smallest bending radius, fixed installation   | 60 mm                                                                                                                                     |
| Smallest bending radius, movable installation | 120 mm                                                                                                                                    |
| Dynamic load capacity (bending)               | Max. bending cycles: 5000000, Bending radius: 120 mm, Traversing path: 10 m, Traversing rate: 1.6 m/s, Acceleration: 3.2 m/s <sup>2</sup> |
| Near end crosstalk attenuation (NEXT)         | ≥ 61 dB (at 772 kHz)                                                                                                                      |
|                                               | ≥ 59 dB (with 1 MHz)                                                                                                                      |
|                                               | ≥ 55 dB (at 2 MHz)                                                                                                                        |
|                                               | ≥ 50 dB (at 4 MHz)                                                                                                                        |
|                                               | ≥ 46 dB (at 8 MHz)                                                                                                                        |
|                                               | ≥ 44 dB (at 10 MHz)                                                                                                                       |
|                                               | ≥ 41 dB (at 16 MHz)                                                                                                                       |
| Shield attenuation                            | ≥ 40 dB (at 20 MHz)                                                                                                                       |
|                                               | ≤ 15 dB/km (at 256 kHz)                                                                                                                   |
|                                               | ≤ 24 dB/km (at 772 kHz)                                                                                                                   |
|                                               | ≤ 27 dB/km (with 1 MHz)                                                                                                                   |
|                                               | ≤ 52 dB/km (at 4 MHz)                                                                                                                     |
|                                               | ≤ 84 dB/km (at 10 MHz)                                                                                                                    |
|                                               | ≤ 112 dB/km (at 16 MHz)                                                                                                                   |
| Flame resistance                              | ≤ 119 dB/km (at 20 MHz)                                                                                                                   |
|                                               | according to VDE 0472, Part 4, test type B                                                                                                |
| Ambient temperature (operation)               | according to IEC 60332-1                                                                                                                  |
|                                               | -40 °C ... 80 °C (cable, fixed installation)                                                                                              |
|                                               | -30 °C ... 70 °C (Cable, flexible installation)                                                                                           |


## Environmental and real-life conditions

### Ambient conditions

|                                 |                                                 |
|---------------------------------|-------------------------------------------------|
| Degree of protection            | IP65                                            |
|                                 | IP67                                            |
|                                 | IP68                                            |
| Ambient temperature (operation) | -25 °C ... 90 °C (Plug / socket)                |
|                                 | -40 °C ... 80 °C (cable, fixed installation)    |
|                                 | -30 °C ... 70 °C (Cable, flexible installation) |


## Drawings

Dimensional drawing




Plug, M12 x 1, straight, shielded

Dimensional drawing



M12 x 1 socket, straight, shielded

Schematic diagram




Pin assignment M12 male connector, 5-pos., B-coded, male side

1577312


<https://www.phoenixcontact.com/us/products/1577312>

Schematic diagram



Pin assignment M12 socket, 5-pos., B-coded, female side

Circuit diagram



Contact assignment of the M12 connector and the M12 socket

Classifications

ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27060307 |
| ECLASS-15.0 | 27060307 |

## Environmental product compliance

### EU RoHS

|                                         |                    |
|-----------------------------------------|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|-----------------------------------------|--------------------|

### China RoHS

|                                        |                                                                                                                                                                                                                                   |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Environment friendly use period (EFUP) | EFUP-50                                                                                                                                                                                                                           |
|                                        | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|