

VS-25-DEVNET - D-SUB connector



1652240

<https://www.phoenixcontact.com/us/products/1652240>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



D-SUB connector, degree of protection: IP67, number of positions: 5, material: Plastic, connection method: Screw connection, connection cross section: AWG 24- 12, cable outlet: angled, DeviceNet™

Commercial data

Item number	1652240
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB19
Product key	ABNCBA
GTIN	4017918929169
Weight per piece (including packing)	107.2 g
Weight per piece (excluding packing)	107.2 g
Customs tariff number	85369010
Country of origin	DE

VS-25-DEVNET - D-SUB connector

1652240

<https://www.phoenixcontact.com/us/products/1652240>



Technical data

Notes

Safety note

Safety note	<p>WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.</p> <ul style="list-style-type: none">• WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.• WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.• The products are suitable for applications in plant, controller, and electrical device engineering.• When operating the connectors in outdoor applications, they must be separately protected against environmental influences.• Assembled products may not be manipulated or improperly opened.• Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).• When using the product in direct connection with third-party manufacturers, the user is responsible.• For operating voltages > 50 V AC, conductive connector housings must be grounded• Only use tools recommended by Phoenix Contact• The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product.• Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at phoenixcontact.com/products• Operate the connector only when it is fully plugged in and interlocked.• Operate the connector only when it is fully plugged in.• Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.• Observe the minimum bending radius of the cable. Lay the cable without twisting it.• VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector
-------------	--

Product properties

VS-25-DEVNET - D-SUB connector

1652240

<https://www.phoenixcontact.com/us/products/1652240>



Product type	Data connector (cable side)
Type	D-SUB
Sensor type	DeviceNet™
Number of positions	5
Shielded	no
Cable outlet	angled

Insulation characteristics	
Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated voltage (III/3)	250 V
Rated current	8 A
Transmission medium	Copper

Connection data

Connection technology	
Connection method	Screw connection
Connection cross section AWG	24 ... 12
Conductor cross section	0.2 mm² ... 2.5 mm²

Material specifications

Flammability rating according to UL 94	V0
Housing material	Plastic
Contact material	Cu alloy
Contact surface material	gold-plated
Contact carrier material	PA

Cable/line

Cable type	Round cable
Cable cross section	0.14 mm²

Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP67
Ambient temperature (operation)	-40 °C ... 80 °C

VS-25-DEVNET - D-SUB connector

1652240

<https://www.phoenixcontact.com/us/products/1652240>



Classifications

ECLASS

ECLASS-15.0	27440290
ECLASS-13.0	27440290

ETIM

ETIM 9.0	EC002943
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

VS-25-DEVNET - D-SUB connector

1652240

<https://www.phoenixcontact.com/us/products/1652240>



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-50 An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
--	--

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA

586 Fulling Mill Road

Middletown, PA 17057, United States

(+717) 944-1300

info@phoenixcon.com