

WIREMARK-F 15 - Marking foil for automatic conductor labeling device



5144042

<https://www.phoenixcontact.com/us/products/5144042>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Marking foil for automatic conductor labeling device, Roll, white, unmarked, can be labeled with: WIREMARK, mounting type: adhesive, Number of individual labels: 1, text field height: 14 mm, text field width: 14.8 mm

Commercial data

Item number	5144042
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	NULL
Product key	BG2211
GTIN	4017918921958
Weight per piece (including packing)	265.1 g
Weight per piece (excluding packing)	265.1 g
Customs tariff number	39206219
Country of origin	CH

WIREMARK-F 15 - Marking foil for automatic conductor labeling device



5144042

<https://www.phoenixcontact.com/us/products/5144042>

Technical data

Product properties

Product type	Conductor marker
Marking	
Number of individual labels	1

Dimensions

Height	14.8 mm
Depth	0.11 mm

Material specifications

Color	white (RAL 9010)
Material	PEPT

Cable/line

External cable diameter	> 0 mm
-------------------------	--------

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed
Specification	DIN EN ISO 1518-1:2019-10 (following)
Requirements	≥ 5 N
Result	Test passed

Tesafilm test

Specification	DIN EN ISO 2409:2013 (following)
Result	Test passed

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h
Procedure	Artificial irradiation.

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-1):2011-07
	DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl [CAS No. 67-63-0]	Test passed
n-Hexane [CAS No. 110-54-3]	Test passed

WIREMARK-F 15 - Marking foil for automatic conductor labeling device



5144042

<https://www.phoenixcontact.com/us/products/5144042>

Water + Petroleum ether [CAS No. 64742-82-1]	Test passed
---	-------------

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C (100°C short-term)
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 % (Storage in a dry and dark place in the original packaging is recommended)

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Mounting

Mounting type	adhesive
---------------	----------

WIREMARK-F 15 - Marking foil for automatic conductor labeling device



5144042

<https://www.phoenixcontact.com/us/products/5144042>

Classifications

ECLASS

ECLASS-13.0	27281102
ECLASS-15.0	27281102

ETIM

ETIM 9.0	EC001530
----------	----------

UNSPSC

UNSPSC 21.0	39131500
-------------	----------

WIREMARK-F 15 - Marking foil for automatic conductor labeling device



5144042

<https://www.phoenixcontact.com/us/products/5144042>

Environmental product compliance

EU REACH SVHC

REACH candidate substance (CAS No.)

No substance above 0.1 wt%

Phoenix Contact 2025 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com