



Powering Business Worldwide

Eaton 9PXM Battery Module Hot-swap Modular for Online Double-Conversion UPS (two required per slot), TAA

MODEL NUMBER: **9PXMBAT**



UPS battery cartridge provides initial or extended battery backup runtime for your Eaton 9PXM UPS system or EBM.

Features

Battery Cartridge for Eaton 9PXM Modular UPS Systems

This UPS battery cartridge is compatible with Eaton's 9PXM UPS systems and extended battery modules (EBM). Eaton UPS batteries have an expected lifespan of three to five years, so you should take proactive steps to avoid a dead battery and ensure continuous uptime. You can also add 9PXMBAT battery packs to your current application to increase runtime. Two 9PXMBAT battery cartridges are required for each slot.

Comes Pre-Wired for Quick, Easy Installation

The valve regulated lead acid (VRLA) 9PXMBAT internal battery cartridge is hot-swappable, allowing you to install it without powering down any connected equipment. Built to function in a wide range of operating temperatures, the 9PXMBAT has been carefully screened and certified to restore your UPS system's runtime performance to its original specifications or add runtime. It is leakproof, requires no maintenance and comes pre-wired for quick and easy installation in your 9PXM UPS system or EBM.

Highlights

- This UPS battery cartridge (Eaton Part Number P-103002954) is compatible with Eaton's 9PXM modular UPS systems and extended battery modules (EBM)
- Screened and certified to add UPS runtime or restore runtime to original specs
- Leakproof battery cartridge requires no regular maintenance
- Ships pre-wired and ready for immediate installation to expand redundancy and runtime
- Two 9PXMBAT battery cartridges are required for each slot

System Requirements

Compatible with Eaton's 9PXM8S4K-PD, 9PXM8S4K, 9PXM8S8K-PD, 9PXM8S8K, 9PXM12S8K, 9PXM12S8K-PD, 9PXM12S12K-PD, 9PXM8S12K, 9PXM12S12K, 9PXM8S16K, 9PXM12S16K-PD, 9PXM12S16K, 9PXM12S20K, 9PXM12S20K-PD, 9PXM12AAAAA, 9PXM08AAXXX, other 9PXM UPS systems and 9PXM08SEBM, 9PXM12SEBM, 9PXM08SEBM-C and 9PXM12SEBM-C EBMs

Package Includes

- 9PXMBAT Internal Battery Pack (P/N P-103002954)
- TWO 9PXMBAT batteries are required for each slot

Specifications

OVERVIEW	
UPC Code	743172091444
INPUT	
Input Phase	Single-Phase
Input Frequency	60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz
OUTPUT	
Frequency Compatibility	60 Hz



Powering Business Worldwide

BATTERY	
Battery Type	Valve Regulated Lead Acid (VRLA)
Expandable Runtime	No
DC System Voltage (VDC)	60 VDC per pack, 120 VDC full string
Battery Replacement Description	Hot-swappable internal batteries and extended battery modules (EBMs)
UPS Connection	Hardwired
Hot Swap Battery	Yes
PHYSICAL	
External Battery Pack Form Factor	Rack/Tower
Unit Dimensions (hwd / in.)	21.500 x 3.000 x 8.500
Unit Weight (lbs.)	33
Unit Weight (kg)	14.97
ENVIRONMENTAL	
Operating Temperature Range	32° to 104°F (0° to 40°C)
Relative Humidity	5-95% non-condensing
APPLICATIONS	
Used With	9PXM8S4K-PD, 9PXM8S4K, 9PXM8S8K-PD, 9PXM8S8K, 9PXM12S8K, 9PXM12S8K-PD, 9PXM12S12K-PD, 9PXM8S12K, 9PXM12S12K, 9PXM8S16K, 9PXM12S16K-PD, 9PXM12S16K, 9PXM12S20K, 9PXM12S20K-PD, 9PXM12AAAAA, 9PXM08AAXXX, 9PXM08SEBM, 9PXM12SEBM, 9PXM08SEBM-C, 9PXM12SEBM-C
STANDARDS & COMPLIANCE	
Product Certifications	UL Listed; cUL Listed
Product Compliance	FCC (USA); Trade Agreements Act (TAA)
WARRANTY & SUPPORT	
Product Warranty Period (U.S. & Canada)	2-year limited warranty

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2026 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.