

# Technical data sheet

## Flexible VFD Cable with 3 Symmetrical Grounds for Stationary Applications · shielded

### LUTZE DRIVEFLEX® XLPE (C) SYMMETRICAL



#### Identification

Type DR 3 XLPE (C) PVC (3x1/0+3xAWG8)  
Part No. [A2201/003](#)

#### Product version

Datasheet version 01

#### Use/Application/Properties

Application

- Dual-shielded motor supply cable to connect power to 3-phase-motors, VFDs and servo drives
- Three insulated symmetrical ground design helps to reduce stray currents
- Cable design for harsh industrial environments and operating conditions with high noise levels
- Thermoset XLPE insulation offering superior overload and short-circuit temperature
- Type XHHW-2 insulation offering smaller ODs for general VFD applications
- Compliant with NFPA 79 requirements
- TC-ER for use with cable trays without conduit, which can reduce installation costs in industrial environments
- WTTC – wind turbine tray cable rating for use in wind power generation
- Dry, damp or wet conditions

---

#### United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
[www.lutze.com](http://www.lutze.com) • [sales.gb@lutze.co.uk](mailto:sales.gb@lutze.co.uk)

#### Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt  
Tel. +49 (0)7151 6053-0 • Fax +49 (0)7151 6053-277(-288)  
[www.luetze.de](http://www.luetze.de) • [info@luetze.de](mailto:info@luetze.de)

26.04.2024 • Subject to technical modification

Part No. [A2201/003](#) • Datasheet version: 01

page 1 of 4

## Technical data sheet

### Flexible VFD Cable with 3 Symmetrical Grounds for Stationary Applications · shielded

#### Properties

- Flexible XLPE conductors
- Three symmetrical grounds (PE)
- High insulation resistance
- Low capacitance cable
- Effective dual layer shield for EMC compliance
- Specially formulated jacket for oil resistance and easy strip design
- Non-wicking fillers
- Ecolab certified resistance to common cleaning agents and chemicals used in food and beverage washdown procedures
- Crush impact resistant
- Gas/vapor-tight sheath per UL 1277
- Sunlight resistant
- Flame retardant
- Direct burial
- Talc free and silicone free

#### Construction

Description	DRIVEFLEX® 3 SYMMETRICAL GROUNDS
Number of conductors/cross-section	(3×AWG1/0+3×AWG8)
Number of conductors	6
Cross-section, metric	50 mm <sup>2</sup>
Cross-section AWG	1/0
Jacket material	PVC
Jacket color	black RAL 9005
Outer Ø	37.1 mm
Outer Ø	1.462 inch
Weight	1850 Lbs/Mft
Cu-Index	1348 Lbs/Mft

#### Construction Element 1

Element construction	1/0/03C
Conductor	AWG conductor CU-wire tin-plated
Conductor category	fine wire Class K
Conductor marking	black • with white number print
Conductor insulation	XLPE XHHW-2

#### Construction Element 2

Element construction	AWG8/03C
Conductor	AWG conductor CU-wire tin-plated
Conductor category	fine wire
Conductor marking	green/yellow
Conductor insulation	XLPE 3C XHHW-2 (Ground/PEs)

## Technical data sheet

### Flexible VFD Cable with 3 Symmetrical Grounds for Stationary Applications · shielded

#### Overall construction

Drain wire	CU-wire tin-plated
Overall shield	Foil shield
	Aluminium laminate
	Braid shield
	tinned copper wires
	optical cover approx. 80 %
Jacket characteristics	Oil resistant
	Silicone free

#### Technical data

Rated voltage U <sub>N</sub>	600 V TC-ER 1000 V Flexible VFD servo cable 90C 1000 V WTTC
Temperature range fixed	-40 °C ... +90 °C
Minimum bending radius fixed	7.5×D

#### Technical Data Element 1

Element construction	1/0/03C
----------------------	---------

#### Technical Data Element 2

Element construction	AWG8/03C
----------------------	----------

#### Certifications/Standards

Certifications	cULus WTTC TC-ER cUL TC CIC FT4 Meets NEC 336, 392 Class I and II, Div. 2 and Class I Zone 2 per NEC 501, 502, 505 UL 1277 UL 2277 Wet/Dry P-07-KA130021-MSHA
Conformity	CE RoHS REACH TSCA
Oil resistant according to	Oil Res II

#### General

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--

# Technical data sheet

## Flexible VFD Cable with 3 Symmetrical Grounds for Stationary Applications · shielded

### PIN assignment

