

Technical data sheet

LUTZE SILFLEX® M FBP · Shielded

Flexible Motor Cable for Food and Beverage Processing



Identification

Type SI M FBP (C) TPE (4×AWG10)
Part No. [A6061004](#)

Product version

Datasheet version 00

Use/Application/Properties

- Application
- Dual-shielded motor supply cable to connect power to 3-phase-motors, VFDs and servo drives
 - For machine and handling devices in food, beverage and drug processing applications
 - FDA sanctioned jacket material for direct food contact per 21 CFR
 - Compliant with NFPA 79, Article 12.9
 - Suitable for use in food contact zone, splash zone and non-contact zones
 - Thermoset XLPE insulation offers superior electrical values for VFD applications
- Properties
- FDA compliance tested per 21 CFR 175.300
 - REACH 1907/2006/EC compliant
 - Phthalate free jacket
 - Low-capacitance cable
 - High protection against electromagnetic interferences (EMI)
 - Easy stripping and fast installation
 - Easy routing and bending due to flexibility
 - Resistance to most oils and fats
 - Ecolab certified resistance to common cleaning agents and chemicals used in food and beverage washdown procedures
 - Non-wicking fillers
 - Flame-retardant
 - Talc free and silicone free
 - Patented design US-11443871-B2

Construction

Description SILFLEX® M FBP (C) TPE

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0 • Fax +49 (0)7151 6053-277(-288)
www.luetze.de • info@luetze.de

11.07.2023 • Subject to technical modification

Part No. [A6061004](#) • Datasheet version: 00

page 1 of 3

Technical data sheet

LUTZE SILFLEX® M FBP · Shielded

Number of conductors/cross-section	4×AWG10
Number of conductors	4
Cross-section, metric	6 mm ²
Cross-section AWG	AWG 10
Jacket material	Thermoplastic Polymer
Jacket color	black similar to RAL 9005
Outer Ø	16.5 mm
Outer Ø	0.65 inch
Weight	320 Lbs/Mft
Cu-Index	27.2 kg/100 m
Cu-Index	183 Lbs/Mft

Construction Element 1

Element construction	4xAWG10
Conductor	AWG conductor CU-wire tin-plated
Conductor category	fine wire Class K
Conductor marking	black • with white number print • green/yellow
Conductor insulation	XLPE XHHW-2 Wet/Dry

Overall construction

Drain wire	CU-wire tin-plated
Overall shield	aluminium-laminated film shield Braid shield tinned copper wires optical cover approx. 80 %

Technical data

Rated voltage UL	1000 V
Temperature according to UL	90 °C
Temperature range fixed	-40 °C ... +90 °C
Minimum bending radius fixed	6×D

Technical Data Element 1

Element construction	4xAWG10
----------------------	---------

Certifications/Standards

Certifications	21 CFR 175.300 NFPA 79, Artikel 12.9
UL style	AWM 20886

Technical data sheet

LUTZE SILFLEX® M FBP · Shielded

Conformity	CE RoHS REACH TSCA
Burning behavior according to	UL 1581 cable flame

General

Note	CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU
------	--