SIEMENS

## Data sheet 3RH2122-2AB00




contactor relay, 2 NO + 2 NC, 24 V AC, 50/60 Hz, spring-loaded terminal, frame size S00

| | |
|---|---|
| **product brand name** | SIRIUS |
| **product designation** | Auxiliary contactor |
| **product type designation** | 3RH2 |
| **General technical data** | |
| **size of contactor** | S00 |
| product extension auxiliary switch | Yes |
| power loss [W] for rated value of the current without load current share typical | 1.43 W |
| insulation voltage with degree of pollution 3 at AC rated value | 690 V |
| **degree of pollution** | 3 |
| **surge voltage resistance rated value** | 6 kV |
| **shock resistance at rectangular impulse** | |
| ● at AC | 7,3 g / 5 ms, 4,7 g / 10 ms |
| **shock resistance with sine pulse** | |
| ● at AC | 11,4 g / 5 ms, 7,3 g / 10 ms |
| **mechanical service life (operating cycles)** | |
| ● of contactor typical | 30 000 000 |
| ● of the contactor with added electronically optimized auxiliary switch block typical | 5 000 000 |
| ● of the contactor with added auxiliary switch block typical | 10 000 000 |
| **reference code according to IEC 81346-2** | K |
| **Substance Prohibitance (day/month/year)** | 10/01/2009 |
| **Net Weight** | 0.237 kg |
| **Ambient conditions** | |
| installation altitude at height above sea level maximum | 2 000 m |
| **ambient temperature** | |
| ● during operation | -25 ... +60 °C |
| ● during storage | -55 ... +80 °C |
| **relative humidity minimum** | 10 % |
| **relative humidity at 55 °C according to IEC 60068-2-30 maximum** | 95 % |
| **Main circuit** | |
| **no-load switching frequency** | |
| ● at AC | 10 000 1/h |
| ● at DC | 10 000 1/h |
| **Control circuit/ Control** | |
| **type of voltage of the control supply voltage** | AC |
| **control supply voltage at AC** | |
| ● at 50 Hz rated value | 24 V |
| ● at 60 Hz rated value | 24 V |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| **control supply voltage frequency** | |
| ● **1 rated value** | 50 Hz |
| ● **2 rated value** | 60 Hz |
| **operating range factor control supply voltage rated value of magnet coil at AC** | |
| ● at 50 Hz | 0.8 ... 1.1 |
| ● at 60 Hz | 0.85 ... 1.1 |
| **apparent pick-up power of magnet coil at AC** | 37 V·A |
| **inductive power factor with closing power of the coil** | 0.8 |
| **apparent holding power of magnet coil at AC** | 5.7 V·A |
| **inductive power factor with the holding power of the coil** | 0.25 |
| **closing delay** | |
| ● at AC | 8 ... 33 ms |
| **opening delay** | |
| ● at AC | 4 ... 15 ms |
| **arcing time** | 10 ... 15 ms |
| **Auxiliary circuit** | |
| **number of NC contacts for auxiliary contacts** | 2 |
| ● instantaneous contact | 2 |
| **number of NO contacts for auxiliary contacts** | 2 |
| ● instantaneous contact | 2 |
| **identification number and letter for switching elements** | 22 E |
| operational current at AC-12 maximum | 10 A |
| **operational current at AC-15** | |
| ● at 230 V rated value | 10 A |
| ● at 400 V rated value | 3 A |
| ● at 500 V rated value | 2 A |
| ● at 690 V rated value | 1 A |
| **operational current at 1 current path at DC-12** | |
| ● at 24 V rated value | 10 A |
| ● at 60 V rated value | 6 A |
| ● at 110 V rated value | 3 A |
| ● at 220 V rated value | 1 A |
| ● at 440 V rated value | 0.3 A |
| ● at 600 V rated value | 0.15 A |
| **operational current with 2 current paths in series at DC-12** | |
| ● at 24 V rated value | 10 A |
| ● at 60 V rated value | 10 A |
| ● at 110 V rated value | 4 A |
| ● at 220 V rated value | 2 A |
| ● at 440 V rated value | 1.3 A |
| ● at 600 V rated value | 0.65 A |
| **operational current with 3 current paths in series at DC-12** | |
| ● at 24 V rated value | 10 A |
| ● at 60 V rated value | 10 A |
| ● at 110 V rated value | 10 A |
| ● at 220 V rated value | 3.6 A |
| ● at 440 V rated value | 2.5 A |
| ● at 600 V rated value | 1.8 A |
| **operating frequency at DC-12 maximum** | 1 000 1/h |
| **operational current at 1 current path at DC-13** | |
| ● at 24 V rated value | 10 A |
| ● at 60 V rated value | 2 A |
| ● at 110 V rated value | 1 A |
| ● at 220 V rated value | 0.3 A |
| ● at 440 V rated value | 0.14 A |
| ● at 600 V rated value | 0.1 A |
| **operational current with 2 current paths in series at DC-13** | |
| ● at 24 V rated value | 10 A |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| ● at 60 V rated value | 3.5 A |
| ● at 110 V rated value | 1.3 A |
| ● at 220 V rated value | 0.9 A |
| ● at 440 V rated value | 0.2 A |
| ● at 600 V rated value | 0.1 A |
| **operational current with 3 current paths in series at DC-13** | |
| ● at 24 V rated value | 10 A |
| ● at 60 V rated value | 4.7 A |
| ● at 110 V rated value | 3 A |
| ● at 220 V rated value | 1.2 A |
| ● at 440 V rated value | 0.5 A |
| ● at 600 V rated value | 0.26 A |
| **operating frequency at DC-13 maximum** | 1 000 1/h |
| **contact reliability of auxiliary contacts** | 1 faulty switching per 100 million (17 V, 1 mA) |
| **UL/CSA ratings** | |
| **contact rating of auxiliary contacts according to UL** | A600 / Q600 |
| **Short-circuit protection** | |
| design of the miniature circuit breaker for short-circuit protection of the auxiliary circuit up to 230 V | C characteristic: 10 A; 0.4 kA |
| design of the fuse link for short-circuit protection of the auxiliary switch required | gG: 10 A (690 V, 1 kA) |
| **Installation/ mounting/ dimensions** | |
| **mounting position** | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface |
| **fastening method** | screw and snap-on mounting onto 35 mm DIN rail |
| **height** | 70 mm |
| **width** | 45 mm |
| **depth** | 73 mm |
| **required spacing** | |
| ● with side-by-side mounting | |
| — forwards | 10 mm |
| — upwards | 10 mm |
| — downwards | 10 mm |
| — at the side | 0 mm |
| ● for grounded parts | |
| — forwards | 10 mm |
| — upwards | 10 mm |
| — at the side | 6 mm |
| — downwards | 10 mm |
| ● for live parts | |
| — forwards | 10 mm |
| — upwards | 10 mm |
| — downwards | 10 mm |
| — at the side | 6 mm |
| **Connections/ Terminals** | |
| type of electrical connection for auxiliary and control circuit | spring-loaded terminals |
| **type of connectable conductor cross-sections** | |
| ● for auxiliary contacts | |
| — solid or stranded | 2x (0,5 ... 4 mm²) |
| — finely stranded with core end processing | 2x (0.5 ... 2.5 mm²) |
| — finely stranded without core end processing | 2x (0.5 ... 2.5 mm²) |
| ● for AWG cables for auxiliary contacts | 2x (20 ... 12) |
| **Safety related data** | |
| **product function** | |
| **● positively driven operation according to IEC 60947-5-1** | Yes |
| **● suitable for safety function** | Yes |
| **suitability for use safety-related switching OFF** | Yes |
| **service life maximum** | 20 a |
| **proportion of dangerous failures** | |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| • with low demand rate according to SN 31920 | 40 % |
| • with high demand rate according to SN 31920 | 73 % |
| **B10 value with high demand rate according to SN 31920** | 1 000 000; With 0.3 x Ie |
| **failure rate [FIT] with low demand rate according to SN 31920** | 100 FIT |
| ISO 13849 | |
| **device type according to ISO 13849-1** | 3 |
| **overdimensioning according to ISO 13849-2 necessary** | Yes |
| IEC 61508 | |
| **safety device type according to IEC 61508-2** | Type A |
| Electrical Safety | |
| **protection class IP on the front according to IEC 60529** | IP20 |
| **touch protection on the front according to IEC 60529** | finger-safe, for vertical contact from the front |
| **Approvals Certificates** | |
| Environmental Product Declaration | |
| • global warming potential [CO2 eq] / during manufacturing | 1.15 kg |
| • global warming potential [CO2 eq] / during operation | 48.2 kg |
| • global warming potential [CO2 eq] / after end of life | -0.139 kg |
| • global warming potential [CO2 eq] / total | 49.2 kg |

**Environment**

Environmental Confirmations

**General Product Approval**

**General Product Approval** | **EMV** | **Functional Saftey**

Type Examination Certificate

**Test Certificates**

Special Test Certificate | Type Test Certificates/Test Report

**Maritime application**

**Maritime application** | **other** | **Railway**

Confirmation | Miscellaneous | Special Test Certificate

**Further information**

**Information on the packaging**
https://support.industry.siemens.com/cs/ww/en/view/109813875
**Information for data generation and storage**
https://support.industry.siemens.com/cs/ww/en/view/109995012
**Information- and Downloadcenter (Catalogs, Brochures,…)**
https://www.siemens.com/ic10
**Industry Mall (Online ordering system)**
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RH2122-2AB00
**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
https://support.industry.siemens.com/cs/ww/en/ps/3RH2122-2AB00
**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RH2122-2AB00&lang=en
**Cax online generator**
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RH2122-2AB00
**Kennlinien**


© Copyright Siemens

https://curves.simaris.siemens.com/curves/3RH2122-2AB00








© Copyright Siemens




**last modified:** 4/9/2026


Subject to change without notice
© Copyright Siemens