




PSN130S 8 A 120 V/230 V AC IP20 Power supply unit 30 V, for AS-i without AS-i data decoupling IN: 120 V / 230 V AC OUT: 30 V DC, 8 A, IP20 with integrated Overload detection with signaling contact

General technical data		
Type of device		30 V power supply unit IP 20
version		single output
Additional function		Signal contact
input voltage nominal value AC		
• range 1	V	120
• range 2	V	230
Inputs		
input recommended circuit breaker (IEC 898) in the main supply line		10 A, characteristic C
input voltage range		
• voltage range 1 AC	V	85 ... 132
• voltage range 2 AC	V	170 ... 264
input		
• Mains buffering time at I _a rated min		20 ms
• line frequency		50/60 Hz
• Mains frequency range	Hz	47 ... 63
• range changeover using		Automatic range switchover
• input voltage built-in		T 6.3 (not accessible)
Connections input		Screw connection (0.5 ... 2.5 mm ²)
Outputs		
output		
• DC-voltage controlled floating according to AS-Interface specification		yes
• voltage rated value U _a rated DC		30 V
• tolerance total DC	V	29.5 ... 31.6
• rated current I _a rated		8.0 A
• residual ripple peak-to-peak (0-10 kHz, AS-i+/AS-i-) max	mV	150
• spikes peak-to-peak (10-500 kHz, AS-i+/AS-i-) max	mV	150
Connections Output		Screw connection (0.5 ... 2.5 mm ²)
Efficiency/ heat loss		
Efficiency at U _a rated, I _a rated	%	90
Protective and monitoring functions		
Output overvoltage protection		yes (< 37V)
Current limitation from min.		11.0 A
Short-circuit protection		yes
Safety related data		
protection class (EN 60 950/IEC 950)		I
Electrical isolation primary/secondary		ES1 according EN 62368-1 (for products until end of 2020: SELV according to EN 60 950 and EN 50 178)
protection class IP		IP20

Electromagnetic compatibility		
electromagnetic compatibility (EMC)		
- interference immunity - emitted interference		EN 61 000-6-2, EN 61 000-4-2/-3/-4/-5/-11 class B according to EN 55 022, IEC 61 000-6-3
Ambient conditions		
ambient temperature		
- during operation - during storage	°C °C	-20 ... +70 -40 ... +85
humidity rating		climatic class DIN 50010, relative humidity max. 100% without condensation
fastening method		fixing on standard mounting rail DIN EN 59 022-35 x 7.5 mm snap-on
width	mm	70
height	mm	125
depth	mm	125
Environmental footprint		
Environmental Product Declaration(EPD)		Yes
global warming potential [CO2 eq] total	kg	785
global warming potential [CO2 eq] during manufacturing	kg	20.7
global warming potential [CO2 eq] during sales	kg	0.127
global warming potential [CO2 eq] during operation	kg	763
global warming potential [CO2 eq] after end of life	kg	0.565
Certificates/ approvals		
General Product Approval		EMV Maritime application
     		
Maritime application	other	Environment
 	Confirmation	 Environmental Confirmations
Further information		

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/ic10>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RX9513-0AA00>
Cax online generator
<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RX9513-0AA00>
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3RX9513-0AA00>
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RX9513-0AA00&lang=en



last modified:

5/1/2025

