



auxiliary switch, front mounting, 1 NO + 1 NC left and/or right attachable, accessories for 3LD3 switch disconnectors

Model	
product brand name	SETRON
product designation	auxiliary switch
design of the product	accessories for 3LD3 switch disconnectors
operational current	• at AC-15 at 110 V rated value • at AC-15 at 230 V rated value • at AC-15 at 500 V rated value • at DC-13 at 24 V rated value 6 A 3 A 1.4 A 4 A
suitability for use	for 3LD3 front mounting
special product feature	NO: lagging during switching ON, leading during switching OFF the 3LD switch. NC: leading during switching ON, lagging during switching OFF the 3LD switch
Accessories	
accessories	auxiliary switch, 1 NO + 1 NC, can be mounted on the left and/or right
tightening torque with screw-type terminals	• minimum • maximum 0.8 N·m 1.2 N·m
type of connectable conductor cross-sections for auxiliary contacts	• solid • finely stranded with core end processing • stranded 2x (0.75-2.5 mm²), 1x 4 mm² 2x (0.75-2.5 mm²), 1x 4 mm² 2x (0.75-2.5 mm²), 1x 4 mm²
Mechanical Design	
Net Weight	29 g
Approvals Certificates	
Environment	General Product Approval
Environmental Confirmations	Environmental Confirmations
	
CCC	EG-Konf.
	
UL	
General Product Approval	other



[Confirmation](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3LD9340-6B>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3LD9340-6B>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3LD9340-6B

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Characteristic curves

https://curves.simarisiemens.com/curves/<mmp_prod_noCOMP='HAUPT'></mmp_prod_no>



