



SITOP BUF8600/300MS/40A

SITOP BUF8600 300ms buffer module for PSU8600 buffer capacity 300 ms/40 A with electrolytic capacitors maintenance-free

Technical Product Detail Page		https://i.siemens.com/1P6EP4297-8HB10-0XY0
memory		
type of energy storage	electrolytic capacitors	
design of the mains power cut bridging-connection	Backup time with 40 A load current: 300 ms	
buffering time for rated value of the output current in the event of power failure	300 ms	
load time typical	60 s; at 400 V	
output		
output current		
• rated value	40 A	
protection and monitoring		
display version	3-color LED for operating state module	
• for normal operation	LED green for "buffer standby exist"	
• in buffering mode	LED yellow for "buffered mode"	
interfaces		
product function communication function	Yes	
design of the interface	Ethernet/PROFINET via power supply unit PSU8600	
safety		
operating resource protection class	Class III	
protection class IP	IP20	
standard		
• for emitted interference	EN 55022 Class B	
• for interference immunity	EN 61000-6-2	
standards, specifications, approvals		
certificate of suitability		
• CE marking	Yes	
• UL approval	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259	
• EAC approval	Yes	
• SEMI F47	Yes	
type of certification CB-certificate	Yes	
MTBF at 40 °C	4 505 531 h	
standards, specifications, approvals hazardous environments		
certificate of suitability		
• ATEX	No	
standards, specifications, approvals marine classification		
shipbuilding approval	Yes	
Marine classification association		
• American Bureau of Shipping Europe Ltd. (ABS)	Yes	
• Det Norske Veritas (DNV)	Yes	

standards, specifications, approvals Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	<ul style="list-style-type: none"> total 72 kg during manufacturing 35.8 kg during operation 34.7 kg after end of life 0.67 kg
ambient conditions	
ambient temperature	<ul style="list-style-type: none"> during operation -25 ... +60 °C; with natural convection during transport -40 ... +70 °C during storage -40 ... +70 °C
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
connection method	
suitability for interaction modular system	Yes
type of connection to system components	Via integrated connector
mechanical data	
width x height x depth of the enclosure	125 x 125 x 150 mm
installation width x mounting height	125 mm x 225 mm
required spacing	<ul style="list-style-type: none"> top 50 mm bottom 50 mm left 0 mm right 0 mm
fastening method	<ul style="list-style-type: none"> DIN-rail mounting Snaps onto DIN rail EN 60715 35x15 S7 rail mounting Yes wall mounting No
housing can be lined up	Yes
net weight	2.26 kg
accessories	
mechanical accessories	Device identification label 20 mm x 7 mm, TI-grey 3RT2900-1SB20
further information internet links	
internet link	<ul style="list-style-type: none"> to website: Industry Mall https://mall.industry.siemens.com to web page: selection aid TIA Selection Tool https://www.siemens.com/tstcloud to web page: power supplies https://siemens.com/sitop to website: CAx-Download-Manager https://siemens.com/cax to website: Industry Online Support https://support.industry.siemens.com
additional information	
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)
security information	
security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)</p>
Classifications	

	Version	Classification
eClass	14	27-04-07-05
eClass	12	27-04-07-05
eClass	9.1	27-04-07-05
eClass	9	27-04-07-05
eClass	8	27-04-06-90
eClass	7.1	27-04-06-90
eClass	6	27-04-06-90
ETIM	10	EC000382
ETIM	9	EC000382
ETIM	8	EC000382
ETIM	7	EC000382
IDEA	4	4149
UNSPSC	15	39-12-10-11

Approvals Certificates

General Product Approval



[Manufacturer Declaration](#)

[Declaration of Conformity](#)



[China RoHS](#)

General Product Approval

Maritime application

Environment



last modified:

12/4/2025