



SIMATIC ET 200SP, PROFINET, 3-port interface module, IM 155-6PN/3 High Feature, 2 slots for BusAdapter, max. 64 I/O modules and 16 ET 200AL modules, S2 redundancy, multi-hotswap, 0.25 ms, isochronous mode, optional PN strain relief, including server module

General information	
Product type designation	IM 155-6 PN/3 HF
HW functional status	From FS02
Firmware version	V4.2
• FW update possible	Yes
Product function	
• I&M data	Yes; I&M0 to I&M3
• Module swapping during operation (hot swapping)	Yes; Multi-hot swapping
• Isochronous mode	Yes
• Tool changer	Yes; Docking station and docking unit
• Local coupling, IO data	Yes
— Number of coupling modules	16
— Number of coupling submodules per module	4
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V15.1
• STEP 7 configurable/integrated from version	use GSD file
• PROFINET from GSD version/GSD revision	GSDML V2.34
Configuration control	
via dataset	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Short-circuit protection	Yes
Mains buffering	
• Mains/voltage failure stored energy time	10 ms
Input current	
Current consumption (rated value)	175 mA; At 24 V, 2 slots 2x RJ45 BusAdapter, no I/O modules
Current consumption, max.	950 mA
Inrush current, max.	9 A
I^2t	0.34 A ² ·s
Power loss	
Power loss, typ.	4.9 W
Address area	
Address space per module	
• Address space per module, max.	288 byte; For input and output data respectively
Address space per station	
• Address space per station, max.	1 440 byte

Hardware configuration	
Rack	
• Quantity of operable ET 200SP modules, max.	64
• Quantity of operable ET 200AL modules, max.	16
Submodules	
• Number of submodules per station, max.	256
Interfaces	
Number of PROFINET interfaces	1; 3 ports (switch)
1. Interface	
Interface types	
• RJ 45 (Ethernet)	Yes; with BusAdapter
• Number of ports	3; with 2 compatible BusAdapters:
• integrated switch	Yes
• BusAdapter (PROFINET)	Yes; BA 2x RJ45, BA 2x FC, BA 2x SCRJ, BA SCRJ/RJ45, BA SCRJ/FC, BA 2x LC, BA LC/RJ45, BA LC/FC
Protocols	
• PROFINET IO Device	Yes
• Open IE communication	Yes
• Media redundancy	Yes; PROFINET MRP client
PROFINET IO Device	
Services	
— IRT	Yes; 250 µs to 4 ms in 125 µs frame
— PROFIenergy	Yes
— Prioritized startup	Yes
— Shared device	Yes
— Number of IO Controllers with shared device, max.	4
Interface types	
RJ 45 (Ethernet)	
• Transmission procedure	PROFINET with 100 Mbit/s full duplex (100BASE-TX)
• 100 Mbps	Yes
• Autonegotiation	Yes
• Autocrossing	Yes
Protocols	
Supports protocol for PROFINET IO	Yes
PROFIsafe	Yes
PROFIBUS	No
EtherNet/IP	No
Modbus TCP	No
Number of connections	
• Number of MtM communication relationships/connections, max.	16
Redundancy mode	
• PROFINET system redundancy (S2)	Yes; NAP S2
• H-Sync forwarding	Yes
Media redundancy	
— MRP	Yes
— MRPD	No
Open IE communication	
• TCP/IP	Yes
• SNMP	Yes
• LLDP	Yes
Isochronous mode	
Equidistance	Yes
shortest clock pulse	250 µs
max. cycle	4 ms
Bus cycle time (TDP), min.	250 µs
Jitter, max.	1 µs
Interrupts/diagnostics/status information	
Status indicator	Yes

Alarms	Yes		
Diagnostics function	Yes		
Diagnostics indication LED			
• RUN LED	Yes; green LED		
• ERROR LED	Yes; red LED		
• MAINT LED	Yes; Yellow LED		
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED		
• Connection display LINK TX/RX	Yes; 2x green link LEDs on BusAdapter		
Potential separation			
between backplane bus and electronics	No		
between PROFINET and all other circuits	Yes; 1500 V AC (type test)		
between supply and all other circuits	No		
Permissible potential difference			
between different circuits	Safety extra low voltage SELV		
Isolation			
Isolation tested with	707 V DC (type test)		
Standards, approvals, certificates			
Network loading class	3		
Ambient conditions			
Ambient temperature during operation			
• horizontal installation, min.	-30 °C; No condensation		
• horizontal installation, max.	60 °C		
• vertical installation, min.	-30 °C; No condensation		
• vertical installation, max.	50 °C		
Altitude during operation relating to sea level			
• Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual		
Connection method			
ET-Connection			
• via BU/BA Send	Yes; + 16 ET 200AL modules		
Mechanics/material			
Strain relief	Yes; Optional		
Dimensions			
Width	100 mm		
Height	117 mm		
Depth	74 mm		
Weights			
Weight, approx.	220 g; without BusAdapter		
Classifications			
		Version	Classification
	eClass	14	27-24-26-08
	eClass	12	27-24-26-08
	eClass	9.1	27-24-26-08
	eClass	9	27-24-26-08
	eClass	8	27-24-26-08
	eClass	7.1	27-24-26-08
	eClass	6	27-24-26-08
	ETIM	10	EC001604
	ETIM	9	EC001604
	ETIM	8	EC001604
	ETIM	7	EC001604
	IDEA	4	3564
	UNSPSC	15	32-15-17-05
Approvals / Certificates			
General Product Approval			



[Miscellaneous](#)

[Manufacturer Declaration](#)

[China RoHS](#)

[PROFINET](#)

General Product Approval

For use in hazardous locations



[EM](#)

[CCC-Ex](#)

For use in hazardous locations

Maritime application



[Type Examination Certificate](#)



[Miscellaneous](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

Maritime application

Industrial Communication



[PROFINET](#)

last modified:

10/23/2025