

product type designation	IE FC TP Trailing Cable GP 4X2 (AWG 24, Type C)
product description	Shielded TP installation cable (8-core), sold by the meter, unassembled IE FC TP Trailing Cable GP 4x2 TP installation cable CAT6A AWG 24, for connection to IE FC RJ45 plug 4x 2, AWG24, sold by the meter, delivery unit max. 1000 m minimum order quantity 20 m.
Technical Product Detail Page	https://i.siemens.com/1P6XV1878-2C
suitability for use	Flexible cable for fast installation, for installation in trailing cables
cable designation	SF/UTP, 2YH(ST)C11Y 4X2X0.6/1.04-100 LI GN
wire length	sold by the meter
electrical data	
attenuation factor per length	
• at 10 MHz / maximum	0.089 dB/m
• at 100 MHz / maximum	0.287 dB/m
• at 250 MHz / maximum	0.466 dB/m
• at 300 MHz / maximum	0.514 dB/m
• at 500 MHz / maximum	0.679 dB/m
impedance	
• at 1 MHz ... 100 MHz	100 Ω
near-end crosstalk per length	
• at 1 MHz ... 100 MHz	0.453 dB/m
• at 1 MHz ... 250 MHz	0.393 dB/m
• at 1 MHz ... 300 MHz	0.381 dB/m
• at 1 MHz ... 500 MHz	0.348 dB/m
coupling loss / at 30 MHz ... 100 MHz / minimum	80 dB
transfer impedance per length / at 10 MHz	80 mΩ/m
loop resistance per length / maximum	180 mΩ/m
insulation resistance coefficient	5000 GΩ·m
operating voltage	
• RMS value	80 V
• maximum	80 V
NVP value in percent	69 %
mechanical data	
number of electrical cores	8
design of the shield	SF/UTP, overlapped aluminum-clad foil, sheathed in a protective braided shield of tinned copper wires
type of electrical connection / FastConnect	Yes
core diameter	
• of AWG24 insulated conductor	0.51 mm
outer diameter	
• of inner conductor	0.58 mm
• of the wire insulation	1.04 mm
• of the inner sheath of the cable	6.5 mm
• of cable sheath	8 mm
symmetrical tolerance of the outer diameter / of cable sheath	0.2 mm
material	
• of the wire insulation	polyethylene (PE)
• of the inner sheath of the cable	FRNC
• of cable sheath	PUR
color	
• of the insulation of data wires	white-blue/blue, white-orange/orange, white-green/green, white-brown/brown
• of cable sheath	green
bending radius	

<ul style="list-style-type: none"> • with single bend / minimum permissible • with multiple bends / minimum permissible • with continuous bending 	<p>32 mm</p> <p>64 mm</p> <p>120 mm</p>
number of bending cycles	1000000; For use in trailing cables, with a bending radius of 120 mm, a speed of 4 m/s, and an acceleration of 4 m/s ²
tensile load / maximum	100 N
weight per length	102 kg/km
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> • during operation • during storage • during transport • during installation • note 	<p>-30 ... +70 °C</p> <p>-40 ... +80 °C</p> <p>-40 ... +80 °C</p> <p>-30 ... +70 °C</p> <p>In fixed installation -40 °C to 80 °C</p>
fire behavior	flame resistant according to IEC 60332-1-2
class of burning behaviour / according to EN 13501-6	Eca
chemical resistance	
<ul style="list-style-type: none"> • to mineral oil • to grease • to water 	<p>oil resistant according to IEC 60811-404 (7x24h/90°C)</p> <p>Conditional resistance</p> <p>conditional resistance</p>
radiological resistance / to UV radiation	resistant
product features, product functions, product components / general	
product feature	
<ul style="list-style-type: none"> • halogen-free • PoE capability • PoE+ capability • PoE++ capability • silicon-free 	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p>
wire length / for Industrial Ethernet	
<ul style="list-style-type: none"> • with 100BaseTX • with 1000BaseT • for 10GBase T 	<p>100 m</p> <p>100 m</p> <p>80 m</p>
test voltage	
<ul style="list-style-type: none"> • at AC / core-to-core • at AC / core shield 	<p>2000 V</p> <p>2000 V</p>
standards, specifications, approvals	
UL/ETL listing / 300 V Rating	Yes; c(ETL)us CMX, AWM-Style 21329
UL/ETL style / 600 V Rating	Yes
certificate of suitability	
<ul style="list-style-type: none"> • EAC approval • CE marking • RoHS conformity 	<p>Yes</p> <p>Yes</p> <p>Yes</p>
product conformity	
<ul style="list-style-type: none"> • ANSI/TIA-EIA 568-B.2 Cat.5e • IEC 61784-5-2-CP 2/2 (Ethernet/IP) 	<p>No</p> <p>Yes</p>
standard for structured cabling	Cat6A
<ul style="list-style-type: none"> • resistance to air pollution / conformity according to ANSI/ISA-71.04 	Yes; G3
Marine classification association	
<ul style="list-style-type: none"> • American Bureau of Shipping Europe Ltd. (ABS) • French marine classification society (BV) • Det Norske Veritas (DNV) • Germanische Lloyd (GL) • Lloyds Register of Shipping (LRS) • Nippon Kaiji Kyokai (NK) • Polski Rejestr Statkow (PRS) 	<p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p> <p>No</p>
further information / internet links	
internet link	

- to website: Selection guide for cables and connectors
- to web page: selection aid TIA Selection Tool
- to web page: SiePortal
- to website: Image database
- to website: CAx-Download-Manager
- to website: Industry Online Support

- <https://support.industry.siemens.com/cs/ww/en/view/109766358>
- <https://www.siemens.com/tstcloud>
- <https://sieportal.siemens.com/>
- <https://www.automation.siemens.com/bilddb>
- <https://www.siemens.com/cax>
- <https://support.industry.siemens.com>

security information

security information

Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Approvals / Certificates

General Product Approval



[Manufacturer Declaration](#)

[China RoHS](#)

[Fire safety / Physical security](#)

General Product Approval	other	Environment	Industrial Communication
--------------------------	-------	-------------	--------------------------

[Declaration of Conformity](#)

[Miscellaneous](#)

[Environmental Conformations](#)

[PROFINET](#)

last modified:

3/10/2026