



power contactor, AC-3e/AC-3, 95 A, 45 kW / 400 V, 3-pole, 48 V AC, 50 Hz, auxiliary contacts: 1 NO + 1 NC, screw terminal, size: S3

|                                                                                                              |                               |
|--------------------------------------------------------------------------------------------------------------|-------------------------------|
| product brand name                                                                                           | SIRIUS                        |
| product designation                                                                                          | Power contactor               |
| product type designation                                                                                     | 3RT2                          |
| <b>General technical data</b>                                                                                |                               |
| size of contactor                                                                                            | S3                            |
| product extension                                                                                            |                               |
| • function module for communication                                                                          | No                            |
| • auxiliary switch                                                                                           | Yes                           |
| power loss [W] for rated value of the current                                                                |                               |
| • at AC in hot operating state                                                                               | 19.8 W                        |
| • at AC in hot operating state per pole                                                                      | 6.6 W                         |
| • without load current share typical                                                                         | 7.3 W                         |
| type of calculation of power loss current-dependent                                                          | quadratic                     |
| insulation voltage                                                                                           |                               |
| • of main circuit with degree of pollution 3 rated value                                                     | 1 000 V                       |
| • of auxiliary circuit with degree of pollution 3 rated value                                                | 690 V                         |
| surge voltage resistance                                                                                     |                               |
| • of main circuit rated value                                                                                | 8 kV                          |
| • of auxiliary circuit rated value                                                                           | 6 kV                          |
| maximum permissible voltage for protective separation between coil and main contacts according to EN 60947-1 | 690 V                         |
| shock resistance at rectangular impulse                                                                      |                               |
| • at AC                                                                                                      | 10.3 g / 5 ms, 6.7 g / 10 ms  |
| shock resistance with sine pulse                                                                             |                               |
| • at AC                                                                                                      | 16.3 g / 5 ms, 10.5 g / 10 ms |
| mechanical service life (operating cycles)                                                                   |                               |
| • of contactor typical                                                                                       | 10 000 000                    |
| • of the contactor with added electronically optimized auxiliary switch block typical                        | 5 000 000                     |
| • of the contactor with added auxiliary switch block typical                                                 | 10 000 000                    |
| reference code according to IEC 81346-2                                                                      | Q                             |
| Substance Prohibitance (day/month/year)                                                                      | 03/01/2017                    |
| Net Weight                                                                                                   | 1.702 kg                      |
| <b>Ambient conditions</b>                                                                                    |                               |
| installation altitude at height above sea level maximum                                                      | 2 000 m                       |
| ambient temperature                                                                                          |                               |
| • during operation                                                                                           | -25 ... +60 °C                |
| • during storage                                                                                             | -55 ... +80 °C                |
| relative humidity minimum                                                                                    | 10 %                          |
| relative humidity at 55 °C according to IEC 60068-2-30                                                       | 95 %                          |

|                                                                   |                    |
|-------------------------------------------------------------------|--------------------|
| maximum                                                           |                    |
| <b>Main circuit</b>                                               |                    |
| number of poles for main current circuit                          | 3                  |
| number of NO contacts for main contacts                           | 3                  |
| number of NC contacts for main contacts                           | 0                  |
| operating voltage                                                 |                    |
| • at AC-3 rated value maximum                                     | 1 000 V            |
| • at AC-3e rated value maximum                                    | 1 000 V            |
| operational current                                               |                    |
| • at AC-1 at 400 V at ambient temperature 40 °C rated value       | 130 A              |
| • at AC-1                                                         |                    |
| — up to 690 V at ambient temperature 40 °C rated value            | 130 A              |
| — up to 690 V at ambient temperature 60 °C rated value            | 110 A              |
| • at AC-3                                                         |                    |
| — at 400 V rated value                                            | 95 A               |
| — at 500 V rated value                                            | 95 A               |
| — at 690 V rated value                                            | 78 A               |
| — at 1000 V rated value                                           | 30 A               |
| • at AC-3e                                                        |                    |
| — at 400 V rated value                                            | 95 A               |
| — at 500 V rated value                                            | 95 A               |
| — at 690 V rated value                                            | 78 A               |
| — at 1000 V rated value                                           | 30 A               |
| • at AC-4 at 400 V rated value                                    | 80 A               |
| • at AC-5a up to 690 V rated value                                | 114 A              |
| • at AC-5b up to 400 V rated value                                | 95 A               |
| • at AC-6a                                                        |                    |
| — up to 230 V for current peak value n=20 rated value             | 84.4 A             |
| — up to 400 V for current peak value n=20 rated value             | 84.4 A             |
| — up to 500 V for current peak value n=20 rated value             | 84.4 A             |
| — up to 690 V for current peak value n=20 rated value             | 58 A               |
| • at AC-6a                                                        |                    |
| — up to 230 V for current peak value n=30 rated value             | 56.3 A             |
| — up to 400 V for current peak value n=30 rated value             | 56.3 A             |
| — up to 500 V for current peak value n=30 rated value             | 56.3 A             |
| — up to 690 V for current peak value n=30 rated value             | 56.3 A             |
| minimum cross-section in main circuit at maximum AC-1 rated value | 50 mm <sup>2</sup> |
| operational current for approx. 200000 operating cycles at AC-4   |                    |
| • at 400 V rated value                                            | 42 A               |
| • at 690 V rated value                                            | 30 A               |
| operational current                                               |                    |
| • at 1 current path at DC-1                                       |                    |
| — at 24 V rated value                                             | 100 A              |
| — at 60 V rated value                                             | 60 A               |
| — at 110 V rated value                                            | 9 A                |
| — at 220 V rated value                                            | 2 A                |
| — at 440 V rated value                                            | 0.6 A              |
| — at 600 V rated value                                            | 0.4 A              |
| • with 2 current paths in series at DC-1                          |                    |
| — at 24 V rated value                                             | 100 A              |
| — at 60 V rated value                                             | 100 A              |
| — at 110 V rated value                                            | 100 A              |
| — at 220 V rated value                                            | 10 A               |
| — at 440 V rated value                                            | 1.8 A              |
| — at 600 V rated value                                            | 1 A                |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                              |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>● with 3 current paths in series at DC-1 <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> <li>● at 1 current path at DC-3 at DC-5 <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> <li>● with 2 current paths in series at DC-3 at DC-5 <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> <li>● with 3 current paths in series at DC-3 at DC-5 <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> </ul> | 100 A<br>100 A<br>100 A<br>80 A<br>4.5 A<br>2.6 A<br><br>40 A<br>6 A<br>2.5 A<br>1 A<br>0.15 A<br>0.06 A<br><br>100 A<br>100 A<br>100 A<br>7 A<br>0.42 A<br>0.16 A<br><br>100 A<br>100 A<br>100 A<br>35 A<br>0.8 A<br>0.35 A |
| <b>operating power</b> <ul style="list-style-type: none"> <li>● at AC-2 at 400 V rated value</li> <li>● at AC-3 <ul style="list-style-type: none"> <li>— at 230 V rated value</li> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> <li>— at 1000 V rated value</li> </ul> </li> <li>● at AC-3e <ul style="list-style-type: none"> <li>— at 230 V rated value</li> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> <li>— at 1000 V rated value</li> </ul> </li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 45 kW<br><br>22 kW<br>45 kW<br>55 kW<br>75 kW<br>37 kW<br><br>22 kW<br>45 kW<br>55 kW<br>75 kW<br>37 kW                                                                                                                      |
| <b>operating power for approx. 200000 operating cycles at AC-4</b> <ul style="list-style-type: none"> <li>● at 400 V rated value</li> <li>● at 690 V rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 22 kW<br>27.4 kW                                                                                                                                                                                                             |
| <b>operating apparent power at AC-6a</b> <ul style="list-style-type: none"> <li>● up to 230 V for current peak value n=20 rated value</li> <li>● up to 400 V for current peak value n=20 rated value</li> <li>● up to 500 V for current peak value n=20 rated value</li> <li>● up to 690 V for current peak value n=20 rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 33 kVA<br>58 kVA<br>73 kVA<br>69 kVA                                                                                                                                                                                         |
| <b>operating apparent power at AC-6a</b> <ul style="list-style-type: none"> <li>● up to 230 V for current peak value n=30 rated value</li> <li>● up to 400 V for current peak value n=30 rated value</li> <li>● up to 500 V for current peak value n=30 rated value</li> <li>● up to 690 V for current peak value n=30 rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 22.4 kVA<br>39 kVA<br>48.7 kVA<br>67.3 kVA                                                                                                                                                                                   |
| <b>short-time withstand current in cold operating state up to 40 °C</b> <ul style="list-style-type: none"> <li>● limited to 1 s switching at zero current maximum</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 1 725 A; Use minimum cross-section acc. to AC-1 rated value                                                                                                                                                                  |

|                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                    |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• limited to 5 s switching at zero current maximum</li> <li>• limited to 10 s switching at zero current maximum</li> <li>• limited to 30 s switching at zero current maximum</li> <li>• limited to 60 s switching at zero current maximum</li> </ul> | 1 297 A; Use minimum cross-section acc. to AC-1 rated value<br>946 A; Use minimum cross-section acc. to AC-1 rated value<br>610 A; Use minimum cross-section acc. to AC-1 rated value<br>486 A; Use minimum cross-section acc. to AC-1 rated value |
| <b>no-load switching frequency</b>                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• at AC</li> </ul>                                                                                                                                                                                                                                   | 5 000 1/h                                                                                                                                                                                                                                          |
| <b>operating frequency</b>                                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• at AC-1 maximum</li> </ul>                                                                                                                                                                                                                         | 900 1/h                                                                                                                                                                                                                                            |
| <ul style="list-style-type: none"> <li>• at AC-2 maximum</li> </ul>                                                                                                                                                                                                                         | 350 1/h                                                                                                                                                                                                                                            |
| <ul style="list-style-type: none"> <li>• at AC-3 maximum</li> </ul>                                                                                                                                                                                                                         | 850 1/h                                                                                                                                                                                                                                            |
| <ul style="list-style-type: none"> <li>• at AC-3e</li> <li>— maximum</li> </ul>                                                                                                                                                                                                             | 850 1/h                                                                                                                                                                                                                                            |
| <ul style="list-style-type: none"> <li>• at AC-4 maximum</li> </ul>                                                                                                                                                                                                                         | 250 1/h                                                                                                                                                                                                                                            |
| <b>Control circuit/ Control</b>                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                    |
| <b>type of voltage of the control supply voltage</b>                                                                                                                                                                                                                                        | AC                                                                                                                                                                                                                                                 |
| <b>control supply voltage at AC</b>                                                                                                                                                                                                                                                         |                                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• at 50 Hz rated value</li> </ul>                                                                                                                                                                                                                    | 48 V                                                                                                                                                                                                                                               |
| <b>operating range factor control supply voltage rated value of magnet coil at AC</b>                                                                                                                                                                                                       |                                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul>                                                                                                                                                                                                                                | 0.8 ... 1.1                                                                                                                                                                                                                                        |
| <b>apparent pick-up power of magnet coil at AC</b>                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul>                                                                                                                                                                                                                                | 296 VA                                                                                                                                                                                                                                             |
| <b>inductive power factor with closing power of the coil</b>                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul>                                                                                                                                                                                                                                | 0.61                                                                                                                                                                                                                                               |
| <b>apparent holding power of magnet coil at AC</b>                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul>                                                                                                                                                                                                                                | 19 VA                                                                                                                                                                                                                                              |
| <b>inductive power factor with the holding power of the coil</b>                                                                                                                                                                                                                            |                                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> </ul>                                                                                                                                                                                                                                | 0.38                                                                                                                                                                                                                                               |
| <b>closing delay</b>                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• at AC</li> </ul>                                                                                                                                                                                                                                   | 13 ... 50 ms                                                                                                                                                                                                                                       |
| <b>opening delay</b>                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• at AC</li> </ul>                                                                                                                                                                                                                                   | 10 ... 21 ms                                                                                                                                                                                                                                       |
| <b>arcing time</b>                                                                                                                                                                                                                                                                          | 10 ... 20 ms                                                                                                                                                                                                                                       |
| <b>control version of the switch operating mechanism</b>                                                                                                                                                                                                                                    | Standard A1 - A2                                                                                                                                                                                                                                   |
| <b>Auxiliary circuit</b>                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                    |
| number of NC contacts for auxiliary contacts instantaneous contact                                                                                                                                                                                                                          | 1                                                                                                                                                                                                                                                  |
| number of NO contacts for auxiliary contacts instantaneous contact                                                                                                                                                                                                                          | 1                                                                                                                                                                                                                                                  |
| operational current at AC-12 maximum                                                                                                                                                                                                                                                        | 10 A                                                                                                                                                                                                                                               |
| <b>operational current at AC-15</b>                                                                                                                                                                                                                                                         |                                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• at 230 V rated value</li> </ul>                                                                                                                                                                                                                    | 6 A                                                                                                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>• at 400 V rated value</li> </ul>                                                                                                                                                                                                                    | 3 A                                                                                                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>• at 500 V rated value</li> </ul>                                                                                                                                                                                                                    | 2 A                                                                                                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>• at 690 V rated value</li> </ul>                                                                                                                                                                                                                    | 1 A                                                                                                                                                                                                                                                |
| <b>operational current at DC-12</b>                                                                                                                                                                                                                                                         |                                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• at 24 V rated value</li> </ul>                                                                                                                                                                                                                     | 10 A                                                                                                                                                                                                                                               |
| <ul style="list-style-type: none"> <li>• at 48 V rated value</li> </ul>                                                                                                                                                                                                                     | 6 A                                                                                                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>• at 60 V rated value</li> </ul>                                                                                                                                                                                                                     | 6 A                                                                                                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>• at 110 V rated value</li> </ul>                                                                                                                                                                                                                    | 3 A                                                                                                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>• at 125 V rated value</li> </ul>                                                                                                                                                                                                                    | 2 A                                                                                                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>• at 220 V rated value</li> </ul>                                                                                                                                                                                                                    | 1 A                                                                                                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>• at 600 V rated value</li> </ul>                                                                                                                                                                                                                    | 0.15 A                                                                                                                                                                                                                                             |
| <b>operational current at DC-13</b>                                                                                                                                                                                                                                                         |                                                                                                                                                                                                                                                    |
| <ul style="list-style-type: none"> <li>• at 24 V rated value</li> </ul>                                                                                                                                                                                                                     | 10 A                                                                                                                                                                                                                                               |
| <ul style="list-style-type: none"> <li>• at 48 V rated value</li> </ul>                                                                                                                                                                                                                     | 2 A                                                                                                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>• at 60 V rated value</li> </ul>                                                                                                                                                                                                                     | 2 A                                                                                                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>• at 110 V rated value</li> </ul>                                                                                                                                                                                                                    | 1 A                                                                                                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>• at 125 V rated value</li> </ul>                                                                                                                                                                                                                    | 0.9 A                                                                                                                                                                                                                                              |
| <ul style="list-style-type: none"> <li>• at 220 V rated value</li> </ul>                                                                                                                                                                                                                    | 0.3 A                                                                                                                                                                                                                                              |

|                                                                                                           |                                                                                                                                      |
|-----------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| • at 600 V rated value                                                                                    | 0.1 A                                                                                                                                |
| <b>contact reliability of auxiliary contacts</b>                                                          | 1 faulty switching per 100 million (17 V, 1 mA)                                                                                      |
| <b>UL/CSA ratings</b>                                                                                     |                                                                                                                                      |
| <b>full-load current (FLA) for 3-phase AC motor</b>                                                       |                                                                                                                                      |
| • at 480 V rated value                                                                                    | 96 A                                                                                                                                 |
| • at 600 V rated value                                                                                    | 77 A                                                                                                                                 |
| <b>yielded mechanical performance [hp]</b>                                                                |                                                                                                                                      |
| • for single-phase AC motor                                                                               |                                                                                                                                      |
| — at 110/120 V rated value                                                                                | 10 hp                                                                                                                                |
| — at 230 V rated value                                                                                    | 20 hp                                                                                                                                |
| • for 3-phase AC motor                                                                                    |                                                                                                                                      |
| — at 200/208 V rated value                                                                                | 30 hp                                                                                                                                |
| — at 220/230 V rated value                                                                                | 30 hp                                                                                                                                |
| — at 460/480 V rated value                                                                                | 75 hp                                                                                                                                |
| — at 575/600 V rated value                                                                                | 75 hp                                                                                                                                |
| <b>contact rating of auxiliary contacts according to UL</b>                                               | A600 / P600                                                                                                                          |
| <b>Short-circuit protection</b>                                                                           |                                                                                                                                      |
| design of the miniature circuit breaker for short-circuit protection of the auxiliary circuit up to 230 V | C characteristic: 10 A; 0.4 kA                                                                                                       |
| <b>design of the fuse link</b>                                                                            |                                                                                                                                      |
| • for short-circuit protection of the main circuit                                                        |                                                                                                                                      |
| — with type of coordination 1 required                                                                    | gG: 250 A (690 V, 100 kA), aM: 160 A (690 V, 100 kA), BS88: 200 A (415 V, 80 kA)                                                     |
| — with type of coordination 2 required                                                                    | gG: 160 A (690 V, 100 kA), aM: 100 A (690 V, 100 kA), BS88: 125 A (415 V, 80 kA)                                                     |
| • for short-circuit protection of the auxiliary switch required                                           | gG: 10 A (500 V, 1 kA)                                                                                                               |
| <b>Installation/ mounting/ dimensions</b>                                                                 |                                                                                                                                      |
| <b>mounting position</b>                                                                                  | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface |
| fastening method side-by-side mounting                                                                    | Yes                                                                                                                                  |
| <b>fastening method</b>                                                                                   | screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 60715                                                             |
| <b>height</b>                                                                                             | 140 mm                                                                                                                               |
| <b>width</b>                                                                                              | 70 mm                                                                                                                                |
| <b>depth</b>                                                                                              | 152 mm                                                                                                                               |
| <b>required spacing</b>                                                                                   |                                                                                                                                      |
| • with side-by-side mounting                                                                              |                                                                                                                                      |
| — forwards                                                                                                | 20 mm                                                                                                                                |
| — upwards                                                                                                 | 10 mm                                                                                                                                |
| — downwards                                                                                               | 10 mm                                                                                                                                |
| — at the side                                                                                             | 0 mm                                                                                                                                 |
| • for grounded parts                                                                                      |                                                                                                                                      |
| — forwards                                                                                                | 20 mm                                                                                                                                |
| — upwards                                                                                                 | 10 mm                                                                                                                                |
| — at the side                                                                                             | 10 mm                                                                                                                                |
| — downwards                                                                                               | 10 mm                                                                                                                                |
| • for live parts                                                                                          |                                                                                                                                      |
| — forwards                                                                                                | 20 mm                                                                                                                                |
| — upwards                                                                                                 | 10 mm                                                                                                                                |
| — downwards                                                                                               | 10 mm                                                                                                                                |
| — at the side                                                                                             | 10 mm                                                                                                                                |
| <b>Connections/ Terminals</b>                                                                             |                                                                                                                                      |
| <b>type of electrical connection</b>                                                                      |                                                                                                                                      |
| • for main current circuit                                                                                | screw-type terminals                                                                                                                 |
| • for auxiliary and control circuit                                                                       | screw-type terminals                                                                                                                 |
| • at contactor for auxiliary contacts                                                                     | Screw-type terminals                                                                                                                 |
| • of magnet coil                                                                                          | Screw-type terminals                                                                                                                 |
| <b>type of connectable conductor cross-sections</b>                                                       |                                                                                                                                      |
| • for main contacts                                                                                       |                                                                                                                                      |
| — finely stranded with core end processing                                                                | 2x (2.5 ... 35 mm²), 1x (2.5 ... 50 mm²)                                                                                             |
| • for AWG cables for main contacts                                                                        | 2x (10 ... 1/0), 1x (10 ... 2/0)                                                                                                     |

|                                                                                           |                                                                       |
|-------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|
| <b>connectable conductor cross-section for main contacts</b>                              |                                                                       |
| • solid                                                                                   | 2.5 ... 16 mm <sup>2</sup>                                            |
| • stranded                                                                                | 6 ... 70 mm <sup>2</sup>                                              |
| • finely stranded with core end processing                                                | 2.5 ... 50 mm <sup>2</sup>                                            |
| <b>connectable conductor cross-section for auxiliary contacts</b>                         |                                                                       |
| • solid or stranded                                                                       | 0.5 ... 2.5 mm <sup>2</sup>                                           |
| • finely stranded with core end processing                                                | 0.5 ... 2.5 mm <sup>2</sup>                                           |
| <b>type of connectable conductor cross-sections</b>                                       |                                                                       |
| • for auxiliary contacts                                                                  |                                                                       |
| — solid or stranded                                                                       | 2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> ) |
| — finely stranded with core end processing                                                | 2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> ) |
| • for AWG cables for auxiliary contacts                                                   | 2x (20 ... 16), 2x (18 ... 14)                                        |
| <b>AWG number extended as coded connectable conductor cross section for main contacts</b> | 10 ... 2/0                                                            |
| <b>AWG number as coded connectable conductor cross section for auxiliary contacts</b>     | 20 ... 14                                                             |

#### Safety related data

|                                                                      |           |
|----------------------------------------------------------------------|-----------|
| <b>product function</b>                                              |           |
| • mirror contact according to IEC 60947-4-1                          | Yes       |
| • positively driven operation according to IEC 60947-5-1             | No        |
| • suitable for safety function                                       | Yes       |
| suitability for use safety-related switching OFF                     | Yes       |
| <b>service life maximum</b>                                          | 20 a      |
| <b>test wear-related service life necessary</b>                      | Yes       |
| <b>proportion of dangerous failures</b>                              |           |
| • with low demand rate according to SN 31920                         | 40 %      |
| • with high demand rate according to SN 31920                        | 73 %      |
| <b>B10 value with high demand rate according to SN 31920</b>         | 1 000 000 |
| <b>failure rate [FIT] with low demand rate according to SN 31920</b> | 100 FIT   |

#### ISO 13849

|                                                            |     |
|------------------------------------------------------------|-----|
| <b>device type according to ISO 13849-1</b>                | 3   |
| <b>overdimensioning according to ISO 13849-2 necessary</b> | Yes |

#### IEC 61508

|                                                    |        |
|----------------------------------------------------|--------|
| <b>safety device type according to IEC 61508-2</b> | Type A |
|----------------------------------------------------|--------|

#### Electrical Safety

|                                                                |                                                  |
|----------------------------------------------------------------|--------------------------------------------------|
| <b>protection class IP on the front according to IEC 60529</b> | IP20                                             |
| <b>touch protection on the front according to IEC 60529</b>    | finger-safe, for vertical contact from the front |

#### Approvals Certificates

##### Environmental Product Declaration

|                                                            |          |
|------------------------------------------------------------|----------|
| • global warming potential [CO2 eq] / during manufacturing | 7.66 kg  |
| • global warming potential [CO2 eq] / during operation     | 399 kg   |
| • global warming potential [CO2 eq] / after end of life    | -1.19 kg |
| • global warming potential [CO2 eq] / total                | 405 kg   |

#### Environment General Product Approval

[Environmental Confirmations](#)



#### General Product Approval EMV Test Certificates



[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

#### Maritime application



| other | Railway | Dangerous goods |
|-------|---------|-----------------|
|-------|---------|-----------------|

[Confirmation](#)



[Special Test Certificate](#)

[Transport Information](#)

#### Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2046-1AH00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2046-1AH00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)




[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT2046-1AH00&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2046-1AH00&lang=en)


Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2046-1AH00>

Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP='HAUPT'></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP='HAUPT'></mmp_prod_no>)





last modified:

4/4/2026 