



Circuit breaker size S2 for motor protection, Class 20 A-release 54...65 A N-release 845 A screw terminal Standard switching capacity

|                                                                                                |                        |
|------------------------------------------------------------------------------------------------|------------------------|
| product brand name                                                                             | SIRIUS                 |
| product designation                                                                            | Circuit breaker        |
| design of the product                                                                          | For motor protection   |
| product type designation                                                                       | 3RV2                   |
| <b>General technical data</b>                                                                  |                        |
| Product equipment of circuit breaker for motor protection complete unit with protection device | Yes                    |
| size of the circuit-breaker                                                                    | S2                     |
| size of contactor can be combined company-specific                                             | S2                     |
| product function disconnecter functionality                                                    | Yes                    |
| product extension auxiliary switch                                                             | Yes                    |
| power loss [W] for rated value of the current                                                  |                        |
| • at AC in hot operating state                                                                 | 26 W                   |
| • at AC in hot operating state per pole                                                        | 8.7 W                  |
| type of calculation of power loss current-dependent                                            | quadratic              |
| insulation voltage with degree of pollution 3 at AC rated value                                | 690 V                  |
| surge voltage resistance rated value                                                           | 6 kV                   |
| maximum permissible voltage for protective separation                                          |                        |
| • in networks with ungrounded star point between main and auxiliary circuit                    | 400 V                  |
| • in networks with grounded star point between main and auxiliary circuit                      | 400 V                  |
| protection class IP                                                                            |                        |
| • on the front according to IEC 60529                                                          | IP20                   |
| • on the front                                                                                 | IP20                   |
| • of the terminal                                                                              | IP00                   |
| shock resistance according to IEC 60068-2-27                                                   | 25 g / 11 ms Sinus     |
| mechanical service life (operating cycles)                                                     |                        |
| • of the main contacts typical                                                                 | 20 000                 |
| • of auxiliary contacts typical                                                                | 20 000                 |
| electrical endurance (operating cycles) typical                                                | 20 000                 |
| reference code according to IEC 81346-2                                                        | Q                      |
| continuous current rated value                                                                 | 65 A                   |
| Substance Prohibitance (day/month/year)                                                        | 04/10/2015             |
| SVHC substance name                                                                            | Lead CAS-No. 7439-92-1 |
| Net Weight                                                                                     | 1.22 kg                |
| <b>Ambient conditions</b>                                                                      |                        |

|                                                                                            |                |
|--------------------------------------------------------------------------------------------|----------------|
| installation altitude at height above sea level maximum                                    | 2 000 m        |
| <b>ambient temperature</b>                                                                 |                |
| • during operation                                                                         | -20 ... +60 °C |
| • during storage                                                                           | -50 ... +80 °C |
| • during transport                                                                         | -50 ... +80 °C |
| <b>temperature compensation</b>                                                            | -20 ... +60 °C |
| relative humidity during operation                                                         | 10 ... 95 %    |
| <b>Main circuit</b>                                                                        |                |
| <b>number of poles for main current circuit</b>                                            | 3              |
| <b>adjustable current response value current of the current-dependent overload release</b> | 54 ... 65 A    |
| <b>type of voltage for main current circuit</b>                                            | AC             |
| <b>operating voltage</b>                                                                   |                |
| • rated value                                                                              | 690 V          |
| • rated value                                                                              | 20 ... 690 V   |
| • at AC-3 rated value maximum                                                              | 690 V          |
| • at AC-3e rated value maximum                                                             | 690 V          |
| <b>operating frequency rated value</b>                                                     | 50 ... 60 Hz   |
| <b>operational current rated value</b>                                                     | 65 A           |
| <b>operational current</b>                                                                 |                |
| • at AC-3 at 400 V rated value                                                             | 65 A           |
| • at AC-3e at 400 V rated value                                                            | 65 A           |
| <b>operating power</b>                                                                     |                |
| • at AC-3                                                                                  |                |
| — at 230 V rated value                                                                     | 18.5 kW        |
| — at 400 V rated value                                                                     | 30 kW          |
| — at 500 V rated value                                                                     | 45 kW          |
| — at 690 V rated value                                                                     | 55 kW          |
| • at AC-3e                                                                                 |                |
| — at 230 V rated value                                                                     | 18.5 kW        |
| — at 400 V rated value                                                                     | 30 kW          |
| — at 500 V rated value                                                                     | 45 kW          |
| — at 690 V rated value                                                                     | 55 kW          |
| <b>operating frequency</b>                                                                 |                |
| • at AC-3 maximum                                                                          | 15 1/h         |
| • at AC-3e maximum                                                                         | 15 1/h         |
| <b>Auxiliary circuit</b>                                                                   |                |
| <b>type of voltage for auxiliary and control circuit</b>                                   | AC/DC          |
| <b>number of NC contacts for auxiliary contacts</b>                                        | 0              |
| <b>number of NO contacts for auxiliary contacts</b>                                        | 0              |
| <b>number of CO contacts for auxiliary contacts</b>                                        | 0              |
| <b>Protective and monitoring functions</b>                                                 |                |
| <b>product function</b>                                                                    |                |
| • ground fault detection                                                                   | No             |
| • phase failure detection                                                                  | Yes            |
| <b>trip class</b>                                                                          | CLASS 20       |
| <b>design of the overload release</b>                                                      | thermal        |
| <b>protection function thermal overload protection (ANSI 49)</b>                           | Yes            |
| <b>maximum short-circuit current breaking capacity (Icu)</b>                               |                |
| • at AC at 240 V rated value                                                               | 65 kA          |
| • at AC at 400 V rated value                                                               | 65 kA          |
| • at AC at 500 V rated value                                                               | 8 kA           |
| • at AC at 690 V rated value                                                               | 4 kA           |
| <b>operating short-circuit current breaking capacity (Ics) at AC</b>                       |                |
| • at 240 V rated value                                                                     | 100 kA         |
| • at 400 V rated value                                                                     | 30 kA          |
| • at 500 V rated value                                                                     | 5 kA           |
| • at 690 V rated value                                                                     | 2 kA           |
| <b>response value current of instantaneous short-circuit trip unit</b>                     | 845 A          |

| UL/CSA ratings                                                                                                                                  |                                                                          |
|-------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|
| <b>full-load current (FLA) for 3-phase AC motor</b>                                                                                             |                                                                          |
| • at 480 V rated value                                                                                                                          | 65 A                                                                     |
| • at 600 V rated value                                                                                                                          | 62 A                                                                     |
| <b>yielded mechanical performance [hp]</b>                                                                                                      |                                                                          |
| • for 3-phase AC motor                                                                                                                          |                                                                          |
| — at 200/208 V rated value                                                                                                                      | 20 hp                                                                    |
| — at 220/230 V rated value                                                                                                                      | 25 hp                                                                    |
| — at 460/480 V rated value                                                                                                                      | 50 hp                                                                    |
| — at 575/600 V rated value                                                                                                                      | 60 hp                                                                    |
| Short-circuit protection                                                                                                                        |                                                                          |
| <b>product function short circuit protection</b>                                                                                                | Yes                                                                      |
| <b>design of the short-circuit trip</b>                                                                                                         | magnetic                                                                 |
| <b>design of the fuse link for IT network for short-circuit protection of the main circuit</b>                                                  |                                                                          |
| • at 240 V                                                                                                                                      | none required                                                            |
| • at 400 V                                                                                                                                      | 160                                                                      |
| • at 500 V                                                                                                                                      | 125                                                                      |
| • at 690 V                                                                                                                                      | 100                                                                      |
| Installation/ mounting/ dimensions                                                                                                              |                                                                          |
| <b>mounting position</b>                                                                                                                        | any                                                                      |
| <b>fastening method</b>                                                                                                                         | screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 60715 |
| <b>Mounting method of circuit breaker for Transformer protection, Generator protection and system protection optional standard bar mounting</b> | Yes                                                                      |
| <b>height</b>                                                                                                                                   | 140 mm                                                                   |
| <b>width</b>                                                                                                                                    | 55 mm                                                                    |
| <b>depth</b>                                                                                                                                    | 149 mm                                                                   |
| <b>required spacing</b>                                                                                                                         |                                                                          |
| • with side-by-side mounting                                                                                                                    |                                                                          |
| — forwards                                                                                                                                      | 0 mm                                                                     |
| — backwards                                                                                                                                     | 0 mm                                                                     |
| — upwards                                                                                                                                       | 50 mm                                                                    |
| — downwards                                                                                                                                     | 50 mm                                                                    |
| — at the side                                                                                                                                   | 0 mm                                                                     |
| • for grounded parts                                                                                                                            |                                                                          |
| — forwards                                                                                                                                      | 0 mm                                                                     |
| — backwards                                                                                                                                     | 0 mm                                                                     |
| — upwards                                                                                                                                       | 50 mm                                                                    |
| — at the side                                                                                                                                   | 10 mm                                                                    |
| — downwards                                                                                                                                     | 50 mm                                                                    |
| • for live parts                                                                                                                                |                                                                          |
| — forwards                                                                                                                                      | 0 mm                                                                     |
| — backwards                                                                                                                                     | 0 mm                                                                     |
| — upwards                                                                                                                                       | 50 mm                                                                    |
| — downwards                                                                                                                                     | 50 mm                                                                    |
| — at the side                                                                                                                                   | 10 mm                                                                    |
| • for grounded parts at 400 V                                                                                                                   |                                                                          |
| — downwards                                                                                                                                     | 50 mm                                                                    |
| — upwards                                                                                                                                       | 50 mm                                                                    |
| — at the side                                                                                                                                   | 10 mm                                                                    |
| • for live parts at 400 V                                                                                                                       |                                                                          |
| — downwards                                                                                                                                     | 50 mm                                                                    |
| — upwards                                                                                                                                       | 50 mm                                                                    |
| — at the side                                                                                                                                   | 10 mm                                                                    |
| • for grounded parts at 500 V                                                                                                                   |                                                                          |
| — downwards                                                                                                                                     | 50 mm                                                                    |
| — upwards                                                                                                                                       | 50 mm                                                                    |
| — at the side                                                                                                                                   | 10 mm                                                                    |
| • for live parts at 500 V                                                                                                                       |                                                                          |

|                                                                                  |                                                                |
|----------------------------------------------------------------------------------|----------------------------------------------------------------|
| — downwards                                                                      | 50 mm                                                          |
| — upwards                                                                        | 50 mm                                                          |
| — at the side                                                                    | 10 mm                                                          |
| • for grounded parts at 690 V                                                    |                                                                |
| — downwards                                                                      | 50 mm                                                          |
| — upwards                                                                        | 50 mm                                                          |
| — at the side                                                                    | 10 mm                                                          |
| • for live parts at 690 V                                                        |                                                                |
| — downwards                                                                      | 50 mm                                                          |
| — upwards                                                                        | 50 mm                                                          |
| — at the side                                                                    | 10 mm                                                          |
| <b>Connections/ Terminals</b>                                                    |                                                                |
| <b>product component removable terminal for auxiliary and control circuit</b>    | No                                                             |
| <b>type of electrical connection</b>                                             |                                                                |
| • for main current circuit                                                       | screw-type terminals                                           |
| <b>arrangement of electrical connectors for main current circuit</b>             | Top and bottom                                                 |
| <b>type of connectable conductor cross-sections</b>                              |                                                                |
| • for main contacts                                                              |                                                                |
| — solid or stranded                                                              | 2x (1 ... 35 mm <sup>2</sup> ), 1x (1 ... 50 mm <sup>2</sup> ) |
| — finely stranded with core end processing                                       | 2x (1 ... 25 mm <sup>2</sup> ), 1x (1 ... 35 mm <sup>2</sup> ) |
| • for AWG cables for main contacts                                               | 2x (18 ... 2), 1x (18 ... 1)                                   |
| <b>connectable conductor cross-section for main contacts</b>                     |                                                                |
| • solid or stranded                                                              | 1 ... 50 mm <sup>2</sup>                                       |
| • finely stranded with core end processing                                       | 1 ... 35 mm <sup>2</sup>                                       |
| <b>AWG number as coded connectable conductor cross section for main contacts</b> | 18 ... 1                                                       |
| <b>tightening torque</b>                                                         |                                                                |
| • for main contacts with screw-type terminals                                    | 3 ... 4.5 N·m                                                  |
| <b>design of screwdriver shaft</b>                                               | Diameter 5 to 6 mm                                             |
| <b>size of the screwdriver tip</b>                                               | Pozidriv size 2                                                |
| <b>design of the thread of the connection screw</b>                              |                                                                |
| • for main contacts                                                              | M6                                                             |
| <b>Safety related data</b>                                                       |                                                                |
| product function suitable for safety function                                    | Yes                                                            |
| <b>suitability for use</b>                                                       |                                                                |
| • safety-related switching on                                                    | No                                                             |
| • safety-related switching OFF                                                   | Yes                                                            |
| <b>service life maximum</b>                                                      | 10 a                                                           |
| <b>test wear-related service life necessary</b>                                  | Yes                                                            |
| <b>proportion of dangerous failures</b>                                          |                                                                |
| • with low demand rate according to SN 31920                                     | 40 %                                                           |
| • with high demand rate according to SN 31920                                    | 50 %                                                           |
| <b>B10 value with high demand rate according to SN 31920</b>                     | 5 000                                                          |
| <b>failure rate [FIT] with low demand rate according to SN 31920</b>             | 50 FIT                                                         |
| <b>ISO 13849</b>                                                                 |                                                                |
| <b>device type according to ISO 13849-1</b>                                      | 3                                                              |
| <b>overdimensioning according to ISO 13849-2 necessary</b>                       | Yes                                                            |
| <b>IEC 61508</b>                                                                 |                                                                |
| <b>safety device type according to IEC 61508-2</b>                               | Type A                                                         |
| <b>T1 value</b>                                                                  |                                                                |
| • for proof test interval or service life according to IEC 61508                 | 10 a                                                           |
| <b>Electrical Safety</b>                                                         |                                                                |
| <b>protection class IP on the front according to IEC 60529</b>                   | IP20                                                           |
| <b>touch protection on the front according to IEC 60529</b>                      | finger-safe, for vertical contact from the front               |
| <b>Display</b>                                                                   |                                                                |
| display version for switching status                                             | Handle                                                         |

## Approvals Certificates

### Environmental Product Declaration

|                                                            |            |
|------------------------------------------------------------|------------|
| • global warming potential [CO2 eq] / during manufacturing | 12.8 kg    |
| • global warming potential [CO2 eq] / during sales         | 0.477 kg   |
| • global warming potential [CO2 eq] / during operation     | 230 kg     |
| • global warming potential [CO2 eq] / after end of life    | -3.4 kg    |
| • global warming potential [CO2 eq] / total                | 239.877 kg |

### Environment

### General Product Approval

[Environmental Confirmations](#)



### General Product Approval

### Test Certificates



[Special Test Certificate](#)

### Test Certificates

### Maritime application

[Type Test Certificates/Test Report](#)



### Maritime application

### other

### Railway



[Miscellaneous](#)

[Confirmation](#)

[Miscellaneous](#)



[Confirmation](#)

### Railway

[Special Test Certificate](#)

## Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RV2031-4JB10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RV2031-4JB10>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)



[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RV2031-4JB10&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RV2031-4JB10&lang=en)

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RV2031-4JB10>

Characteristic curves

[https://curves.simarisiemens.com/curves/<mmp\\_prod\\_noCOMP='HAUPT'></mmp\\_prod\\_no>](https://curves.simarisiemens.com/curves/<mmp_prod_noCOMP='HAUPT'></mmp_prod_no>)



last modified:

5/5/2026

