



SIRIUS soft starter 200-480 V 113 A, 110-250 V AC spring-type terminals Analog output

|                                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>product brand name</b>                               | SIRIUS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>product category</b>                                 | Hybrid switching devices                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>product designation</b>                              | Soft starter                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>product type designation</b>                         | 3RW52                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>manufacturer's article number</b>                    | <ul style="list-style-type: none"> <li>of standard HMI module usable <a href="#">3RW5980-0HS00</a></li> <li>of high feature HMI module usable <a href="#">3RW5980-0HF00</a></li> <li>of communication module PROFINET standard usable <a href="#">3RW5980-0CS00</a></li> <li>of communication module PROFIBUS usable <a href="#">3RW5980-0CP00</a></li> <li>of communication module Modbus TCP usable <a href="#">3RW5980-0CT00</a></li> <li>of communication module Modbus RTU usable <a href="#">3RW5980-0CR00</a></li> <li>of communication module Ethernet/IP <a href="#">3RW5980-0CE00</a></li> <li>of circuit breaker usable at 400 V <a href="#">3VA2216-7MN32-0AA0; Type of coordination 1, Iq = 65 kA, CLASS 10</a></li> <li>of circuit breaker usable at 400 V at inside-delta circuit <a href="#">3VA2220-7MN32-0AA0; Type of coordination 1, Iq = 65 kA, CLASS 10</a></li> <li>of the gG fuse usable up to 690 V <a href="#">3NA3244-6; Type of coordination 1, Iq = 65 kA</a></li> <li>of the gG fuse usable at inside-delta circuit up to 500 V <a href="#">3NA3244-6; Type of coordination 1, Iq = 65 kA</a></li> <li>of full range R fuse link for semiconductor protection usable up to 690 V <a href="#">3NE1225-0; Type of coordination 2, Iq = 65 kA</a></li> <li>of back-up R fuse link for semiconductor protection usable up to 690 V <a href="#">3NE3332-0B; Type of coordination 2, Iq = 65 kA</a></li> </ul> |
| <b>General technical data</b>                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>starting voltage [%]</b>                             | 30 ... 100 %                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>stopping voltage [%]</b>                             | 50 %; non-adjustable                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>start-up ramp time of soft starter</b>               | 0 ... 20 s                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>current limiting value [%] adjustable</b>            | 130 ... 700 %                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>certificate of suitability</b>                       | <ul style="list-style-type: none"> <li>CE marking Yes</li> <li>UL approval Yes</li> <li>CSA approval Yes</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>product component</b>                                | <ul style="list-style-type: none"> <li>HMI-High Feature No</li> <li>is supported HMI-Standard Yes</li> <li>is supported HMI-High Feature Yes</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>product feature integrated bypass contact system</b> | Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>number of controlled phases</b>                      | 3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>buffering time in the event of power failure</b>     | <ul style="list-style-type: none"> <li>for main current circuit 100 ms</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |

|                                                                |                                                                                                                                                                                                                                                                                                                                                                                       |
|----------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| • for control circuit                                          | 100 ms                                                                                                                                                                                                                                                                                                                                                                                |
| <b>insulation voltage rated value</b>                          | 600 V                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>degree of pollution</b>                                     | 3, acc. to IEC 60947-4-2                                                                                                                                                                                                                                                                                                                                                              |
| <b>impulse voltage rated value</b>                             | 6 kV                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>blocking voltage of the thyristor maximum</b>               | 1 400 V                                                                                                                                                                                                                                                                                                                                                                               |
| <b>service factor</b>                                          | 1                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>surge voltage resistance rated value</b>                    | 6 kV                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>maximum permissible voltage for protective separation</b>   |                                                                                                                                                                                                                                                                                                                                                                                       |
| • between main and auxiliary circuit                           | 600 V                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>shock resistance</b>                                        | 15 g / 11 ms, from 12 g / 11 ms with potential contact lifting                                                                                                                                                                                                                                                                                                                        |
| <b>vibration resistance</b>                                    | 15 mm to 6 Hz; 2 g to 500 Hz                                                                                                                                                                                                                                                                                                                                                          |
| utilization category according to IEC 60947-4-2                | AC 53a                                                                                                                                                                                                                                                                                                                                                                                |
| <b>reference code according to IEC 81346-2</b>                 | Q                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Substance Prohibitance (day/month/year)</b>                 | 02/15/2018                                                                                                                                                                                                                                                                                                                                                                            |
| <b>SVHC substance name</b>                                     | Lead CAS-No. 7439-92-1<br>Lead monoxide (lead oxide) CAS-No. 1317-36-8<br>2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol CAS-No. 79-94-7<br>2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one CAS-No. 71868-10-5<br>Melamine CAS-No. 108-78-1<br>6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol CAS-No. 119-47-1<br>Dibutylbis(pentane-2,4-dionato-O,O')tin CAS-No. 22673-19-4 |
| <b>Net Weight</b>                                              | 7.714 kg                                                                                                                                                                                                                                                                                                                                                                              |
| <b>product function</b>                                        |                                                                                                                                                                                                                                                                                                                                                                                       |
| • ramp-up (soft starting)                                      | Yes                                                                                                                                                                                                                                                                                                                                                                                   |
| • soft stopping                                                | Yes                                                                                                                                                                                                                                                                                                                                                                                   |
| • Soft Torque                                                  | Yes                                                                                                                                                                                                                                                                                                                                                                                   |
| • adjustable current limitation                                | Yes                                                                                                                                                                                                                                                                                                                                                                                   |
| • pump stop                                                    | Yes                                                                                                                                                                                                                                                                                                                                                                                   |
| • intrinsic device protection                                  | Yes                                                                                                                                                                                                                                                                                                                                                                                   |
| • motor overload protection                                    | Yes; Electronic motor overload protection                                                                                                                                                                                                                                                                                                                                             |
| • evaluation of thermistor motor protection                    | No                                                                                                                                                                                                                                                                                                                                                                                    |
| • inside-delta circuit                                         | Yes                                                                                                                                                                                                                                                                                                                                                                                   |
| • auto-RESET                                                   | Yes                                                                                                                                                                                                                                                                                                                                                                                   |
| • manual RESET                                                 | Yes                                                                                                                                                                                                                                                                                                                                                                                   |
| • remote reset                                                 | Yes; By turning off the control supply voltage                                                                                                                                                                                                                                                                                                                                        |
| • communication function                                       | Yes                                                                                                                                                                                                                                                                                                                                                                                   |
| • operating measured value display                             | Yes; Only in conjunction with special accessories                                                                                                                                                                                                                                                                                                                                     |
| • error logbook                                                | Yes; Only in conjunction with special accessories                                                                                                                                                                                                                                                                                                                                     |
| • via software parameterizable                                 | No                                                                                                                                                                                                                                                                                                                                                                                    |
| • via software configurable                                    | Yes                                                                                                                                                                                                                                                                                                                                                                                   |
| • <b>PROFenergy</b>                                            | Yes; in connection with the PROFINET Standard communication module                                                                                                                                                                                                                                                                                                                    |
| • <b>firmware update</b>                                       | Yes                                                                                                                                                                                                                                                                                                                                                                                   |
| • <b>removable terminal for control circuit</b>                | Yes                                                                                                                                                                                                                                                                                                                                                                                   |
| • torque control                                               | No                                                                                                                                                                                                                                                                                                                                                                                    |
| • analog output                                                | Yes; 4 ... 20 mA (default) / 0 ... 10 V (parameterizable with High Feature HMI)                                                                                                                                                                                                                                                                                                       |
| <b>Power Electronics</b>                                       |                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>operational current</b>                                     |                                                                                                                                                                                                                                                                                                                                                                                       |
| • at 40 °C rated value                                         | 113 A                                                                                                                                                                                                                                                                                                                                                                                 |
| • at 50 °C rated value                                         | 101 A                                                                                                                                                                                                                                                                                                                                                                                 |
| • at 60 °C rated value                                         | 89 A                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>operational current at inside-delta circuit</b>             |                                                                                                                                                                                                                                                                                                                                                                                       |
| • at 40 °C rated value                                         | 196 A                                                                                                                                                                                                                                                                                                                                                                                 |
| • at 50 °C rated value                                         | 175 A                                                                                                                                                                                                                                                                                                                                                                                 |
| • at 60 °C rated value                                         | 154 A                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>operating voltage</b>                                       |                                                                                                                                                                                                                                                                                                                                                                                       |
| • rated value                                                  | 200 ... 480 V                                                                                                                                                                                                                                                                                                                                                                         |
| • at inside-delta circuit rated value                          | 200 ... 480 V                                                                                                                                                                                                                                                                                                                                                                         |
| <b>relative negative tolerance of the operating voltage</b>    | -15 %                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>relative positive tolerance of the operating voltage</b>    | 10 %                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>relative negative tolerance of the operating voltage at</b> | -15 %                                                                                                                                                                                                                                                                                                                                                                                 |

|                                                                                     |        |
|-------------------------------------------------------------------------------------|--------|
| <b>inside-delta circuit</b>                                                         |        |
| <b>relative positive tolerance of the operating voltage at inside-delta circuit</b> | 10 %   |
| <b>operating power for 3-phase motors</b>                                           |        |
| • at 230 V at 40 °C rated value                                                     | 30 kW  |
| • at 230 V at inside-delta circuit at 40 °C rated value                             | 55 kW  |
| • at 400 V at 40 °C rated value                                                     | 55 kW  |
| • at 400 V at inside-delta circuit at 40 °C rated value                             | 110 kW |
| <b>Operating frequency 1 rated value</b>                                            | 50 Hz  |
| <b>Operating frequency 2 rated value</b>                                            | 60 Hz  |
| <b>relative negative tolerance of the operating frequency</b>                       | -10 %  |
| <b>relative positive tolerance of the operating frequency</b>                       | 10 %   |
| <b>adjustable motor current</b>                                                     |        |
| • at rotary coding switch on switch position 1                                      | 53 A   |
| • at rotary coding switch on switch position 2                                      | 57 A   |
| • at rotary coding switch on switch position 3                                      | 61 A   |
| • at rotary coding switch on switch position 4                                      | 65 A   |
| • at rotary coding switch on switch position 5                                      | 69 A   |
| • at rotary coding switch on switch position 6                                      | 73 A   |
| • at rotary coding switch on switch position 7                                      | 77 A   |
| • at rotary coding switch on switch position 8                                      | 81 A   |
| • at rotary coding switch on switch position 9                                      | 85 A   |
| • at rotary coding switch on switch position 10                                     | 89 A   |
| • at rotary coding switch on switch position 11                                     | 93 A   |
| • at rotary coding switch on switch position 12                                     | 97 A   |
| • at rotary coding switch on switch position 13                                     | 101 A  |
| • at rotary coding switch on switch position 14                                     | 105 A  |
| • at rotary coding switch on switch position 15                                     | 109 A  |
| • at rotary coding switch on switch position 16                                     | 113 A  |
| • minimum                                                                           | 53 A   |
| <b>adjustable motor current</b>                                                     |        |
| • for inside-delta circuit at rotary coding switch on switch position 1             | 91.8 A |
| • for inside-delta circuit at rotary coding switch on switch position 2             | 98.7 A |
| • for inside-delta circuit at rotary coding switch on switch position 3             | 106 A  |
| • for inside-delta circuit at rotary coding switch on switch position 4             | 113 A  |
| • for inside-delta circuit at rotary coding switch on switch position 5             | 120 A  |
| • for inside-delta circuit at rotary coding switch on switch position 6             | 126 A  |
| • for inside-delta circuit at rotary coding switch on switch position 7             | 133 A  |
| • for inside-delta circuit at rotary coding switch on switch position 8             | 140 A  |
| • for inside-delta circuit at rotary coding switch on switch position 9             | 147 A  |
| • for inside-delta circuit at rotary coding switch on switch position 10            | 154 A  |
| • for inside-delta circuit at rotary coding switch on switch position 11            | 161 A  |
| • for inside-delta circuit at rotary coding switch on switch position 12            | 168 A  |
| • for inside-delta circuit at rotary coding switch on switch position 13            | 175 A  |
| • for inside-delta circuit at rotary coding switch on switch position 14            | 182 A  |
| • for inside-delta circuit at rotary coding switch on switch position 15            | 189 A  |
| • for inside-delta circuit at rotary coding switch on switch position 16            | 196 A  |
| • at inside-delta circuit minimum                                                   | 91.8 A |

|                                                                                 |                                                                                                                                                                                                                                    |
|---------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>minimum load [%]</b>                                                         | 15 %; Relative to smallest settable I <sub>e</sub>                                                                                                                                                                                 |
| <b>power loss [W] for rated value of the current at AC</b>                      |                                                                                                                                                                                                                                    |
| • at 40 °C after startup                                                        | 46 W                                                                                                                                                                                                                               |
| • at 50 °C after startup                                                        | 42 W                                                                                                                                                                                                                               |
| • at 60 °C after startup                                                        | 39 W                                                                                                                                                                                                                               |
| <b>power loss [W] at AC at current limitation 350%</b>                          |                                                                                                                                                                                                                                    |
| • at 40 °C during startup                                                       | 1 512 W                                                                                                                                                                                                                            |
| • at 50 °C during startup                                                       | 1 291 W                                                                                                                                                                                                                            |
| • at 60 °C during startup                                                       | 1 086 W                                                                                                                                                                                                                            |
| <b>Control circuit/ Control</b>                                                 |                                                                                                                                                                                                                                    |
| <b>type of voltage of the control supply voltage</b>                            | AC                                                                                                                                                                                                                                 |
| <b>control supply voltage at AC</b>                                             |                                                                                                                                                                                                                                    |
| • at 50 Hz                                                                      | 110 ... 250 V                                                                                                                                                                                                                      |
| • at 60 Hz                                                                      | 110 ... 250 V                                                                                                                                                                                                                      |
| <b>relative negative tolerance of the control supply voltage at AC at 50 Hz</b> | -15 %                                                                                                                                                                                                                              |
| <b>relative positive tolerance of the control supply voltage at AC at 50 Hz</b> | 10 %                                                                                                                                                                                                                               |
| <b>relative negative tolerance of the control supply voltage at AC at 60 Hz</b> | -15 %                                                                                                                                                                                                                              |
| <b>relative positive tolerance of the control supply voltage at AC at 60 Hz</b> | 10 %                                                                                                                                                                                                                               |
| <b>control supply voltage frequency</b>                                         | 50 ... 60 Hz                                                                                                                                                                                                                       |
| <b>relative negative tolerance of the control supply voltage frequency</b>      | -10 %                                                                                                                                                                                                                              |
| <b>relative positive tolerance of the control supply voltage frequency</b>      | 10 %                                                                                                                                                                                                                               |
| <b>control supply current in standby mode rated value</b>                       | 30 mA                                                                                                                                                                                                                              |
| <b>holding current in bypass operation rated value</b>                          | 75 mA                                                                                                                                                                                                                              |
| <b>inrush current by closing the bypass contacts maximum</b>                    | 2.5 A                                                                                                                                                                                                                              |
| inrush current peak at application of control supply voltage maximum            | 12.2 A                                                                                                                                                                                                                             |
| duration of inrush current peak at application of control supply voltage        | 2.2 ms                                                                                                                                                                                                                             |
| <b>design of the overvoltage protection</b>                                     | Varistor                                                                                                                                                                                                                           |
| <b>design of short-circuit protection for control circuit</b>                   | 4 A gG fuse (I <sub>cu</sub> =1 kA), 6 A quick-acting fuse (I <sub>cu</sub> =1 kA), C1 miniature circuit breaker (I <sub>cu</sub> = 600 A), C6 miniature circuit breaker (I <sub>cu</sub> = 300 A); Is not part of scope of supply |
| <b>Inputs/ Outputs</b>                                                          |                                                                                                                                                                                                                                    |
| <b>number of digital inputs</b>                                                 | 1                                                                                                                                                                                                                                  |
| <b>number of digital outputs</b>                                                | 3                                                                                                                                                                                                                                  |
| • not parameterizable                                                           | 2                                                                                                                                                                                                                                  |
| <b>digital output version</b>                                                   | 2 normally-open contacts (NO) / 1 changeover contact (CO)                                                                                                                                                                          |
| <b>number of analog outputs</b>                                                 | 1                                                                                                                                                                                                                                  |
| <b>switching capacity current of the relay outputs</b>                          |                                                                                                                                                                                                                                    |
| • at AC-15 at 250 V rated value                                                 | 3 A                                                                                                                                                                                                                                |
| • at DC-13 at 24 V rated value                                                  | 1 A                                                                                                                                                                                                                                |
| <b>Installation/ mounting/ dimensions</b>                                       |                                                                                                                                                                                                                                    |
| <b>mounting position</b>                                                        | with vertical mounting surface +/-90° rotatable, with vertical mounting surface +/- 22.5° tiltable to the front and back                                                                                                           |
| <b>fastening method</b>                                                         | screw fixing                                                                                                                                                                                                                       |
| <b>height</b>                                                                   | 306 mm                                                                                                                                                                                                                             |
| <b>width</b>                                                                    | 185 mm                                                                                                                                                                                                                             |
| <b>depth</b>                                                                    | 203 mm                                                                                                                                                                                                                             |
| required spacing with side-by-side mounting                                     |                                                                                                                                                                                                                                    |
| • forwards                                                                      | 10 mm                                                                                                                                                                                                                              |
| • backwards                                                                     | 0 mm                                                                                                                                                                                                                               |
| • upwards                                                                       | 100 mm                                                                                                                                                                                                                             |
| • downwards                                                                     | 75 mm                                                                                                                                                                                                                              |
| • at the side                                                                   | 5 mm                                                                                                                                                                                                                               |
| <b>weight without packaging</b>                                                 | 6.6 kg                                                                                                                                                                                                                             |
| <b>Connections/ Terminals</b>                                                   |                                                                                                                                                                                                                                    |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>type of electrical connection</b> <ul style="list-style-type: none"> <li>• for main current circuit</li> <li>• for control circuit</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | busbar connection<br>spring-loaded terminals                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>width of connection bar maximum</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 25 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>type of connectable conductor cross-sections</b> <ul style="list-style-type: none"> <li>• for DIN cable lug for main contacts stranded</li> <li>• for DIN cable lug for main contacts finely stranded</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 2x (16 ... 95 mm <sup>2</sup> )<br>2x (25 ... 120 mm <sup>2</sup> )                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>type of connectable conductor cross-sections</b> <ul style="list-style-type: none"> <li>• for control circuit solid</li> <li>• for control circuit finely stranded with core end processing</li> <li>• for AWG cables for control circuit solid</li> <li>• for AWG cables for control circuit finely stranded with core end processing</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 2x (0.25 ... 1.5 mm <sup>2</sup> )<br>2x (0.25 ... 1.5 mm <sup>2</sup> )<br>2x (24 ... 16)<br>2x (24 ... 16)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>wire length</b> <ul style="list-style-type: none"> <li>• between soft starter and motor maximum</li> <li>• at the digital inputs at AC maximum</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 800 m<br>100 m                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>tightening torque</b> <ul style="list-style-type: none"> <li>• for main contacts with screw-type terminals</li> <li>• for auxiliary and control contacts with screw-type terminals</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 10 ... 14 N·m<br>0.8 ... 1.2 N·m                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>tightening torque [lbf·in]</b> <ul style="list-style-type: none"> <li>• for main contacts with screw-type terminals</li> <li>• for auxiliary and control contacts with screw-type terminals</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 89 ... 124 lbf·in<br>7 ... 10.3 lbf·in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Ambient conditions</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| installation altitude at height above sea level maximum                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 5 000 m                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>ambient temperature</b> <ul style="list-style-type: none"> <li>• during operation</li> <li>• during storage and transport</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | -25 ... +60 °C; Please observe derating at temperatures of 40 °C or above<br>-40 ... +80 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>environmental category</b> <ul style="list-style-type: none"> <li>• during operation according to IEC 60721</li> <li>• during storage according to IEC 60721</li> <li>• during transport according to IEC 60721</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 3K6 (no ice formation, only occasional condensation), 3C3 (no salt mist), 3S2 (sand must not get into the devices), 3M6<br>1K6 (only occasional condensation), 1C2 (no salt mist), 1S2 (sand must not get inside the devices), 1M4<br>2K2, 2C1, 2S1, 2M2 (max. fall height 0.3 m)                                                                                                                                                                                                                                                                                                                                      |
| <b>Electromagnetic compatibility</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>EMC emitted interference</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | acc. to IEC 60947-4-2: Class A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Communication/ Protocol</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>communication module is supported</b> <ul style="list-style-type: none"> <li>• PROFINET standard</li> <li>• EtherNet/IP</li> <li>• Modbus RTU</li> <li>• Modbus TCP</li> <li>• PROFIBUS</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Yes<br>Yes<br>Yes<br>Yes<br>Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>UL/CSA ratings</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>manufacturer's article number</b> <ul style="list-style-type: none"> <li>• of circuit breaker usable for Standard Faults <ul style="list-style-type: none"> <li>— at 460/480 V according to UL</li> <li>— 60/480 V according to UL</li> <li>— at 460/480 V at inside-delta circuit according to UL</li> <li>— 60/480 V at inside-delta circuit according to UL</li> <li>— at 575/600 V according to UL</li> <li>— at 575/600 V at inside-delta circuit according to UL</li> </ul> </li> <li>• of the fuse <ul style="list-style-type: none"> <li>— usable for Standard Faults up to 575/600 V according to UL</li> <li>— usable for High Faults up to 575/600 V according to UL</li> <li>— usable for Standard Faults at inside-delta circuit up to 575/600 V according to UL</li> <li>— usable for High Faults at inside-delta circuit up to</li> </ul> </li> </ul> | Siemens type: 3VA52, max. 250 A; I <sub>q</sub> = 10 kA<br>Siemens type: 3VA52, max. 250 A; I <sub>q</sub> max = 65 kA<br>Siemens type: 3VA52, max. 250 A; I <sub>q</sub> = 10 kA<br>Siemens type: 3VA52, max. 250 A; I <sub>q</sub> max = 65 kA<br>Siemens type: 3VA52, max. 250 A; I <sub>q</sub> = 10 kA<br>Siemens type: 3VA52, max. 250 A; I <sub>q</sub> = 10 kA<br><br>Type: Class RK5 / K5, max. 350 A; I <sub>q</sub> = 10 kA<br>Type: Class J / L, max. 350 A; I <sub>q</sub> = 100 kA<br>Type: Class RK5 / K5, max. 350 A; I <sub>q</sub> = 10 kA<br>Type: Class J / L, max. 350 A; I <sub>q</sub> = 100 kA |

|                                                                                                                                                                                                                                                                                                                                                                                                             |                                                             |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------|
| 575/600 V according to UL                                                                                                                                                                                                                                                                                                                                                                                   |                                                             |
| <b>operating power [hp] for 3-phase motors</b>                                                                                                                                                                                                                                                                                                                                                              |                                                             |
| <ul style="list-style-type: none"> <li>at 200/208 V at 50 °C rated value</li> <li>at 220/230 V at 50 °C rated value</li> <li>at 460/480 V at 50 °C rated value</li> <li>at 200/208 V at inside-delta circuit at 50 °C rated value</li> <li>at 220/230 V at inside-delta circuit at 50 °C rated value</li> <li>at 460/480 V at inside-delta circuit at 50 °C rated value</li> </ul>                          | 30 hp<br>30 hp<br>75 hp<br>50 hp<br>60 hp<br>125 hp         |
| <b>contact rating of auxiliary contacts according to UL</b>                                                                                                                                                                                                                                                                                                                                                 | R300-B300                                                   |
| Electrical Safety                                                                                                                                                                                                                                                                                                                                                                                           |                                                             |
| <b>protection class IP on the front according to IEC 60529</b>                                                                                                                                                                                                                                                                                                                                              | IP00; IP20 with cover                                       |
| <b>touch protection on the front according to IEC 60529</b>                                                                                                                                                                                                                                                                                                                                                 | finger-safe, for vertical contact from the front with cover |
| <b>Approvals Certificates</b>                                                                                                                                                                                                                                                                                                                                                                               |                                                             |
| Environmental Product Declaration                                                                                                                                                                                                                                                                                                                                                                           |                                                             |
| <ul style="list-style-type: none"> <li>global warming potential [CO<sub>2</sub> eq] / during manufacturing</li> <li>global warming potential [CO<sub>2</sub> eq] / during sales</li> <li>global warming potential [CO<sub>2</sub> eq] / during operation</li> <li>global warming potential [CO<sub>2</sub> eq] / after end of life</li> <li>global warming potential [CO<sub>2</sub> eq] / total</li> </ul> | 67.7 kg<br>1.84 kg<br>242 kg<br>-15.7 kg<br>296 kg          |
| Environment                                                                                                                                                                                                                                                                                                                                                                                                 | General Product Approval                                    |

[Environmental Confirmations](#)



|                                                                                     |                                                                                     |                                                                                     |                                                                                       |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| General Product Approval                                                            | EMV                                                                                 | Test Certificates                                                                   | Maritime application                                                                  |
|  |  |  |    |
| EG-Konf.                                                                            |                                                                                     |                                                                                     | <a href="#">Type Test Certificates/Test Report</a>                                    |
|                                                                                     |                                                                                     |                                                                                     |  |

| Maritime application                                                                |                                                                                     |                                                                                     |                                                                                     | other                                                                                                              |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|
|  |  |  |  | <a href="#">Confirmation</a>  |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Further information</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <p>Information on the packaging<br/> <a href="https://support.industry.siemens.com/cs/ww/en/view/109813875">https://support.industry.siemens.com/cs/ww/en/view/109813875</a></p> <p>Information for data generation and storage<br/> <a href="https://support.industry.siemens.com/cs/ww/en/view/109995012">https://support.industry.siemens.com/cs/ww/en/view/109995012</a></p> <p>Information- and Downloadcenter (Catalogs, Brochures,...)<br/> <a href="https://www.siemens.com/ic10">https://www.siemens.com/ic10</a></p> <p>Industry Mall (Online ordering system)<br/> <a href="https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5234-2AC14">https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5234-2AC14</a></p> <p>Service&amp;Support (Manuals, Certificates, Characteristics, FAQs,...)<br/> <a href="https://support.industry.siemens.com/cs/ww/en/ps/3RW5234-2AC14">https://support.industry.siemens.com/cs/ww/en/ps/3RW5234-2AC14</a></p> <p>Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)<br/> <a href="https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5234-2AC14&amp;lang=en">https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5234-2AC14&amp;lang=en</a></p> <p>Cax online generator<br/> <a href="https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&amp;mlfb=3RW5234-2AC14">https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&amp;mlfb=3RW5234-2AC14</a></p> <p>Characteristic curves<br/> <a href='https://curves.simaris.siemens.com/curves/&lt;mmp_prod_noCOMP="HAUPT"&gt;&lt;/mmp_prod_no&gt;'>https://curves.simaris.siemens.com/curves/&lt;mmp_prod_noCOMP="HAUPT"&gt;&lt;/mmp_prod_no&gt;</a></p> <p>Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current<br/> <a href="https://support.industry.siemens.com/cs/ww/en/ps/3RW5234-2AC14/char">https://support.industry.siemens.com/cs/ww/en/ps/3RW5234-2AC14/char</a></p> <p>Characteristic: Installation altitude<br/> <a href="https://www.automation.siemens.com/bilddb/index.aspx?gridview=view2&amp;objkey=G_NSB0_XX_01704&amp;showdetail=true&amp;view=Search">https://www.automation.siemens.com/bilddb/index.aspx?gridview=view2&amp;objkey=G_NSB0_XX_01704&amp;showdetail=true&amp;view=Search</a></p> <p>Simulation Tool for Soft Starters (STS)<br/> <a href="https://support.industry.siemens.com/cs/ww/en/view/101494917">https://support.industry.siemens.com/cs/ww/en/view/101494917</a></p> |







