

Addressing plug, for assigning the PROFIBUS address to SIMOCODE pro without PC/PG

General technical data	
product brand name	SIMOCODE
product designation	addressing plug
design of the product	For assigning the PROFIBUS or Modbus RTU address without using a PC/PG
ambient temperature	
• during storage	-40 ... +80 °C
• during operation	-25 ... +60 °C
• during transport	-40 ... +80 °C
Certificates/ approvals	
General Product Approval	



EMV	Test Certificates	Maritime application

Maritime application	other	Environment	Industrial Communication

Further information

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
 Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
 Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/ic10>
 Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UF7910-0AA00-0>
 Cax online generator
<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UF7910-0AA00-0>
 Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3UF7910-0AA00-0>
 Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UF7910-0AA00-0&lang=en



