

1xUSB-A female/female + 1xSUB-D9 female/soldering

Art.No.: 4000-68000-1020000

Weight: 0.040 kg

Country of origin: CZ

Model designation: Fr.Modul 9pol. Bu/Lötanschl. + USB Bu/Bu

USB (form A); SUB-D9

1x USB 2.0 (female/female) form A

1x SUB-D9 (solder connection/female)

Link to Product

The image shows the rear panel of a laptop. On the left side, there is a FireWire (IEEE 1394) port, which is a small, rectangular, gold-colored connector. To its right is a DVI port, which is a larger, rectangular connector with a blue plastic insert and a metal frame. Above the FireWire port is a small circular hole, and below it is another small circular hole. To the right of the DVI port are two small circular holes, one above and one below the port. At the bottom of the panel, there is a long, narrow, rectangular slot, likely for a battery or a hard drive.

Product may differ from Image



Material short text Fr.Modul 9pol. Bu/Lötanschl. + USB Bu/Bu

URL Webshop	https://shop.murrelektronik.com/4000-68000-1020000
GTIN	4048879037723
ECLASS-6.0	27189217
ECLASS-6.1	27189217
ECLASS-7.0	27189217
ECLASS-7.1	27189217
ECLASS-8.0	27189217
ECLASS-8.1	27189217
ECLASS-9.0	27182806
ECLASS-9.1	27189217
ECLASS-10.0.1	27182806
ECLASS-10.1	27182806
ECLASS-11.0	27182806
ECLASS-11.1	27182806
ECLASS-12.0	27182806
ECLASS-13.0	27182806

ECLASS-14.0	27182806
ETIM-5.0	EC002625
ETIM-6.0	EC002625
ETIM-7.0	EC002625
ETIM-8.0	EC002625
customs tariff number	85366990
EAN	4048879037723
Packaging unit	1

Mechanical data | Mounting data

Height	88 mm
Width	51 mm
Depth	70,4 mm

Environmental characteristics | Climatic

Ambient temperature (storage, transport)	-10 °C ... 60 °C
--	------------------

USB

USB specification	2.0
Looking techniques	Snap-in connector
Data transmission rate max.	480 Mbit/s
Operating voltage AC	48 V
Operating voltage DC	48 V
Operating current max.	500 mA
Operating voltage DC (UL-listed)	42,4 V

SUB-D9

Family construction form	SUB-D9
Gender	female
No. of poles	9
Looking techniques	Standard UNC 4-40 screw thread bolt (EN 60807)
Family type Back side	SUB-D9
Gender Rear	Solder connection
Operating voltage AC	48 V
Operating voltage DC	48 V
Operating current	3 A
Operating voltage AC max. (UL-listed)	30 V
Operating voltage DC max. (UL-listed)	42,4 V
Current operating max. (UL)	175 mA