

MODLINK MSDD DATA INSERT

1xUSB-A fem./fem. + 1xRJ45 + 2xPS2 fem./sold.
Art.No.: 4000-68000-1530000
Weight: 0.080 kg
Country of origin: DE
Model designation: Fr.Modul USB Bu/Bu+RJ45/45+2xPS2 gesch.

USB (form A); RJ45; PS2; PS2
1x RJ45, 8-pole metal, CAT5e (female/female)
1x USB 3.0 (female/female) form A
2x PS2 (6-pole solder connection)

Link to Product

Illustration



Product may differ from Image



Header	
Material short text	Fr.Modul USB Bu/Bu+RJ45/45+2xPS2 gesch.
Commercial data	
URL Webshop	https://shop.murrelektronik.com/4000-68000-1530000
GTIN	4048879037457
ECLASS-6.0	27189217
ECLASS-6.1	27189217
ECLASS-7.0	27189217
ECLASS-7.1	27189217
ECLASS-8.0	27189217
ECLASS-8.1	27189217
ECLASS-9.0	27182806
ECLASS-9.1	27189217
ECLASS-10.0.1	27182806
ECLASS-10.1	27182806
ECLASS-11.0	27182806
ECLASS-11.1	27182806
ECLASS-12.0	27182806

ECLASS-13.0	27182806
ECLASS-14.0	27182806
ETIM-5.0	EC002625
ETIM-6.0	EC002625
ETIM-7.0	EC002625
ETIM-8.0	EC002625
customs tariff number	85366990
EAN	4048879037457
Packaging unit	1

Mechanical data | Mounting data

Height	88 mm
Width	51 mm
Depth	70,4 mm

Environmental characteristics | Climatic

Ambient temperature (storage, transport)	5 °C ... 40 °C
--	----------------

Shielding plate

Connection information	Threaded hole M4
Tightening torque	0,9 Nm
Tightening torque tolerance	± 0,1 Nm

USB

USB specification	3.0
Looking techniques	Snap-in connector
Data transmission rate max.	5.000 Mbit/s
Operating voltage AC	48 V
Operating voltage DC	48 V
Operating current	1,5 A
Operating voltage AC max. (UL-listed)	30 V
Operating voltage DC max. (UL-listed)	42,4 V

RJ45

Family construction form	RJ45
Looking techniques	Snap-in connector
Cable category min.	Cat5e
Family type Back side	RJ45
Operating voltage AC max. (UL-listed)	30 V
Operating voltage DC max. (UL-listed)	42,4 V
Current operating max. (UL)	175 mA

PS2

Family construction form	PS2
Gender	female
No. of poles	6
Looking techniques	Screw locking
Connection cross section max.	0,5 mm ²
AWG number max.	20
Family type Back side	PS2
Gender Rear	Solder connection
Operating voltage AC	30 V
Operating voltage DC	30 V
Operating current	1 A