


Product: [8779MN](#)

[Request Sample](#)

SpaceMaker™, 4 Pr #22 Str TC, PO Ins, IS/OS, PVC Jkt, AWM 2937

Product Description

SpaceMaker™, 4 Pair 22AWG (19x34) Tinned Copper, PO Insulation, Individual & Overall Beldfoil® Shield, PVC Outer Jacket, AWM 2937

Technical Specifications
Construction Details
Conductor

| Element | No. of Elements | Size | Stranding | Material |
|---------|-----------------|--------|-----------|--------------------|
| Pair(s) | 4 | 22 AWG | 19x34 | TC - Tinned Copper |

Insulation

| Element | Material | Nom. Thickness | Nom. Insulation Diameter | Color Code |
|---------|--------------------|--------------------|--------------------------|---|
| Pair(s) | PP - Polypropylene | 0.010 in (0.25 mm) | 0.050 in (1.3 mm) | Black & White, Red & Green, Brown & Blue, Orange & Yellow |

Inner Shield

| Shield Type | Material | Coverage | Drainwire Type |
|-------------|-------------------------|----------|-------------------|
| Tape | Bi-Laminate (Alum+Poly) | 100% | 24 AWG (19x36) TC |

Outer Shield

| Shield Type | Material | Coverage | Drainwire Type |
|-------------|-------------------------|----------|-------------------|
| Tape | Bi-Laminate (Alum+Poly) | 100% | 22 AWG (19x34) TC |

Outer Jacket

| Material | Nom. Thickness | Nom. Diameter |
|--------------------------|--------------------|---------------|
| PVC - Polyvinyl Chloride | 0.016 in (0.41 mm) | 0.268 in |

Overall Cable Diameter (Nominal): 0.268 in

Electrical Characteristics
Electricals

| Nom. Conductor DCR | Nom. Capacitance Cond-to-Cond | Nom. Capacitance Cond-to-Other (Conds + Shield) | Nom. Characteristic Impedance | Nom. Inductance | Max. Current |
|--------------------|-------------------------------|---|-------------------------------|----------------------------------|--------------------------------|
| 18.1 Ohm/1000ft | 33 pF/ft (110 pF/m) | 62.7 pF/ft (206 pF/m) | 51 Ohm | 0.18 μ H/ft (0.59 μ H/m) | 4.8 Amps per Conductor at 30°C |

Voltage

| UL Voltage Rating |
|-------------------|
| 300 V |

Mechanical Characteristics
Temperature

| UL Temperature | Operating |
|----------------|----------------|
| 80°C | -20°C to +80°C |

Bend Radius

| Stationary Min. | Installation Min. |
|---------------------|-------------------|
| 1.072 in (27.23 mm) | 1.072 in |

| | |
|--------------------|--------------------|
| Max. Pull Tension: | 91.4 lbs (41.5 kg) |
| Bulk Cable Weight: | 43 lbs/1000ft |

Standards and Compliance

| | |
|----------------------------------|---|
| Environmental Suitability: | Indoor |
| Flammability / Reaction to Fire: | FT2 |
| AWM Compliance: | AWM 2937 |
| European Directive Compliance: | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.321 Revision Date: 09-07-2025 |
|----------------------|--|

Part Numbers

Variants

| Item # | Color | UPC |
|----------------|-------------|--------------|
| 8779MN 006100 | Blue, Light | 612825393122 |
| 8779MN 0061000 | Blue, Light | 612825393139 |
| 8779MN 008100 | Gray | 612825393146 |
| 8779MN 0081000 | Gray | 612825393153 |
| 8779MN 004100 | Yellow | 612825393108 |
| 8779MN 0041000 | Yellow | 612825393115 |

© 2026 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.