


Product: [89841](#)
RS485, 1 Pr #24 Str TC, FEP Ins, OS+TC Brd, FEP Jkt, CMP
[Request Sample](#)
Product Description

RS-485, 1 Pair 24AWG (7x32) Tinned Copper, FEP Insulation, Overall Beldfoil®+Tinned Copper Braid(90%) Shield, FEP Outer Jacket, CMP

Technical Specifications
Product Overview

Suitable Applications: RS-485, POS; Computer communications; Low Voltage Analog Signals (4-20mA, 0-10V, ...); Low Voltage Digital Control (24V, ...); Line Level Audio; Panel Wiring; serial communication (RS-485 standard) comprising of PLCs, VFDs, HMIs, motors, RTU, SCADA, etc. within noisy environments over long distance, etc.

Construction Details
Conductor

| Element | No. of Elements | Size | Stranding | Material |
|---------|-----------------|--------|-----------|--------------------|
| Pair(s) | 1 | 24 AWG | 7x32 | TC - Tinned Copper |

Insulation

| Element | Material | Nom. Thickness | Nom. Insulation Diameter | Color Code |
|---------|---|--------------------|--------------------------|---------------------------------------|
| Pair(s) | FEP - Fluorinated Ethylene Propylene (Foam) | 0.025 in (0.64 mm) | 0.074 in (1.9 mm) | White/Blue Stripe & Blue/White Stripe |

Outer Shield

| Shield Type | Material | Coverage | Drainwire Type |
|-------------|-------------------------|----------|------------------|
| Tape | Bi-Laminate (Alum+Poly) | 100% | 24 AWG (7x32) TC |
| Braid | Tinned Copper (TC) | 90% | |

Outer Jacket

| Material | Nom. Thickness | Nom. Diameter |
|--------------------------------------|--------------------|--------------------|
| FEP - Fluorinated Ethylene Propylene | 0.015 in (0.38 mm) | 0.204 in (5.18 mm) |

Overall Cable Diameter (Nominal): 0.204 in (5.18 mm)

Electrical Characteristics
Electricals

| Element | Nom. Conductor DCR | Nom. Capacitance Cond-to-Cond | Nom. Capacitance Cond-to-Other (Conds + Shield) | Nom. Characteristic Impedance | Nom. Velocity of Prop. | Max. Current |
|---------|--------------------|-------------------------------|---|-------------------------------|------------------------|------------------------------|
| Pair(s) | 24 Ohm/1000ft | 12 pF/ft (39 pF/m) | 22 pF/ft (72 pF/m) | 120 Ohm | 76% | 4 Amps per Conductor at 25°C |

Nom Outer Shield DCR: 3.1 Ohm/1000ft (10 Ohm/km)

High Frequency (Nominal/Typical)

| Element | Frequency [MHz] | Nom. Insertion Loss (Attenuation) |
|---------|-----------------|-----------------------------------|
| Pair(s) | 1 | 0.6 dB/100ft |

Voltage

| UL Voltage Rating |
|-------------------|
| 300 V (CMP) |

Mechanical Characteristics

Temperature

| UL Temperature | Operating |
|----------------|-----------------|
| 200°C | -70°C to +200°C |

Bend Radius

| Stationary Min. | Installation Min. |
|-------------------|-------------------|
| 2.25 in (57.2 mm) | 2.25 in (57.2 mm) |

Max. Pull Tension: 45.7 lbs (20.7 kg)

Bulk Cable Weight: 27 lbs/1000ft

Standards and Compliance

| | |
|----------------------------------|--|
| Environmental Suitability: | Indoor, Oil Resistance |
| Flammability / Reaction to Fire: | NFPA 262, UL 910 (Plenum), FT6, IEC 60332-1-2 |
| CPR Compliance: | CPR Euroclass: Eca |
| NEC / UL Compliance: | Article 800, CMP |
| CEC / C(UL) Compliance: | CMP |
| European Directive Compliance: | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| UK Regulation Compliance: | UKCA Mark |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) |
| Non-Plenum Number: | 9841, 9841ZH |

Product Notes

| | |
|--------|-----------------------|
| Notes: | Oil and Gas Resistant |
|--------|-----------------------|

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.577 Revision Date: 09-07-2025 |
|----------------------|--|

Part Numbers

Variants

| Item # | Color | UPC | Footnote |
|---------------|-------|--------------|----------|
| 89841 0021000 | Red | 612825221302 | C |
| 89841 002500 | Red | 612825221319 | |
| 89841 0025000 | Red | 612825221326 | |

Footnote: C - CRATE REEL PUT-UP.

© 2026 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.