




APPROVED: _____
DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-	7790	RELEASED	5/10/07	
A		REVISED SPEC.	2/22/12	



RECOMMENDED
PCB LAYOUT

SPECIFICATIONS:

Material:

Insulator: Hi-temp thermoplastic, rated UL 94V-0

Insulator color: Natural

Contacts: Brass

Plating:

Tin over Nickel underplate overall

Electrical:

Operating voltage: 350 V AC/DC

Current rating: 3 V AC/DC

Contact resistance: 20 mohms max

Insulation resistance: 1000 Mohms min

Dielectric withstanding voltage: 500 VAC for 1 minute

Temperature Rating:

Operating temperature: -25°C to +85°C

Environmental:

Lead free, RoHS compliant.



Positions: 02 thru 15
A=.059 [1.50] X No. of (Positions -1)
B=.059 [1.50] X No. of (Positions -1) + .110 [2.80]

ADAM TECH

909 Railway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

MX1.5mm WAFER 90°, SURFACE MOUNT

2 THRU 15 POSITIONS

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM] TOLERANCES: EXCEPT AS NOTED				TITLE			
.X	± .10	ØX	± .10	MX1.5mm WAFER 90°, SURFACE MOUNT			
.XX	± .020	ØXX	± .015	2 THRU 15 POSITIONS			
.XXX	± .015	ØXXX	± .010				
APPROVALS				DATE			
DRAWN	BW			5/10/07			
CHECKED							
APPROVED							
SIZE				PART NO.			
X				15SH-B-XX-TR-SMT			
REF:				SCALE: NTS			
				SHEET 1 OF 1			