


Data sheet chainflex® CF11



Data cable (Class 6.6.4.1) ● For extremely heavy duty applications ● TPE outer jacket
● Shielded ● Twisted pair ● Oil and bio-oil resistant ● PVC and halogen-free
● Hydrolysis and microbe-resistant



1. Outer jacket: Pressure extruded, halogen-free TPE mixture
2. Overall shield: Extremely bending-resistant braiding made of tinned copper wires
3. Inner jacket: Pressure extruded, gusset-filling TPE mixture
4. Core insulation: Mechanically high-quality TPE mixture
5. Conductor: Fine-wire strand in especially bending-stable version consisting of bare copper wires
6. Strain relief: Tensile stress-resistant centre element



igus 4-year
chainflex cable
guarantee and
service life
calculator based
on 2 billion test
cycles per year

Example image

For detailed overview please see design table

Cable structure



Conductor



Core insulation



Core structure



Core identification



Inner jacket



Overall shield



Outer jacket

Stranded conductor in especially bending-resistant version consisting of bare copper wires (following DIN EN 60228).

Mechanically high-quality TPE mixture.

Cores twisted in pairs with a short pitch length, core pairs then wound with short pitch lengths.

Cores < 1.0mm²: Colour code in accordance with DIN 47100
Cores ≥ 1.0mm²: Black cores with white numbers.

TPE mixture adapted to suit the requirements in e-chains®.

Extremely bending-resistant braiding made of tinned copper wires.
Coverage linear approx. 70%, optical approx. 90%

Low-adhesion, extremely abrasion-resistant and highly flexible TPE mixture, adapted to suit the requirements in e-chains®.
Colour: Steel-blue (similar to RAL 5011)
Printing: white

„00000 m** igus chainflex CF11.---.02① ---② E310776

RU AWM Style 22357 90°C 300V EAC CE UKCA RoHS-II conform

www.igus.eu

+++ chainflex cable works +++

* Length printing: Not calibrated. Only intended as an orientation aid.
① / ② Cable identification according to Part No. (see technical table).
Example: ... chainflex CF11.01.04.02 (4x(2x0.14))C EAC ...



Data sheet chainflex® CF11



Data cable (Class 6.6.4.1) ● For extremely heavy duty applications ● TPE outer jacket
● Shielded ● Twisted pair ● Oil and bio-oil resistant ● PVC and halogen-free
● Hydrolysis and microbe-resistant

Dynamic information



	Bend radius	e-chain® linear flexible fixed	minimum 6.8 x d minimum 5 x d minimum 4 x d	
	Temperature	e-chain® linear flexible fixed	-35°C up to +100°C -50°C up to +100°C (following DIN EN 60811-504) -55°C up to +100°C (following DIN EN 50305)	
	v max.	unsupported gliding	10m/s 6m/s	
	a max.		100m/s ²	
	Travel distance	Unsupported travels and up to 400m and more for gliding applications, Class 6		



These values are based on specific applications or tests. They do not represent the limit of what is technically feasible.

Guaranteed service life according to guarantee conditions

Double strokes	5 million	7.5 million	12.5 million
Temperatur, von/bis [°C]	R min. [x d]	R min. [x d]	R min. [x d]
-35/-25	7.5	8.5	9.5
-25/+90	6.8	7.5	8.5
+90/+100	7.5	8.5	9.5

Minimum guaranteed service life of the cable under the specified conditions.

The installation of the cable is recommended within the middle temperature range.

Electrical information

	Nominal voltage	300/300V (following DIN VDE 0298-3) 300V (following UL)
	Testing voltage	150 V (following DIN EN 50395)

Example image

igus® chainflex® CF11

Data sheet chainflex® CF11



Data cable (Class 6.6.4.1) ● For extremely heavy duty applications ● TPE outer jacket
● Shielded ● Twisted pair ● Oil and bio-oil resistant ● PVC and halogen-free
● Hydrolysis and microbe-resistant

Properties and approvals



	UV resistance	High
	Oil resistance	Oil-resistant (following DIN EN 60811-404), bio-oil-resistant (following VDMA 24568 with Plantocut 8 S-MB tested by DEA), Class 4
	Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)
	Halogen-free	Following DIN EN 60754
	PTFE-free	The design of these products does not contain PTFE
	UL-verified	Certificate No. V293650: „igus 4-year chainflex cable guarantee and service life calculator based on 2 billion test cycles per year“
	UL AWM	Details see table UL AWM (from production date 01/2022)
	REACH	In accordance with regulation (EC) No. 1907/2006 (REACH)
	Lead-free	Following 2011/65/EC (RoHS-II/RoHS-III)
	Cleanroom	According to ISO Class 1. The outer jacket material of this series complies with CF9.15.07 - tested by IPA according to standard DIN EN ISO 14644-1
	Dry cleanroom	Tested in „dry cleanroom“ according to DIN EN ISO 14644-1, Report No. IG 2405-1526
	CE	Following 2014/35/EU



Properties and approvals

UL AWM details

Conductor nominal cross section [mm ²]	Number of cores	UL style core insulation	UL style outer jacket	UL Voltage Rating [V]	UL Temperature Rating [°C]
0.14	8-36	11884	22357	300	90
0.25	2-28	11884	22357	300	90
0.34	16	11884	22357	300	90
0.5	8-16	11884	22357	300	90
0.75	6	11884	22357	300	90
1	8	11884	22357	300	90
1.5	12	11884	22357	300	90

Example image
igus® chainflex® CF11


Data sheet chainflex® CF11



Data cable (Class 6.6.4.1) ● For extremely heavy duty applications ● TPE outer jacket
● Shielded ● Twisted pair ● Oil and bio-oil resistant ● PVC and halogen-free
● Hydrolysis and microbe-resistant

Typical lab test setup for this cable series

Test bend radius R	approx. 38 - 115 mm
Test travel S	approx. 1 - 15 m
Test duration	minimum 2 - 4 million double strokes
Test speed	approx. 0.5 - 2 m / s
Test acceleration	approx. 0.5 - 1.5 m / s ²



Typical application areas

- For heavy-duty applications, Class 6
- Unsupported travels and up to 400m and more for gliding applications, Class 6
- Almost unlimited resistance to oil, also with bio-oils, Class 4
- No torsion, Class 1
- Indoor and outdoor applications, UV-resistant
- Storage and retrieval units for high-bay warehouses, machining units/machine tools, quick handling, cleanroom, semiconductor insertion, outdoor cranes, low-temperature applications

Example image



Data sheet

chainflex® CF11



Data cable (Class 6.6.4.1) ● For extremely heavy duty applications ● TPE outer jacket
 ● Shielded ● Twisted pair ● Oil and bio-oil resistant ● PVC and halogen-free
 ● Hydrolysis and microbe-resistant

Technical tables:

Mechanical information

Art.-Nr.	Number of cores and conductor nominal cross section	Outer diameter (d) max.	Copper index	Weight
	[mm ²]	[mm]	[kg/km]	[kg/km]
CF11.01.04.02	(4x(2x0.14))C	7.5	30	63
CF11.01.18.02	(18x(2x0.14))C	12.5	101	202
CF11.02.01.02	(2x0.25)C	6.0	17	39
CF11.02.02.02 ²⁾	(2x(2x0.25))C	6.5	26	47
CF11.02.03.02	(3x(2x0.25))C	8.0	35	78
CF11.02.04.02	(4x(2x0.25))C	8.5	42	90
CF11.02.05.02	(5x(2x0.25))C	9.0	49	100
CF11.02.06.02	(6x(2x0.25))C	10.0	69	125
CF11.02.10.02	(10x(2x0.25))C	13.5	103	207
CF11.02.14.02	(14x(2x0.25))C	14.0	124	228
CF11.03.08.02	(8x(2x0.34))C	13.0	106	209
CF11.05.04.02	(4x(2x0.5))C	9.5	77	140
CF11.05.06.02	(6x(2x0.5))C	12.0	103	198
CF11.05.08.02	(8x(2x0.5))C	14.5	135	251
CF11.07.03.02	(3x(2x0.75))C	10.5	83	155
CF11.10.04.02	(4x(2x1.0))C	12.5	125	232
CF11.15.06.02	(6x(2x1.5))C	16.5	247	420

²⁾ The chainflex® types marked with ²⁾ are cables designed as a star-quad.

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.

G = with green-yellow earth core x = without earth core

Electrical information

Conductor nominal cross section [mm ²]	Maximum conductor resistance at 20 °C (following DIN EN 50289-1-2) [Ω/km]	Max. current rating at 30 °C [A]
0.14	138	2.5
0.25	79	5
0.34	57	7
0.5	39	10
0.75	26	14
1	19.5	17
1.5	13.3	21

The final maximum current rating depends among other things on the ambient conditions, the type of the installation and the number of loaded cores.



Data sheet

chainflex® CF11



Data cable (Class 6.6.4.1) • For extremely heavy duty applications • TPE outer jacket
 • Shielded • Twisted pair • Oil and bio-oil resistant • PVC and halogen-free
 • Hydrolysis and microbe-resistant

Design table

Part No.	Number of cores	Core design	Part No.	Number of cores	Core design
CF11.XX.01.02	2		CF11.XX.08.02	8x2	
CF11.XX.02.02	4		CF11.XX.09.02	9x2	
CF11.XX.03.02	3x2		CF11.XX.10.02	10x2	
CF11.XX.04.02	4x2		CF11.XX.14.02	14x2	
CF11.XX.05.02	5x2		CF11.XX.18.02	18x2	
CF11.XX.06.02	6x2				



Example image



Data sheet chainflex® CF11



Data cable (Class 6.6.4.1) ● For extremely heavy duty applications ● TPE outer jacket
● Shielded ● Twisted pair ● Oil and bio-oil resistant ● PVC and halogen-free
● Hydrolysis and microbe-resistant

Colour code in accordance with DIN 47100

Conductor no.	Colours according to DIN ISO 47100
1	white
2	brown
3	green
4	yellow
5	grey
6	pink
7	blue
8	red
9	black
10	violet
11	grey-pink
12	red-blue
13	white-green
14	brown-green
15	white-yellow
16	yellow-brown
17	white-grey
18	grey-brown

Conductor no.	Colours according to DIN ISO 47100
19	white-pink
20	pink-brown
21	white-blue
22	brown-blue
23	white-red
24	brown-red
25	white-black
26	brown-black
27	grey-green
28	yellow-grey
29	pink-green
30	yellow-pink
31	green-blue
32	yellow-blue
33	green-red
34	yellow-red
35	green-black
36	yellow-black



igus 4-year
chainflex cable
guarantee and
service life
calculator based
on 2 billion test
cycles per year



Example image

