Product data sheet
Characteristics

XGSZ09L2
Radio frequency identification XG, pre wired M12 female connector, cable 2 m, IP67

Main

Range of Product	Telemecanique Radio frequency identification XG
Accessory / separate part category	Connection accessories
Accessory / Separate Part Type	Connecting cable
Accessory / separate part designation	Pre-wired M12 female connector
Accessory / separate part destination	For 24 V DC supply of connection box
Cable length	6.56 ft (2 m)

Complementary

Product Compatibility	TCSAMT31FP XGSZ33ETH
Electrical connection	1 female connector M12 4 pins A coding
Color	Black
Net Weight	0.25 lb(US) (0.115 kg)

Environment

IP Degree of Protection	IP67

Ordering and shipping details

Category	22491-SENS,IDENTIFICATION DEVICE (XGK)
Discount Schedule	DS2
GTIN	3389118314030
Returnability	No
Country of origin	PL

Packing Units

|	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.79 in (2.0 cm)
Package 1 Width	6.10 in (15.5 cm)
Package 1 Length	6.89 in (17.5 cm)
Package 1 Weight	3.03 oz (85.9 g)
Unit Type of Package 2	S02
Number of Units in Package 2	40
Package 2 Height	5.91 in (15 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	8.36 lb(US) (3.792 kg)
Package 3 Height	5.91 in (15 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months

Wiring Diagram

Modbus Connections

Pin no.		Signal
1	Red	+ 24 VDC
2	NC	-
3	Black	0 VDC
4	NC	-