


Data Surge Protector SPD ALPU ALPU-TSU Replacement PCBA RJ45 Terminal Block SASD, -TSU PCB Assy



2250-700

Features

- Models for all Common Ethernet/PoE Protocols
- Shielded RJ-45 or Screw Terminal
- Pole or Wall Mount

Applications

- Telecommunications Base Stations
- WISP/ISP
- IT & Data Centers
- Point-to-Point Links
- Control Lines and Sense Loops
- Oil & Gas

Description

Data surge protector (also known as SPD or lightning protector) 2250-700 from Transtector is an outdoor style SPD that utilizes state of the art technology to protect critical equipment in protocol data networks while remaining transparent to data throughput. This surge protector provides effective protection against electrical transient surges that are generated both by external lightning events and by internal switching events and supports long-term system reliability by absorbing high amounts of transient energy while maintaining a very low clamping voltage. Transtector Data Signal surge protectors are available in stock with same day shipping.


Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Connectors		RJ45 to Terminal Block		
Compatible Cables		Cat5/5e UTP/STP, Cat6/6A STP		
Data Protocols		ALPU-TSU Replace- ment PCBA		
Data Rate			100	Mb/s
Power over Ethernet Protocols			PoE	
Vdc Rating (Data)		48	60	Vdc

Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
Surge Protection Technology		SASD		
Protected Pins		[1,2], [3,6], [4,5], [7,8]		
Protection Modes		L-G, L-L		
10/1000µs Surge Current				
L-G			200	A
8/20µs Surge Current				
L-G			2.5	kA
Vpl 10/1000µs		21.5 @ 200A	86 @ 200A	Vpk
L-G				

Data Surge Protector SPD ALPU ALPU-TSU Replacement PCBA RJ45 Terminal Block SASD, -TSU PCB Assy



2250-700

Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
V _{pl} 8/20μs L-G		27 @ 2.5kA	108 @ 2.5kA	Vpk
Response Time			5	ns

Mechanical Specifications

Size

Length	3.25 in	[82.55 mm]
Width/Diameter	2.9 in	[73.66 mm]
Height	0.6 in	[15.24 mm]
Weight	0.069 lbs	[31.3 g]

Environmental Specifications

Temperature

Operating Temperature	-40 to +80 deg C
Storage Temperature	-40 to +80 deg C

Installation

Mount Type	1101-656-1
------------	------------

Compliance Certifications

Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Data Surge Protector SPD ALPU ALPU-TSU Replacement PCBA RJ45 Terminal Block SASD, -TSU PCB Assy 2250-700](https://www.transtector.com/data-surge-protector-spd-alpu-alpu-tsu-2250-700)

URL: <https://www.transtector.com/data-surge-protector-spd-alpu-alpu-tsu-2250-700>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume liability arising out of the use of any part or document.

