

Super SMA Female Connector Solder Attachment 0.082 inch End Launch PCB, 0.020 inch Pin Diameter, Up to 26.5 GHz



PE517849

Configuration

- SMA Female Connector
- 50 Ohms
- Straight Body Geometry
- Connector Interface Types: End Launch

Features

- Max. Operating Frequency 26.5 GHz
- Good VSWR of 1.3:1
- Gold Plated Beryllium Copper Contact

Applications

- General Purpose Test
- PCB Applications

Description

Pasternack's PE517849 Super SMA Female End Launch PCB Connector is part of our full line of RF components available for same-day shipping. Our SMA female connector operates up to a maximum frequency of 26.5 GHz and offers good VSWR of 1.3:1.

Our SMA female connector PE517849 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		26.5	GHz
VSWR		1.2:1	1.3:1	
Impedance		50		Ohms

Mechanical Specifications

Size

Length	0.49 in [12.45 mm]
Width	0.291 in [7.39 mm]
Height	0.236 in [5.99 mm]
Weight	0.0036 lbs [1.63 g]
Mating Cycles	500 Cycles

Material Specifications

Description	Material	Plating
Contact	Beryllium Copper	Gold
Insulation	PTFE	
Body	Brass	Gold

Environmental Specifications

Temperature

Operating Range	-40 to +125 deg C
-----------------	-------------------

Super SMA Female Connector Solder Attachment 0.082 inch End Launch PCB, 0.020 inch Pin Diameter, Up to 26.5 GHz



PE517849

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Super SMA Female Connector Solder Attachment 0.082 inch End Launch PCB, 0.020 inch Pin Diameter, Up to 26.5 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Super SMA Female Connector Solder Attachment 0.082 inch End Launch PCB, 0.020 inch Pin Diameter, Up to 26.5 GHz PE517849](#)

URL: <https://www.pasternack.com/sma-female-end-launch-pcb-connector-pe517849.html>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PE517849 CAD Drawing

Super SMA Female Connector Solder Attachment 0.082 inch End Launch PCB, 0.020 inch Pin Diameter, Up to 26.5 GHz

