

## Low Loss SMA Male to SMA Male Cable LMR-400 Coax in 6 Inch with Times Microwave Connectors with LF Solder



### FMC0202400LF-06

#### Configuration

- Connector 1: SMA Male
- Connector 2: SMA Male
- Cable Type: LMR-400
- Coax Flex Type: Flexible

#### Features

- Max Frequency 6 GHz
- Shielding Effectivity > 90 dB
- 85% Phase Velocity
- Double Shielded
- PE Jacket

#### Applications

- General Purpose
- Laboratory Use

#### Description

The SMA male to SMA male 6 inch cable using LMR-400 coax, part number FMC0202400LF-06, from Fairview Microwave is in-stock and ships same day. This Fairview SMA to SMA cable assembly has a male to male gender configuration with 50 ohm flexible LMR-400 coax. Fairview Microwave's flexible RF cable assemblies are ideal for applications where tight bends and continual flexure are required. The FMC0202400LF-06 SMA male to SMA male cable assembly operates to 6 GHz. The double shielding of this Fairview cable assembly provides excellent shielding effectiveness of better than 90 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other RF cable assembly value added services including connector orientation or clocking, heat shrink booting and labeling are also available. RF testing can also be performed to document the electrical performance of your cable assembly.

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		6	GHz
VSWR			1.35:1	
Velocity of Propagation		85		%
RF Shielding	90			dB
Capacitance		23.9 [78.41]		pF/ft [pF/m]
Inductance		0.06 [0.2]		uH/ft [uH/m]
DC Resistance Inner Conductor		1.39 [4.56]		Ohms/1000ft [Ohms/Km]
DC Resistance Outer Conductor		1.65 [5.41]		Ohms/1000ft [Ohms/Km]

#### Mechanical Specifications

##### Cable Assembly

Length

6 in [152.4 mm]

## Low Loss SMA Male to SMA Male Cable LMR-400 Coax in 6 Inch with Times Microwave Connectors with LF Solder



### FMC0202400LF-06

Width/Diameter	0.5 in [12.7 mm]
Weight	0.112 lbs [50.8 g]

#### Cable

Cable Type	LMR-400
Impedance	50 Ohms
Inner Conductor Type	Solid
Inner Conductor Material and Plating	Copper Clad Aluminum
Dielectric Type	PE (F)
Number of Shields	2
Shield Layer 1	Tinned Copper
Shield Layer 2	Aluminum Tape
Jacket Material	PE, Black
Jacket Diameter	0.405 in [10.29 mm]

#### Connectors

Description	Connector 1	Connector 2
Type	SMA Male	SMA Male
Impedance	50 Ohms	50 Ohms
Configuration	Straight	Straight
Color	SV	SV
Contact Material and Plating	Brass, Gold	Brass, Gold
Contact Plating Specification	50 $\mu$ " Minimum	50 $\mu$ " Minimum
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Nickel	Brass, Nickel
Hex Size	5/16 inch	5/16 inch

#### Environmental Specifications

Operating Range Temperature      -40 to +85 deg C

#### Compliance Certifications

(see product page for current document)

#### Plotted and Other Data

Notes:

Low Loss SMA Male to SMA Male Cable LMR-400 Coax in 6 Inch with Times Microwave Connectors with LF Solder




## **FMC0202400LF-06**

### **Typical Performance Data**

### **How to Order**

Part Number Configuration:



Example: FMC0202400LF-12 = 12 inches long cable  
FMC0202400LF-100cm = 100 cm long cable

Low Loss SMA Male to SMA Male Cable LMR-400 Coax in 6 Inch with Times Microwave Connectors with LF Solder from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.


For additional information on this product, please click the following link: [Low Loss SMA Male to SMA Male Cable LMR-400 Coax in 6 Inch with Times Microwave Connectors with LF Solder FMC0202400LF-06](#)

URL: <https://www.fairviewmicrowave.com/standard-sma-male-sma-male-cable-lmr400-coax-fmc0202400lf-06-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume liability arising out of the use of any part or document.

# FMC0202400LF-06 CAD Drawing

Low Loss SMA Male to SMA Male Cable LMR-400 Coax in 6 Inch  
with Times Microwave Connectors with LF Solder



 <b>Fairview Microwave</b> an INFINITE brand	
INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5	
SCALE	1 OF 1
NONE	SHEET
A	B

UNLESS OTHERWISE SPECIFIED, LEADING DIMENSIONS ARE INCHES. DIMENSIONS IN [ ] ARE MILLIMETERS. TOLERANCES: $X = \pm 2.5$   FRACTIONS: $XX = \pm 0.02$ [0.5]   $\pm 1/32$ $XXX = \pm 0.005$ [0.13]   ANGLES $\pm 1^\circ$
CABLE LENGTH TOLERANCES: $\pm 1/2 [30.5] + 1 25/64 [62.4] - 0$ $\pm 1/2 [30.5] + 2 1/2 [64.8] + 2 [64.8] - 0$ $\pm 1/2 [30.5] + 2 1/2 [64.8] + 6 [65.2] - 0$ $\pm 1/2 [30.5] + 2 1/2 [64.8] + 6 [65.2] - 0$ $\pm 1/2 [30.5] + 2 1/2 [64.8] + 6 [65.2] - 0$ $\pm 1/2 [30.5] + 2 1/2 [64.8] + 6 [65.2] - 0$
SMA MALE TO SMA MALE CABLE LMR-400 COAX WITH TIMES MICROWAVE CONNECTORS AND RoHS COMPLIANT
DESCRIPTION: SMA MALE TO SMA MALE CABLE LMR-400 COAX WITH TIMES MICROWAVE CONNECTORS AND RoHS COMPLIANT

SIZE	CAGE CODE	DRAWN BY	REV
A	3FKR5	DMAY	B

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

FM DS Rev-D4 A-size

6