

## SuperQ™ 150V N-Channel Power MOSFET

### FEATURES

- Industry leading  $R_{DS(on)}$  in TOLL package
- High short-circuit withstand capability (SCWC)
- 100% UIS tested in production
- Low switching losses,  $Q_{sw}$  and  $E_{oss}$
- 175°C temperature rating


### APPLICATIONS

- Motor control
- Battery disconnect switch
- Switch mode power on primary & secondary

### DESCRIPTION

Engineered for high-efficiency motor drives and battery disconnect switches, this 150V SuperQ MOSFET delivers ultra-low conduction and switching losses in a robust TOLL package. Featuring best-in-class  $R_{DS(on)}$ ,  $Q_{sw}$  and short-circuit handling, it minimizes heat dissipation at both full and partial loads.

### PRODUCT SUMMARY



TOLL

Parameter	Value	Unit
$T_A = 25^\circ\text{C}$		
$V_{DS}$	150	V
$R_{DS(on),max}$	2.5	m $\Omega$
$I_D$	233	A
$Q_G$	123	nC
$Q_{sw}$	8.9	nC
$E_{oss}$	2.6	$\mu\text{J}$



### ORDERING INFORMATION

Part Number	Package	Marking	Packaging
iS15M2R5S1T	TOLL	iS15M2R5S1	13' 2,000pcs T&R




Figure 1: Typical Drain-Source On Resistance




Figure 2: Typical  $C_{oss}$  Stored Energy

ABSOLUTE MAXIMUM RATINGS			
SYMBOL	PARAMETER (T <sub>A</sub> = 25°C unless otherwise specified)	VALUE	UNIT
V <sub>GS</sub>	Gate-to-source voltage	± 20	V
I <sub>D</sub>	Continuous drain current (silicon limited), T <sub>C</sub> = 25°C	233	A
	Continuous drain current (silicon limited), T <sub>C</sub> = 100°C	165	
I <sub>DM</sub>	Pulsed drain current	829	A
P <sub>D</sub>	Power dissipation, T <sub>C</sub> = 25°C	314	W
T <sub>J</sub> , T <sub>stg</sub>	Operating junction, storage temperature	-55 to 175	°C
E <sub>AS</sub>	Avalanche energy, single pulse I <sub>D</sub> = 48.4A, R <sub>GS</sub> = 25Ω	1,171	mJ

THERMAL CHARACTERISTICS					
SYMBOL	PARAMETER (T <sub>A</sub> = 25°C unless otherwise specified)	VALUE			UNIT
		MIN	TYP	MAX	
R <sub>θJC</sub>	Junction-to-case thermal resistance - TOLL	-	-	0.48	°C/W
R <sub>θJA</sub>	Junction-to-ambient thermal resistance <sup>(1)</sup>	-	-	50	°C/W

(1) 40 mm x 40 mm x 1.5 mm epoxy PCB FR4 with 6 cm (one layer, 70 μm thick) copper area for drain connection. PCB is vertical in still air.

ELECTRICAL CHARACTERISTICS (T <sub>A</sub> = 25°C unless otherwise specified)						
SYMBOL	PARAMETER	TEST CONDITIONS	VALUE			UNIT
			MIN	TYP	MAX	
<b>STATIC CHARACTERISTICS</b>						
BV <sub>DSS</sub>	Drain-to-source voltage	V <sub>GS</sub> = 0V, I <sub>D</sub> = 1mA	150	-	-	V
I <sub>DSS</sub>	Drain-to-source leakage current	V <sub>GS</sub> = 0V, V <sub>DS</sub> = 120V, T <sub>J</sub> = 25°C	-	0.2	1	μA
		V <sub>GS</sub> = 0V, V <sub>DS</sub> = 120V, T <sub>J</sub> = 125°C <sup>(2)</sup>	-	-	100	
I <sub>GSS</sub>	Gate-to-source leakage current	V <sub>DS</sub> = 0V, V <sub>GS</sub> = 20V	-	1	100	nA
V <sub>GS(th)</sub>	Gate-to-source threshold voltage	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 321μA	2.5	3.3	4.1	V
R <sub>DS(on)</sub>	Drain-to-source on-resistance	V <sub>GS</sub> = 10V, I <sub>D</sub> = 47A	-	2.0	2.5	mΩ
		V <sub>GS</sub> = 8V, I <sub>D</sub> = 24A	-	2.2	2.8	
g <sub>fs</sub>	Transconductance	V <sub>DS</sub> = 10V, I <sub>D</sub> = 47A	107	215	-	S
<b>DYNAMIC CHARACTERISTICS</b>						
C <sub>iss</sub>	Input capacitance <sup>(2)</sup>	V <sub>GS</sub> = 0V, V <sub>DS</sub> = 75V, f = 100kHz	-	7,560	9,828	pF
C <sub>rss</sub>	Reverse transfer capacitance <sup>(2)</sup>		-	58	75	
C <sub>oss</sub>	Output capacitance <sup>(2)</sup>		-	344	447	
C <sub>o(er)</sub>	Effective output capacitance	V <sub>DS</sub> = 0 to 75V, V <sub>GS</sub> = 0V	-	458	-	
R <sub>G</sub>	Series gate resistance	f = 1MHz	-	1.0	1.4	Ω
t <sub>d(on)</sub>	Turn-on delay time	V <sub>DS</sub> = 75V, V <sub>GS</sub> = 10V, I <sub>DS</sub> = 47A, R <sub>G,EXT</sub> = 0 Ω	-	18.8	-	ns
t <sub>r</sub>	Rise time		-	2.6	-	
t <sub>d(off)</sub>	Turn-off delay time		-	50.0	-	
t <sub>f</sub>	Fall time		-	4.9	-	
<b>GATE CHARGE CHARACTERISTICS</b>						
Q <sub>g</sub>	Gate charge total <sup>(2)</sup>	V <sub>DS</sub> = 75V, I <sub>D</sub> = 30A, V <sub>GS</sub> = 0 to 10V	-	123	160	nC
Q <sub>sw</sub>	Switching charge <sup>(3)</sup>		-	8.9	-	
Q <sub>gd</sub>	Gate to drain charge <sup>(2) (3)</sup>		-	4.9	6.4	
Q <sub>g(th)</sub>	Gate charge at threshold <sup>(3)</sup>		-	20.4	-	
Q <sub>gs2</sub>	Gate to source charge <sup>(3)</sup>		-	4.0	-	
V <sub>plateau</sub>	Gate plateau voltage		-	5.2	-	V
Q <sub>oss</sub>	Output charge <sup>(2)</sup>	V <sub>DS</sub> = 0 to 75V, V <sub>GS</sub> = 0V	-	349	401	nC
E <sub>oss</sub>	Capacitive stored energy		-	2.6	-	μJ
<b>DIODE CHARACTERISTICS</b>						
V <sub>SD</sub>	Diode forward voltage	I <sub>SD</sub> = 47A, V <sub>GS</sub> = 0V	-	0.80	0.90	V
Q <sub>rr</sub>	Reverse recovery charge	V <sub>DS</sub> = 75V, I <sub>F</sub> = 47A,	-	209	-	nC
t <sub>rr</sub>	Reverse recovery time	di/dt = 100A/μs	-	111	-	ns

(2) Defined by design. Not subject to production test.

(3) Q<sub>sw</sub> should be used for switching loss calculations. See Figure 16 for gate charge definitions. For more information see Q<sub>sw</sub> application note on [www.idealsemi.com](http://www.idealsemi.com)




Figure 3: Power Dissipation




Figure 4: Drain Current




Figure 5: Safe Operating Area




Figure 6: Max Transient Thermal Impedance




Figure 7: Typical Output Characteristics




Figure 8: Typical Drain-Source On-Resistance




Figure 9: Typical Transfer Characteristics




Figure 10: Normalized On-State Resistance vs. Temperature




Figure 11: Typical Threshold Voltage




Figure 12: Typical Capacitances




Figure 13: Typical Diode Forward Voltage




Figure 14: Min Drain-Source Breakdown Voltage




Figure 15: Typical Gate Charge








Figure 16: Gate Charge Definitions

## DEVICE DECODER RING



- 1 - iDEAL Semiconductor product
- 2 - Voltage rating divided by 10 (150V)
- 3 - M = N-Channel MOSFET, Standard Threshold
- 4 - Maximum drain-to-source resistance
- 5 - SuperQ™ Generation
- 6 - T = TOLL

## TOLL Package Drawing



SYMBOL	MIN	MAX
A	2.20	2.40
b	0.70	0.90
b1	9.70	9.90
c	0.40	0.6
D	10.28	10.58
D2	3.10	3.50
E	9.70	10.00
E1	7.90	8.60
e	1.20 BSC	
H	11.48	11.880
H1	6.75	7.43
L	1.40	2.10
L1	0.60	0.80
L2	0.500	0.700
θ	10° REF	

Notes:

1. All linear dimensions in millimeters

<b>Revision History</b>		
<b>Version</b>	<b>Date</b>	<b>Comments</b>
1.0	February 2026	Initial Release

## IMPORTANT NOTICE AND DISCLAIMER

IDEAL SEMICONDUCTOR DEVICES, INC. ("IDEAL") PROVIDES THE DATASHEET AND ALL SUPPORTING DESIGN RESOURCES, SAFETY INFORMATION, AND OTHER MATERIALS (THE "RESOURCES") "AS IS". IDEAL AND/OR ITS LICENSORS DO NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE RESOURCES OR THAT SUCH RESOURCES WILL BE SUITABLE FOR YOUR APPLICATION. IDEAL HEREBY DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE, OR NON-INFRINGEMENT.

You are only permitted to use the Resources and any products provided by IDEAL ("Products") in accordance with the operating parameters set forth in the Resources and IDEAL's standard terms and conditions made available at the time of order placement. Please note that the Resources are intended for skilled, technically-trained developers. You are solely responsible for, and IDEAL disclaims all responsibility and liability for: (a) choosing the Products and evaluating the suitability of such Products for the intended application, as well as determining if the information in the Resources is complete for your application; (b) designing, validating and testing the Products in your system; and (c) ensuring your application meets applicable safety, security, regulatory or other industry requirements and standards. IDEAL assumes no liability for any damage or malfunction resulting from improper handling of Products, or use of Products and Resources outside of the specified parameters. You are responsible for consulting the latest datasheet before placing orders.

IDEAL reserves the right to make corrections, modifications, enhancements, improvements and other change to or otherwise discontinue its Resources and Products in its sole discretion at any time without notice. All Products are sold subject to IDEAL's standard terms and conditions made available at the time of order placement.

Mailing Address:

iDEAL Semiconductor Devices, Inc.  
116 Research Drive  
Bethlehem, Pennsylvania, USA 18015  
[info@idealsemi.com](mailto:info@idealsemi.com)