


Part No.	Code No.	A	B	C	D
DF3EA- 2P-2V(21)	CL543-0315-0-21	4.6	2.0	8.5	8.74
DF3EA- 3P-2V(21)	CL543-0316-0-21	6.6	4.0	10.5	10.74
DF3EA- 4P-2V(21)	CL543-0317-0-21	8.6	6.0	12.5	12.74
DF3EA- 5P-2V(21)	CL543-0318-0-21	10.6	8.0	14.5	14.74
DF3EA- 6P-2V(21)	CL543-0319-0-21	12.6	10.0	16.5	16.74
DF3EA- 7P-2V(21)	CL543-0320-0-21	14.6	12.0	18.5	18.74
DF3EA- 8P-2V(21)	CL543-0321-0-21	16.6	14.0	20.5	20.74
DF3EA- 9P-2V(21)	CL543-0322-0-21	18.6	16.0	22.5	22.74
DF3EA-10P-2V(21)	CL543-0323-0-21	20.6	18.0	24.5	24.74
DF3EA-11P-2V(21)	CL543-0324-0-21	22.6	20.0	26.5	26.74
DF3EA-12P-2V(21)	CL543-0325-0-21	24.6	22.0	28.5	28.74
DF3EA-13P-2V(21)	CL543-0326-0-21	26.6	24.0	30.5	30.74
DF3EA-14P-2V(21)	CL543-0327-0-21	28.6	26.0	32.5	32.74
DF3EA-15P-2V(21)	CL543-0328-0-21	30.6	28.0	34.5	34.74

Notes

- 1 It shows configuration of 2 to 6 position.
- 2 If there is pattern on  part, there is a possibility that it will make contact with the leads.
3. Lead co-planarity include reinforced metal fittings shall be 0.1mm MAX.

						5		Polyester		Clear(Cover tape)		
2	Brass	Surface: Tin plated 1μm MIN (Under plating)Copper plated 0.5μm MIN				4		PS		Clear(Embossed carrier tape)		
						3		Brass		Surface: Tin plated 1μm MIN (Under plating)Nickel plated 1μm MIN		
1	Polyamide	Natural(Beige), UL94V-0										
NO.	MATERIAL	FINISH . REMARKS				NO.		MATERIAL		FINISH . REMARKS		
UNITS mm				SCALE 5 : 1		COUNT 3	DESCRIPTION OF REVISIONS DIS-H-00003426		DESIGNED TO. KUROMATSU		CHECKED TS. FUKUSHIMA	DATE 18. 01. 16
 HIROSE ELECTRIC CO., LTD.				APPROVED : KI. AKIYAMA		15. 12. 17		DRAWING NO.		EDC-367142-21-00		
				CHECKED : TS. FUKUSHIMA		15. 12. 17		PART NO.		DF3EA-*P-2V(21)		
				DESIGNED : HT. SATO		15. 12. 17		CODE NO.		CL543-		
				DRAWN : MI. SAKIMURA		15. 12. 17				 		

