



Feb.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



NOTE 1. PER TRAY:100 PIECES.
2. REFER TO THE DF59 SERIES MATING/UNMATING OPERATION INSTRUCTION MANUAL(ETAD-H0496)
FOR THE OPERATING OF THE PRODUCT.
3. UL(FILE NO. E52653).
C-UL(FILE NO. E52653) APPROVED PRODUCT.




				3		PS		CLEAR											
				2		BRASS		CONTACT AREA : GOLD PLATING 0.2μm MIN UNDER PLATING : NICKEL PLATING 0.5μm MIN											
1		PBT		UL94V-0 , NATURAL(WHITE)															
NO.		MATERIAL		FINISH .		REMARKS		NO.		MATERIAL		FINISH .		REMARKS					
UNITS mm				SCALE 5 : 1				COUNT 1		DESCRIPTION OF REVISIONS DIS-H-00000436				DESIGNED TS. KUMAZAWA		CHECKED TS. FUKUSHIMA		DATE 15. 05. 15	
 HIROSE ELECTRIC CO., LTD.				APPROVED : KI. AKIYAMA				10. 10. 20		DRAWING NO. EDC3-332594-01									
				CHECKED : OM. MIYAMOTO				10. 10. 20		PART NO. DF59-2P-2SP(50)									
				DESIGNED : KT. ISHII				10. 10. 20		CODE NO. CL667-0017-0-50									
				DRAWN : KT. ISHII				10. 10. 20		  									

Operation Procedures for Crimp Socket

【 Mating 】


1. By positioning the convexity of the short circuit pin sides to the receptacle concavity, align the centers of the short circuit pin and the receptacle in pitch direction.

2. Press down at the center surface of short circuit pin.
Note>Press down until the short circuit pin touches to the receptacle.



【 Unmating 】

1. Hook the lever with finger and lift up to the upper direction for unlock.



HRS

図番： EDC3-332594-01
製品名： DF59-2P-2SP<50>
製品コード CL667-0017-0-50

3/2/2