

Dec.1.2025 Copyright 2025 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

1		2		3		4	
A						A	
B						B	
C						C	
D						D	
E						E	
F						F	

Technical drawing showing a screw head and a side view of the screw assembly. The top view shows a hexagonal head with a diameter of 3.6 mm (reference) and a height of 2.5 ± 0.15 mm. The side view shows a screw with a length of 14.4 mm (reference) and a thread of M2.3X0.4. Callouts 1 and 2 point to the head and the screw body respectively.

NOTE 1 THIS PRODUCT IS ASSEMBLED TO A "DH60-**P".
THE APPLICABLE PANEL THICKNESS IS FROM 1.4 TO 1.6mm.

2 THIS PRODUCT IS PACKED IN A BAG. (QUANTITY IN A BAG : 200pcs.)

1 ASSEMBLED(1:1)

1	STEEL	OVER PLATING : NICKEL 5μm MIN UNDER PLATING : COPPER 1μm MIN	2	STEEL	OVER PLATING : NICKEL 5μm MIN UNDER PLATING : COPPER 1μm MIN
NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS

UNITS mm		SCALE 4 : 1	COUNT 1	DESCRIPTION OF REVISIONS DIS-E-003059	DESIGNED MO. SHIMOYAMA	CHECKED KN. ICHIKAWA	DATE 09.12.07
-------------	--	----------------	------------	--	---------------------------	-------------------------	------------------

HIROSE
ELECTRIC
CO., LTD.

APPROVED : AO. SUZUKI 09.04.27

CHECKED : MO. SHIMOYAMA 09.04.24

DESIGNED : TS. ITO 09.04.24

DRAWN : TS. ITO 09.04.24

DRAWING NO. EDC4-126895-00

PART NO. DH-LNA

CODE NO. CL244-0045-0-00

1/1

FORM HC0011-5-51