


Dec.1.2025 Copyright 2025 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
1	RE-F-4613	S.M	M.T	'96.4.2					



HRS DRAWING FOR REFERENCE

NUMBER OF CONTACT	PART NO.	CODE NO.	DRAWING NO.	A	B	C	D	E
60	FX8- 60S-SV(22)	CL578-0201-5-22	ADC3-150674-02	24.6	23.05	20.8	17.4	22.2
80	FX8- 80S-SV(22)	CL578-0203-0-22	ADC3-150740-02	30.6	29.05	26.8	23.4	28.2
90	FX8- 90S-SV(22)	CL578-0204-3-22	ADC3-150675-02	33.6	32.05	29.8	26.4	31.2

NOTE 1 READ CO-PLANARITY SHALL BE 0.1mm.
2 FOR DETAILS, SEE THE SECTION CONCERNING THE DELIVERY FORM ON NEXT PAGE.
3 FOR MODIFICATION, ETC., PREVENTIVE HOLE FOR SINK MARK MAY BE ADDED DEPENDS ON CIRCUMSTANCES.

2	PHOSPHOR BRONZE	CONTACT AREA: GOLD(0.1μm) OVER NICKEL OTHERS: GOLD(FLASH) OVER NICKEL	1	PPS	LIGHT BROWN (UL94V-0)
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
CODE NO. (OLD)		DRAWN	DESIGNED	CHECKED	APPROVED
		S. Morita	J. Matsukawa	M. Tomita	Y. Yoshimura
		95.04.20	95.04.20	95.04.20	95.04.20
DRAWING NO. EDC3-150730-02		PART NO. FX8-***S-SV(22)			
SCALE 5:1		UNITS mm		CODE NO. CL578	
		HRS HIROSE ELECTRIC CO., LTD.		1/2	

TO
PCM

