

The drawing consists of two views: a top view and a side cross-sectional view.

Top View: A hexagonal nut with a central threaded hole. The dimension across the flats is $7^{+0.05}_{-0.15}$ HEX.

Side Cross-sectional View: Shows the assembly of the nut with a cable. Key dimensions and features include:

- Overall height: 13.1 ± 0.3 (with a note (8.1) for the lower section).
- Upper section height: 5 ± 0.3 (with a note (4) for the lower part of this section).
- Lower section height: 1 ± 0.2 (with a note (4.4) for the lower part of this section).
- Outer diameter of the upper part: $\phi 2.3 \pm 0.1$.
- Outer diameter of the lower part: $\phi 0.8 \pm 0.2$.
- Thread specification: $M5 \times 0.5 - 2$.
- Callout 1 points to the upper part of the assembly.
- Callout 2 points to the lower part of the assembly.
- Callout 3 points to the **PRESS FITTING** area.
- The word **CAULKING** is labeled near the bottom of the assembly.

NOTES

1. USE ONLY FOR INSPECTION OF CONTINUITY AND OF VOLTAGE PROOF ETC. FOR CABLE ASSEMBLY, BECAUSE OF NO LOCKING DEVICE.
2. MATED CONNECTOR SHALL BE INSERTED AND WITHDRAWN PERPENDICULARLY BECAUSE OF NO SCOOP-PROOF.

1 2 3 4 FORM No. 22