



- NOTE 1 APPLICABLE CRIMP CONTACT:HR12-SC-212(CL112-0408-9)
WIRE RANGE:AWG#26 TO 30(JACKET DIAMETER:φ1 MAX.)
APPLICABLE CRIMP CONTACT EXTRACTION TOOL:HR12-SC-TP(CL150-0050-3)
- 2 APPLICABLE CRIMP TOOL, REF. NO. 7:HR10A-TC-02(CL150-0041-2)
APPLY TO φ5.3.
- 3 THE RECOMMENDED CLAMP TORQUE, REF. NO. 5:1.5 TO 2N·m.
- 4 ACROSS FLATS HEXAGON HEAD OF REF. NO. 6:1.27.
THE RECOMMENDED CLAMP TORQUE, REF. NO. 6:0.3 TO 0.4N·m.
- 5 LOCTITE 242, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT REF. NO. 1, 6 FOR LOOSENING.
- 6 ONE EXAMPLE OF THE ROTATION OF REF. NO. 1 TO REF. NO. 5 IS SHOWN.
- 7 THE CABLE PULL AND TWISTING STRENGTH AND OTHER CHARACTERISTICS MAY DIFFER, DEPENDING ON THE CABLE STRUCTURE.
PLEASE CONFIRM BEFORE THE USE.

4	BRASS	MATTE FINISH NICKEL PLATED	8	CHLOROPRENE RUBBER	(BLACK)
3	POLYBUTYLENE TEREPHTHALATE	(BLACK) UL94V-0	7	BRASS	
2	STAINLESS STEEL		6	STEEL	NICKEL PLATING M2.6X0.45X2
1	ZINC ALLOY	MATTE FINISH NICKEL PLATED	5	BRASS	MATTE FINISH NICKEL PLATED
NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS

UNITS mm		SCALE 2 : 1	COUNT 	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
-------------	--	----------------	-----------	--------------------------	----------	---------	------



HIROSE
ELECTRIC
CO., LTD.

APPROVED :MO. SATOH

06.12.21

CHECKED :EJ. KUNII

06.12.20

DESIGNED :TO. HORII

06.12.19

DRAWN :MK. SATO

06.12.15

DRAWING
NO.

EDC4-021661-73

PART
NO.

HR10A-7J-4SC(73)

CODE
NO.

CL110-0510-2-73

