


Feb.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
Case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

1					2					3					4				
COUNT	DESCRIPTION OF REVISIONS				BY	CHKD	DATE			COUNT	DESCRIPTION OF REVISIONS				BY	CHKD	DATE		
△							. .			△							. .		
△										△							. .		
△										△							. .		



DETAIL OF MOUNTING GUIDE

NOTE 1 APPLICABLE CONTACT: HR10-PC-212
APPLICABLE WIRE: AWG#26~30 (INSULATOR OUTER DIA. OF ϕ 1 OR LESS)
APPLICABLE TOOL, EXTRACTOR: RP6-SC-TP
② THE RECOMMENDED CLAMP TORQUE OF REF. NO. ⑤: 1.5N · m.
LOCTITE 242, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT
REF. NO. ⑤ FROM LOOSENING.

PANEL CUTOUT
t 0.7~2

3	PBT	(BLACK) UL94V-0			
2	STAINLESS STEEL		5	BRASS	NICKEL PLATING
1	ZINC ALLOY	MATTE FINISH NICKEL PLATED	4	PHOSPHOR BRONZE	NICKEL PLATING
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
CODE NO. (OLD)		CL	DRAWN	DESIGNED	CHECKED
			H.Kishi	H.Kishi	E. Kuni
			05.08.29	05.08.29	05.08.30
DRAWING NO.		PART NO.			
EDC4-025175-73		HR10A-7R-4PC(73)			
SCALE		CODE NO.			
2 : 1		CL110-0505-2-73			
UNITS		1			
mm		1			

HRS

HIROSE ELECTRIC CO., LTD.

CL110-0505-2-73