

1	2	3	4						
COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△△				..	△△				..
△△					△△				..
△△					△△				..
△△					△△				..

A A

SOLDER CUP  
INSIDE DIA. (Ø 0.8)

(1.5)

(10)HEX

A DETAIL OF MOUNTING GUIDE

1.6 +0.1 -0.0

5.1 +0.1 -0.0

Ø8.1 +0.1 -0.1

PANEL CUTOUT  
 $t = 0.7 \sim 2$

NOTE 1 THE RECOMMENDED CLAMP TORQUE OF REF. NO. ⑥ TO BE 1.5 N·m.  
 LOCTITE 242, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO  
 PREVENT REF. NO. ⑥ FROM LOOSENING.

6	BRASS	NICKEL PLATING				
3	POLYAMIDE (BLUE)					
2	STAINLESS STEEL					
1	ZINC ALLOY MATTE FINISH NICKEL PLATED					
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS	
CODE NO. (OLD) CL		DRAWN D. Matsumi 05.11.19	DESIGNED D. Matsumi 05.11.19	CHECKED E. Kunii 05.11.22	APPROVED M. Sato 05.11.24	RELEASED

TO	DRAWING NO.	PART NO.	F
R	EDC4-007769-73	HR10-7R-6P(73)	
	SCALE 2 : 1 UNITS mm	CODE NO. CL110-0034-8-73	1/1
	HIROSE ELECTRIC CO., LTD.		