

Feb.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.




Fig.1(FREE)

Mating Cross Section (Free)

- NOTE.
- ① Mounting side is mated with the receptacle:IT3M-300S-BGA(**) and fixed with the latch.
 - ② Lot No. shall be marked on the indicated position.
 - ③ The indicated mother board and daughter card shall be fastened to the additional reinforcements to prevent the stress on IT3*-300S-BGA(**) solder joints.
 - 4. Please refer to HIROSE document: ETAD-F0347 'IT3 design guideline'.
 - 5. This product consists of 300 signal lines and 270 ground lines.
 - 6. 15pcs of this products are packed in a soft tray.
 - 7. Standard package of 30pcs are packaged in a carton box.

NO.	MATERIAL	FINISH	REMARKS	NO.	MATERIAL	FINISH	REMARKS
3	LCP	BLACK.	UL94V-0	5	Copper Alloy		CONTACT AREA:NICKEL(1.5μm)+GOLD(0.76μm)
2	LCP	GRAY.	UL94V-0	4	Copper Alloy		CONTACT AREA:NICKEL(1.5μm)+GOLD(0.76μm)
1	PBT	BLACK.	UL94V-0				

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	△				
APPROVED : TM. MATSUO			17.05.11	DRAWING NO. EDC-157443-03-00		
CHECKED : MK. EZAKI			17.05.11	PART NO. IT3-300P-40H(03)		
DESIGNED : KT. AIZAWA			17.05.11	CODE NO. CL636-0175-3-03		
DRAWN : KT. AIZAWA			17.05.11	①/1		