







2 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE



RECOMMENDED P.C.B. HOLE PATTERN(t=1.6±0.1)



HRS No.	PART NO.	NUMBER OF CONTACT	A	B	C	D	E
583-0139-9-72	PCN10-20P-2.54DSA(72)	20	43.30	38.10	32.10	29.47	22.86
583-0007-8-72	PCN10-32P-2.54DSA(72)	32	58.54	53.34	47.34	44.71	38.10
583-0488-8-72	PCN10-44P-2.54DSA(72)	44	73.78	68.58	62.58	59.95	53.34
583-0008-0-72	PCN10-50P-2.54DSA(72)	50	81.40	76.20	70.20	67.57	60.96
583-0009-3-72	PCN10-64P-2.54DSA(72)	64	99.18	93.98	87.98	85.35	78.74
583-0010-2-72	PCN10-90P-2.54DSA(72)	90	132.20	127.00	121.00	118.37	111.76
583-0251-9-72	PCN10-100P-2.54DSA(72)	100	144.90	139.70	133.70	131.07	124.46

NOTE 1. AS FOR AUG, 2005.
2. THE DIMENSION IN PARENTHESIS IS FOR REFERENCE.

2,3	BRASS	CONTACT AREA: Ni2.5μm+Au0.2μm
1	PBT	MOUNTING AREA: Ni2.5μm+Sn2μm
NO. MATERIAL		GRAY, UL94V-0

CODE NO. (OLD) CL	DRAWN M. OGAWA	CHECKED H. SAITOU	DESIGNED H. SAITOU	APPROVED K. HAYASHI	RELEASED K. HAYASHI
SCALE 2 : 1		PART NO. PCN10-2.54DSA(72)		FINISH, REMARKS	
UNITS mm		DRAWING NO. EDC3-154145-01		CODE NO. CL583	
HRS		HIROSE ELECTRIC CO., LTD.		FORM NO. 229	