






-  NOTES
1. APPLICABLE WIRE IS AWG #14~#15.
INSULATION DIAMETER ϕ 3.30mm MAX.
WHEN CRIMPING AWG#14 (UL1015 ϕ 3.80mm),
DUE TO THE DESIGN OF INSULATION BARREL,
THE SHAPE OF CRIMP DOES NOT COVER INSULATION.
IT DOES NOT AFFECT THE PRODUCT QUALITY.
REFER TO ATAI-E2926 FOR CRIMP QUALITY STANDARDS.
 2. APPLICABLE CRIMPING MACHINE AND CRIMPING CONDITIONS
(CRIMP HEIGHT etc.) WILL BE SPECIFIED ACCORDING TO
AWG # OR WIRE APPLIED.
 3. ONE PACKAGE CONSISTS OF 100 PCS.

				1	COPPER ALLOY	CONTACT AREA : GOLD PLATING 0.2μm MIN. TERMINAL AREA : TIN PLATING 1μm MIN. UNDER PLATING : NICKEL PLATING 0.5μm MIN.		
NO.	MATERIAL	FINISH , REMARKS			NO.	MATERIAL	FINISH , REMARKS	
UNITS mm		SCALE 5 : 1	COUNT  1	DESCRIPTION OF REVISIONS DIS-E-004877		DESIGNED TY. MIURA	CHECKED AH. KODAMA	DATE 13. 12. 20
 HIROSE ELECTRIC CO., LTD.		APPROVED : RI. TAKAYASU	12. 12. 11	DRAWING NO. EDC3-128190-00				
		CHECKED : AH. KODAMA	12. 12. 11	PART NO. PQ50-15SCA				
		DESIGNED : TY. MIURA	12. 12. 10	CODE NO. CL236-2043-0-00				
		DRAWN : TY. MIURA	12. 12. 10	 1				