



- Notes
- 1 Rotation example of ref. No. ① and ⑥ are shown.
 - ② The recommended tightening torque of ref. No. ⑩ : 0.2 to 0.3 N·m. LOCTITE 243, HENKEL JAPAN or equivalent is recommended to prevent ref. No. ⑩ from loosening.
 - ③ The recommended tightening torque of ref. No. ⑧ : 0.6 to 0.7 N·m.
 - ④ The recommended tightening torque of ref. No. ⑥ : 2 to 3 N·m.
 - ⑤ Clamp movable range of ref. No. ⑦ : 15 max. 8 min.
 - 6 The cable pull and twisting strength and other characteristics may differ, depending on the cable structure, please confirm before the use.

5	Brass ①	Nickel plating	10	Brass ①	Nickel plating	JIS B 1117 M2.6×0.45×2
4	PPS	(Black) UL94V-0	9	Phosphor bronze	Nickel plating	
3	PPS	(Black) UL94V-0	8	Brass ①	Nickel plating	JIS B 1101 M3×0.5×12
2	Copper alloy	Silver plating 5μm min	7	Brass ①	Nickel plating	
1	Brass ①	Nickel plating	6	Brass ①	Nickel plating	
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS	
UNITS mm		SCALE 2 : 1	COUNT ① 6	DESCRIPTION OF REVISIONS DIS-C-00007407	DESIGNED TY. SUZUKI	CHECKED HY. KOBAYASHI
APPROVED : HY. KOBAYASHI 20151210				DRAWING NO. EDC-003427-81-00		
CHECKED : HY. KOBAYASHI 20151210				PART NO. RM21TP-20S(81)		
DESIGNED : KN. IKEHARA 20151210				CODE NO. CL0109-0322-2-81		
DRAWN : KN. IKEHARA 20151210				① 1		