

Jan.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

1		2			3			4		
COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	
△				..	△				..	
△					△				..	
△					△				..	

Technical drawing of a connector. The drawing includes three views: a side view (top left), a front view (top right), and a top view (bottom center). Dimensions are provided for various features, including diameters (e.g.,  $\phi 5.8$ ,  $\phi 5.9$ ,  $\phi 7.1$ ,  $\phi 7.5 \pm 0.5$ ,  $\phi 9^{+0.2}_{-0.4}$ ), lengths (e.g.,  $12 \pm 0.4$ ,  $4.8 \pm 0.2$ ), and radii (e.g.,  $2-R0.5$ ,  $4-R0.5$ ). A callout '1' points to a specific feature on the side view. A watermark 'HRS DRAWING FOR REFERENCE' is overlaid diagonally across the drawing.

1	ELASTOMER	UL94HB BLACK			
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
CODE NO. (OLD)			DRAWN	DESIGNED	CHECKED
			<i>H. Yamaoka</i>	<i>H. Yamaoka</i>	<i>M. Nohmura</i>
			03.7.14	03.7.14	03.7.14
			APPROVED		
			<i>[Signature]</i>		
			RELEASED		

 SCALE 2 : 1 UNITS mm	DRAWING NO. EDC4-124189	PART NO. ST40X-BS(5.8)
	<b>HRS</b> HIROSE ELECTRIC CO., LTD.	CODE NO. CL241-0025-3
		1/1

TO
Q1