



LoRaWAN LPWAN 433MHz COMBINATION FPC ANTENNA

Part Number: L000925-XX
L000926-XX

(see page 07 for details)

FEATURES & BENEFITS

- Low-power, wide-area (LPWA) applications – LoRaWAN®, ITU-T Y.4480
- Internet of Things (IoT) devices
- Smart Home networking, Remote control, monitoring and sensing
- 410 MHz LTE cellular bands 87 and 88, 450 MHz LTE cellular bands 31, 72 and 73
- Different cable length and connector options available

SPECIFICATIONS (Shown as L000925-10 : Others can vary with different cable lengths.)

Frequency Range (MHz)	410 - 430	430 - 435	450 - 470 VSWR
(center frequency)	< 1.6 :1	< 1.5 : 1	< 2.0 : 1
Average Efficiency	26.4 %	25.5 %	25.4 %
Peak Gain	-2.73dBi	-3.05 dBi	-3.16 dBi
Average Gain	-5.78 dB	-5.94 dB	-5.96 dB
Power Handling	5 Watt cw		
Feed Point Impedance	50 ohms		
Polarization	Linear		
Size	47.0 mm x 17.0 mm x 0.2 mm (FPCB + adhesive)		
Weight	< 2.0 g		
Mounting	Acrylic PSA Adhesive		
Mating Connectors	MHF1 and MHF4L type, Refer to page 11		
Cable	L000925-XX: 1.37mm Dia., Refer to page 11,L000926-XX: 1.13mm Dia., Refer to page 11		
Operating Temperature	-40 to +85°C		
Storage Temperature	-40 to +85°C		
Hazardous Materials	A certificate of conformance is available from the product page on TE website.		

Antenna RF Specifications with different cable assemblies

P/N Cable Length/ Connector/Cable OD	RF DATA	Frequency Range (MHz)		
		410 - 430	430 - 435	450 - 470
L000925-05 50 mm MHF 1.37 mm	VSWR	< 2.3:1	< 1.7:1	< 1.3:1
	Avg. Efficiency	16.2 %	17.9 %	19.0 %
	Peak Gain (Max)	-5.04 dBi	-4.49 dBi	-4.33 dBi
	Average Gain	-7.92 dB	-7.47 dB	-7.22 dB
L000925-10 100 mm MHF 1.37 mm	VSWR	< 1.6 :1	< 1.5 :1	< 2.0 :1
	Avg. Efficiency	26.4 %	25.5 %	25.4 %
	Peak Gain (Max)	-2.73dBi	-3.05 dBi	-3.16 dBi
	Average Gain	-5.78 dB	-5.94 dB	-5.96 dB
L000925-15 150 mm MHF 1.37 mm	VSWR	< 2.4 :1	< 2.3 :1	< 2.1 :1
	Avg. Efficiency	25.3 %	24.6 %	27.1 %
	Peak Gain (Max)	-2.88 dBi	-3.02 dBi	-2.50 dBi
	Average Gain	-5.98 dB	-6.09 dB	-5.68 dB
L000925-20 200 mm MHF 1.37 mm	VSWR	< 3.3 :1	< 2.9 :1	< 2.1 :1
	Avg. Efficiency	19.1 %	19.4 %	22.3 %
	Peak Gain (Max)	-4.05 dBi	-4.24 dBi	-3.64 dBi
	Average Gain	-7.19 dB	-7.12 dB	-6.52 dB
L000925-25 250 mm MHF 1.37 mm	VSWR	< 4.0 :1	< 3.4 :1	< 2.0 :1
	Avg. Efficiency	14.8 %	15.5 %	18.2 %
	Peak Gain (Max)	-4.76 dBi	-4.71 dBi	-3.64 dBi
	Average Gain	-8.31 dB	-8.10 dB	-7.41 dB

CABLE LOSS

OD 1.37mm (P/N: 3-2108921)							
Freq. Range (MHz)	400-500	617-960	1427-1517	1690-2400	2496-2690	3300-3800	4400-5000
Cable attenuation (dB/m)	< 2.0	< 2.2	<2.9	< 3.69	< 4.0	<4.5	< 5.0


Antenna RF Specifications with different cable assemblies

P/N Cable Length/ Connector/Cable OD	RF DATA	Frequency Range (MHz)		
		410 - 430	430 - 435	450 - 470
L000926-05 50 mm MHF4L 1.13 mm	VSWR	< 1.8:1	< 1.4:1	< 1.6:1
	Avg. Efficiency	16.3 %	18.1 %	19.1 %
	Peak Gain (Max)	-5.02 dBi	-4.47 dBi	-4.30 dBi
	Average Gain	-7.90 dB	-7.45 dB	-7.20 dB
L000926-10 100 mm MHF4L 1.13 mm	VSWR	< 1.7 :1	< 1.8 :1	< 2.3 :1
	Avg. Efficiency	26.2 %	25.3 %	25.1 %
	Peak Gain (Max)	-2.75 dBi	-3.07 dBi	-3.18 dBi
	Average Gain	-5.80 dB	-5.96 dB	-5.99 dB
L000926-15 150 mm MHF4L 1.13 mm	VSWR	< 3.1 :1	< 3.1 :1	< 2.9 :1
	Avg. Efficiency	24.9 %	24.1 %	26.8 %
	Peak Gain (Max)	-2.91 dBi	-3.05 dBi	-2.54 dBi
	Average Gain	-6.01 dB	-6.12 dB	-5.71 dB
L000926-20 200 mm MHF4L 1.13 mm	VSWR	< 4.3 :1	< 4.0 :1	< 3.1 :1
	Avg. Efficiency	18.7 %	19.8 %	22.8 %
	Peak Gain (Max)	-4.09 dBi	-4.28 dBi	-3.69 dBi
	Average Gain	-7.24 dB	-7.17 dB	-6.56 dB
L000926-25 250 mm MHF4L 1.13 mm	VSWR	< 4.4 :1	< 3.7 :1	< 2.1 :1
	Avg. Efficiency	14.6 %	15.7 %	18.4 %
	Peak Gain (Max)	-4.78 dBi	-4.73 dBi	-3.66 dBi
	Average Gain	-8.34 dB	-8.13 dB	-7.44 dB

CABLE LOSS

OD 1.13mm (P/N: 3-2108921)							
Freq. Range (MHz)	400-500	617-960	1427-1517	1690-2400	2496-2690	3300-3800	4400-5000
Cable attenuation (dB/m)	< 2.0	< 2.2	<2.9	< 3.69	< 4.0	<4.5	< 5.0


RF DATA (Shown as L000925-10 : Others can vary with different cable lengths.)



Data measured in free space and on 150 x 150 x 2.0 mm PC plastic


RADIATION PATTERN

(Shown as L000925-10 : Others can vary with different cable lengths.)



Data measured in free space and on 150 x 150 x 2.0 mm PC plastic

KEEP OUT AREA




NOTES:1. Antenna designed to be mounted on plastic cover.
2. Area in blue above indicates Keep Out Area.
3. For more information, please call TE.

Dimensions: mm
Diagram is not to scale


DIMENSIONS

(Refer to Page07 for dimension "A")




Dimensions: mm
Diagram is not to scale



MATING COMPONENTS TO PART NUMBERS AND DIMENSIONS

L000925-05	50.0	1.968	1.37	MHF-TYPE PLUG	RECEPTACLE (TE PN: 2337019-1)	
L000925-10	100.0	3.937	1.37	MHF-TYPE PLUG	RECEPTACLE (TE PN: 2337019-1)	
L000925-15	150.0	5.905	1.37	MHF-TYPE PLUG	RECEPTACLE (TE PN: 2337019-1)	
L000925-20	200.0	7.874	1.37	MHF-TYPE PLUG	RECEPTACLE (TE PN: 2337019-1)	
L000925-25	250.0	9.842	1.37	MHF-TYPE PLUG	RECEPTACLE (TE PN: 2337019-1)	
L000926-05	50.0	1.968	1.13	MHF4L-TYPE PLUG	RECEPTACLE (TE PN: 2334884-1)	
L000926-10	100.0	3.937	1.13	MHF4L-TYPE PLUG	RECEPTACLE (TE PN: 2334884-1)	
L000926-15	150.0	5.905	1.13	MHF4L-TYPE PLUG	RECEPTACLE (TE PN: 2334884-1)	
L000926-20	200.0	7.874	1.13	MHF4L-TYPE PLUG	RECEPTACLE (TE PN: 2334884-1)	
L000926-25	250.0	9.842	1.13	MHF4L-TYPE PLUG	RECEPTACLE (TE PN: 2334884-1)	
PART	MM	INCH	CABLE O.D (B)	CONNECTOR TYPE	PART NUMBER	IMAGE
NUMBER	CABLE LENGTH (A)			(ON CABLE)	MATING COMPONENTS	

PACKAGING



50pcs (2扎)



TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

For phone numbers in other countries, go to te.com/support-center

te.com

TE Connectivity, TE Connectivity (logo) are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2020 TE Connectivity Ltd. family of companies All Rights Reserved.

07/2024