

**SEARAY™** 8 mm

# SEARAY™ MICRO COAX CABLE ASSEMBLY

(0.80 mm) .0315" PITCH • ESCA SERIES

14  
Gbps



**ESCA**  
Mates:  
SEAM8, SEA8


ESCA	NO. OF PINS PER ROW	NO. OF ROWS	CABLE LENGTH	END 1	END 2
	-20, -30	-08 = Eight Rows	-"XX.X" = Overall Length in Inches (50.8 mm) 02.0" minimum	-1 = SEAM8 without Screw Down	
		-10 = Ten Rows		-2 = SEA8 with Screw Down	
				-3 = SEA8 without Screw Down	
				-4 = SEA8 with Screw Down	

## SPECIFICATIONS

**Cable:**  
34 AWG micro ribbon coax cable  
**Signal Routing:**  
50 Ω Single-Ended  
**Plating:**  
Au over 50 μ" (1.27 μm) Ni  
**Operating Temp Range:**  
-25 °C to +105 °C


NO. PINS PER ROW	A	B	C
-20	(23.65) .931	(28.73) 1.131	(35.20) 1.386
-30	(31.65) 1.246	(36.73) 1.446	(43.20) 1.701

## SIGNAL MAPPING



For complete signal mapping, see [www.samtec.com?ESCA](http://www.samtec.com?ESCA)

For other alternative mapping options, contact [hdr@samtec.com](mailto:hdr@samtec.com).




## Notes:

Cable lengths longer than 40.00" (1 meter) are not supported with S.I. test data.

Design your full cable assembly with Samtec's High-Speed Cable Solutionator® at [www.samtec.com/cablebuilder](http://www.samtec.com/cablebuilder)

Some lengths, styles and options are non-standard, non-returnable.



ESCA-30-08-XX.XX-1-4 SHOWN