MI8A-I/O S SUBD15B

Specific adapter to be connected to the MICROSERIE RELAYS using a 10-pole flat-cable connector or 15-pole Sub-D connector.

General ordering data

Version	Adapter, MICRO-Interface, IEC 60603/DIN41612 plug-in connectors, Screw connection
Order No.	8800220000
Type	MI8A-I/O S SUBD15B
GTIN (EAN)	4032248497157
Qty.	10 pc(s).

Creation date July 9, 2025 9:09:15 AM CEST

MI8A-I/O S SUBD15B

Technical data

Dimensions and weights

Depth	61 mm	Depth (inches)	2.402 inch
Height	42 mm	Height (inches)	1.654 inch
Width	32 mm	Width (inches)	1.26 inch
Net weight	27.456 g		

Temperatures

Storage temperature	-20...85 °C	Operating temperature	0...50 °C

Connection data

Voltage supply	max. 30 V AC/DC

Ratings data

Operating voltage	30 V UC	Max. current per channel	0.5 A
Total operating current	2 A		

Insulation coordination (EN50178)

According to	DIN EN 50178	Rated insulation voltage	< 50 V AC
Surge voltage category	III	Pollution severity level	2
Insulation test voltage AC	0.35 kV		

Supply connection

Type of connection	Screw connection

Classifications

ETIM 6.0	EC002584	ETIM 7.0	EC002584
ETIM 8.0	EC002584	ETIM 9.0	EC002584
ETIM 10.0	EC002584	ECLASS 9.0	27-33-02-92
ECLASS 9.1	27-24-22-92	ECLASS 10.0	27-33-02-92
ECLASS 11.0	27-33-02-92	ECLASS 12.0	27-33-02-92
ECLASS 13.0	27-33-02-92	ECLASS 14.0	27-33-02-92
ECLASS 15.0	27-33-02-92		

Approvals

ROHS	Conform

Environmental Product Compliance

RoHS Compliance Status	Compliant with exemption
RoHS Exemption (if applicable/known)	6al, 6c
REACH SVHC	Lead 7439-92-1 Potassium perfluorobutane sulfonate 29420-49-3
SCIP	a009610c-b9bf-4453-8f5a-4b028e0ef0cc

Downloads

Catalogues	Catalogues in PDF-format

Creation date July 9, 2025 9:09:15 AM CEST

Catalogue status 04.07.2025 / We reserve the right to make technical changes.

2