

## LXP-RS

~9.6° spot beam optimized for CREE XP-E. 14.7 mm high assembly with installation tape.

### SPECIFICATION:

Dimensions	Ø 21.6
Height	14.7 mm
Fastening	tape
ROHS compliant	yes ⓘ




### MATERIALS:

Component	Type	Material	Colour	Finish	Length (mm)
LR1-RS	Single lens	PMMA	clear		
LXP-LH1-TAPE-BLK	Holder	PC	black		
LEILA-TAPE	Tape	Acryl tape	black		

### ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
FA10661_LXP-RS » Box size: 470 x 235 x 270 mm	2304	288	144	11.5




See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)

### OPTICAL RESULTS (MEASURED):



LED XP-E  
FWHM / FWTM 7.5°  
Efficiency 92 %  
Peak intensity 39.7 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files




LED XP-E-HEW  
FWHM / FWTM 10.0°  
Efficiency 92 %  
LEDs/each optic 1  
Light colour/type White  
Required components:

Light distribution files



LED XP-G  
FWHM / FWTM 11.0°  
Efficiency 94 %  
Peak intensity 20.8 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:




Light distribution files

### OPTICAL RESULTS (MEASURED):




LED XP-L HD  
 FWHM / FWTM 16.0° / 28.0°  
 Efficiency 91 %  
 Peak intensity 10 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files




LED XP-L HI  
 FWHM / FWTM 10.0° / 19.0°  
 Efficiency 90 %  
 Peak intensity 22 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files



LED OSLOM Square CSSRM2/CSSRM3  
 FWHM / FWTM 10.0° / 20.0°  
 Efficiency 93 %  
 Peak intensity 21 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:




Light distribution files

### OPTICAL RESULTS (SIMULATED):




LED XP-E2  
 FWHM / FWTM 7.0° / 14.0°  
 Efficiency 92 %  
 Peak intensity 47.5 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files




LED XP-G3  
 FWHM / FWTM 12.0° / 24.0°  
 Efficiency 86 %  
 Peak intensity 14 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files



LED XT-E  
 FWHM / FWTM 9.0° / 20.0°  
 Efficiency 88 %  
 Peak intensity 20.7 cd/lm  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:




Light distribution files

#### OPTICAL RESULTS (SIMULATED):




LED LUXEON CZ  
 FWHM / FWTM 6.0° / 14.0°  
 Efficiency 92 %  
 Peak intensity 53.9 cd/m  
 LEDs/each optic 1  
 Light colour/type Red  
 Required components:



Light distribution files




LED LUXEON V2  
 FWHM / FWTM 11.0° / 24.0°  
 Efficiency 93 %  
 Peak intensity 16 cd/m  
 LEDs/each optic 1  
 Light colour/type White  
 Required components:



Light distribution files



LED NCSxx19B  
 FWHM / FWTM 8.0° / 18.0°  
 Efficiency 91 %  
 Peak intensity 27.6 cd/m  
 LEDs/each optic 1  
 Light colour/type Blue  
 Required components:




Light distribution files

### OPTICAL RESULTS (SIMULATED):




LED NVSxx19B/NVSxx19C  
FWHM / FWTM 12.0° / 24.0°  
Efficiency 87 %  
Peak intensity 14.6 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files




LED LH351C  
FWHM / FWTM 12.0° / 24.0°  
Efficiency 81 %  
Peak intensity 13.5 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files



LED Z5  
FWHM / FWTM 8.0° / 16.0°  
Efficiency 91 %  
Peak intensity 32.5 cd/lm  
LEDs/each optic 1  
Light colour/type White  
Required components:



Light distribution files

### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 7  
FI-24100 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Poznan, Poland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)