

# ILC 2250 BI - Controller



1541303

<https://www.phoenixcontact.com/us/products/1541303>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



The modular Inline controller for automation applications in infrastructure, energy, and buildings is based on the Niagara Framework®.

Four LAN, two USB, and two RS-485 interfaces are integrated.  
The controller can be extended with numerous Inline I/O modules.

## Product description

The ILC 2250 BI is the powerful successor to the ILC 2050 BI, the central controller for automation of buildings, infrastructure, and energy. The industrial design guarantees a high level of reliability and therefore makes the ILC 2250 BI suitable for business-critical applications. It is equipped with 4 LAN, 2 USB, and 2 RS-485 interfaces. The controller can be extended with a wide range of Inline modules for digital and analog I/Os and for all widely used bus systems. The corresponding drivers ensure uniform interfaces, thus greatly simplifying system integration.

## Your advantages

- Time-optimized engineering using the Niagara 4 framework
- Support for all the main communication protocols used in building infrastructure automation
- Effective engineering and visualization with Emalytics and the Niagara Framework
- Easy extension of the Niagara 4 framework with self-programmed functions
- Digital twin as the basis for smart buildings
- Software security with secure boot, signed software, and TPM-protected device identity

## Commercial data

Item number	1541303
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DR18
Product key	DRHAAA
GTIN	4067923013964
Weight per piece (including packing)	317 g
Weight per piece (excluding packing)	237 g
Customs tariff number	85371091
Country of origin	DE

# ILC 2250 BI - Controller

1541303

<https://www.phoenixcontact.com/us/products/1541303>



## Technical data

### Notes

Note on application

Note on application

Only for industrial use

### Product properties

Product family	Inline-Controller
Installation location	indoor use
Installation location	Control cabinet
Special properties	Development process certified in accordance with IEC 62443-4-1

### Insulation characteristics

Protection class	III (IEC 61140, EN 61140, VDE 0140-1)
Oversupply category	II (IEC 60664-1, EN 60664-1)
Pollution degree	2 (IEC 60664-1, EN 60664-1)

### System properties

Trusted Platform Module	TPM 2.0
Retentive data storage	512 kByte (NVRAM)
RAM	2048 Mbyte (LPDDR4-RAM)

### IEC 61131 runtime system

Data storage system	5 GByte (eMMC)
---------------------	----------------

### Functionality

Programming languages supported	Niagara Framework®
---------------------------------	--------------------

### System requirements

Engineering tool	Emalytics
------------------	-----------

### Electrical properties

#### Supply

Current carrying capacity (Terminal points)	8 A
---	-----

#### Real-time clock

Realtime clock	integrated (capacitive buffering)
----------------	-----------------------------------

#### Potentials

Supply voltage	24 V DC -15 % / +20 % (in accordance with EN 61131-2)
Supply voltage range	19.2 V DC ... 30 V DC (including all tolerances, including ripple)
Current draw	≤ 1.5 A
	≤ 170 mA (at nominal voltage without local bus device)

### Connection data

# ILC 2250 BI - Controller

1541303

<https://www.phoenixcontact.com/us/products/1541303>



## Inline connector

Connection method	Spring-cage connection
Conductor cross-section, rigid	0.08 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
Conductor cross-section, flexible	0.08 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
Conductor cross-section AWG	28 ... 16
Stripping length	8 mm

## Interfaces

Supported protocols	BACnet/IP BACnet MS/TP (only at COM1 and COM2) Modbus/TCP Modbus/RTU KNX IP DALI DALI-2 LON IP EnOcean SMI MP-Bus SNMP M-Bus MQTT OPC UA Simple OpenADR LDAP SMS CSV oBIX
Web server	yes

## Ethernet

Bus system	RJ45
Number of interfaces	4
Connection method	RJ45 jack, shielded
Transmission speed	10/100/1000 Mbps
No. of channels	2
Bus system	RS-485
Number of interfaces	2

## USB

Bus system	USB type C
Number of interfaces	2
Connection method	USB type C

# ILC 2250 BI - Controller

1541303

<https://www.phoenixcontact.com/us/products/1541303>



## microSD

Bus system	microSD
Number of interfaces	1 (Top)
Connection method	microSD slot

## Dimensions

Width	80 mm
Height	119.8 mm
Depth	71.5 mm

## Material specifications

Color (Housing)	green (RAL 6021)
-----------------	------------------

## Mechanical tests

Vibration resistance in accordance with EN 60068-2-6/IEC 60068-2-6	: 5g
Shock in accordance with EN 60068-2-27/IEC 60068-2-27	: 30g
Continuous shock in accordance with EN 60068-2-27/IEC 60068-2-27	: 10g

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 55 °C (observe derating)
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Permissible humidity (operation)	0 % ... 75 % (according to DIN EN 61131-2)
Permissible humidity (storage/transport)	0 % ... 75 % (according to DIN EN 61131-2)
Air pressure (operation)	70 kPa ... 106 kPa (up to 3000 m above sea level)
Air pressure (storage/transport)	70 hPa ... 106 kPa (up to 3000 m above sea level)
GRP_Temperature class	T4
Resistance to gases that may endanger the functions, in acc. with DIN 40046-36, DIN 40046-37	Sulfur dioxide (SO <sub>2</sub> ) 10 ±0.3 ppm (test duration: 10 days), hydrogen sulfide (H <sub>2</sub> S) 1 ±0.3 ppm (test duration: 4 days), both at 25°C and with 75% humidity

## EMC data

Electromagnetic compatibility	Conformance with EMC directive
Conformance with EMC directives	Immunity test in accordance with EN IEC 61000-6-2 Transient overvoltage (surge) Criterion B
	Immunity test in accordance with EN IEC 61000-6-2 Fast transients (burst) Criterion A, ±500 V, Criterion B, ±1000 V
	Immunity test in accordance with EN IEC 61000-6-2 Electromagnetic fields Criterion A, Field intensity: 10 V/m
	Immunity test in accordance with EN IEC 61000-6-2 Electrostatic discharge (ESD) Criterion A, ±4 kV contact discharge, ±8 kV air discharge
	Immunity test in accordance with EN IEC 61000-6-2 Conducted disturbance Criterion A, Test voltage 10 V

# ILC 2250 BI - Controller

1541303

<https://www.phoenixcontact.com/us/products/1541303>



Noise emission test in accordance with EN 61000-6-3/IEC 61000-6-3 Class B

## Mounting

Mounting type	DIN rail mounting
Mounting position	horizontal Alternative mounting positions are possible, but can lead to a reduction in thermal performance.

# ILC 2250 BI - Controller

1541303

<https://www.phoenixcontact.com/us/products/1541303>



## Approvals

ⓘ To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1541303>



**cULus Listed**

Approval ID: E238705

# ILC 2250 BI - Controller

1541303

<https://www.phoenixcontact.com/us/products/1541303>



## Classifications

### ECLASS

ECLASS-13.0	27242207
ECLASS-15.0	27242207

### ETIM

ETIM 9.0	EC000236
----------	----------

### UNSPSC

UNSPSC 21.0	32151700
-------------	----------

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(a)-I, 6(c), 7(a), 7(c)-I

### China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

### EU REACH SVHC

REACH candidate substance (CAS No.)	Lead titanium zirconium oxide(CAS: 12626-81-2)
	4,4'-isopropylidenediphenol(CAS: 80-05-7)
	Lead(CAS: 7439-92-1)
	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide(CAS: 75980-60-8)

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)