

Head Office

ADLINK Technology, Inc.
 No. 66, Huaya 1st Rd., Guishan Dist.,
 Taoyuan City 333411, Taiwan
 Tel : +886-3-216-5088
 Fax: +886-3-328-5706

[f](#) [in](#) [s](#) [t](#) [www.adlinktech.com](#)

Worldwide Offices

Ampro ADLINK Technology, Inc.
 6450 Via Del Oro, San Jose, CA 95119-1208, USA
 Tel: +1-408-360-0200
 Toll Free: +1-800-966-5200 (USA only)
 Fax: +1-408-360-0222
 Email: info@adlinktech.com

ADLINK Technology (China) Co., Ltd.
 上海市浦东新区张江高科技园区芳春路300号 (201203)
 300 Fang Chun Rd., Zhangjiang Hi-Tech Park
 Pudong New Area, Shanghai, 201203 China
 Tel: +86-21-5132-8988
 Fax: +86-21-5192-3588
 Email: market@adlinktech.com

ADLINK Technology Beijing
 北京市海淀区上地东路1号盈创动力大厦E座801室
 (100085)
 Rm. 801, Power Creative E, No. 1 Shang Di East Rd.
 Beijing, 100085 China
 Tel: +86-10-5885-8666
 Fax: +86-10-5885-8626
 Email: market@adlinktech.com

ADLINK Technology Shenzhen
 深圳市南山区科技园南区高新南七道数字技术园
 A1栋2楼C区(518057)
 2F, C Block, Bldg. A1, Cyber-Tech Zone, Gao Xin
 Ave. Sec. 7 High-Tech Industrial Park S.,
 Shenzhen, 518054 China
 Tel: +86-755-2643-4858
 Fax: +86-755-2664-6353
 Email: market@adlinktech.com

ADLINK Technology Singapore Pte. Ltd.
 84 Genting Lane #07-02A, Axxel Innovation
 Centre, Singapore 349584
 Tel: +65-6844-2261
 Fax: +65-6844-2263
 Email: singapore@adlinktech.com

ADLINK Technology Singapore Pte Ltd. (Indian Liaison Office)
 #50-56, First Floor, Spearhead Towers
 Margosa Main Road (between 16th/17th Cross)
 Malleswaram, Bangalore - 560 055, India
 Tel: +91-80-42246101, +91-80-23464606
 Fax: +91-80-23464606
 Email: india@adlinktech.com

ADLINK Technology Japan Corporation
 〒101-0045 東京都千代田区神田錦町3-7-4
 ユニゾ神田錦町三丁目ビル4F
 Unizo Kanda Kaji-cho 3 Chome Bldg. 4F,
 3-7-4 Kanda Kajicho, Chiyoda-ku,
 Tokyo 101-0045, Japan
 Tel: +81-3-4455-3722
 Fax: +81-3-5209-6013
 Email: japan@adlinktech.com

ADLINK Technology Korea Ltd.
 경기도 용인시 수지구 신수로 767 A동 1503호
 (동천동, 분당수지유타워) (우) 16827
 A-1503, U-TOWER, 767 Sinsu-ro, Suji-gu,
 Yongin-si, Gyeonggi-do, Republic of Korea, 16827
 Toll Free: +82-80-800-0585
 Tel: +82-31-786-0585
 Fax: +82-31-786-0583
 Email: korea@adlinktech.com

ADLINK Technology, Inc. (Israel Liaison Office)
 MIXER Herzliya (Building B, 9 Floor)
 3 Arik Einstein st., Zip code 4610301
 Herzliya, Israel, P.O.Box - 351
 Tel: +972-54-632-5251
 Fax: +972-77-208-0230
 Email: israel@adlinktech.com

ADLINK Technology GmbH
 Hans-Thoma-Straße 11
 D-68163 Mannheim, Germany
 Tel: +49 621 43214-0
 Fax: +49 621 43214-30
 Email: germany@adlinktech.com

ADLINK Technology, Inc. (French Liaison Office)
 Bâtiment Thalès - Parc des Algorithmes,
 Route de l'Orme des Merisiers,
 91190 SAINT AUBIN, France
 Tel: +33 (0) 1 60 12 35 66
 Fax: +33 (0) 1 60 12 35 66
 Email: france@adlinktech.com

ADLINK Technology, Inc. (UK Liaison Office)
 First Floor West Exeter House,
 Chichester fields Business Park Tangmere,
 West Sussex, PO20 2FU, United Kingdom
 Tel: +44-1243-859677
 Email: uk@adlinktech.com

Responsive, adaptive,
 connected smart factory



**Comprehensive
 Smart Manufacturing
 Solutions**



Visualize Your Field Site for Faster Data-to-Decision

EdgeGO-empowered smart manufacturing solutions that deliver maximum efficiency and security

EdgeGO

"From Automation to Autonomous" has become the latest goal for smart manufacturing, allowing production equipment to independently communicate to prioritize operation processes, detect and analyze abnormalities, and send notifications to OT managers, all via real-time data acquisition. ADLINK's EdgeGO-empowered smart manufacturing solution enables remote management of edge devices, including industrial PCs, smart cameras, and smart data acquisition cards (DAQs) on a single platform.



EdgeGO

Device Management



Event Notification



Dashboard Visualization



Edge Applications



Cloud Connectivity



Edge Security



Why ADLINK

Rely on ADLINK to support you through the process of choosing, configuring, and implementing your solution. Our 25 years of experience in industrial automation have earned us recognition, most recently as one of **BISinfotech's Top 10 Industrial Automation Manufacturers in the World**.

We can put that experience to work for you as you take your operation one step closer to evolving into a smart factory.

Complete Automation Solutions

- Motion control & machine vision
- Data acquisition & PXI control and chassis
- Edge AI vision analysis platform
- AMR
- All-in-one HMI



Local Engineering Teams

- Dedicated to the specific needs of customers in different regions
- Ability to collaborate face-to-face

Deep in Vertical Markets

- Semiconductor
- Optoelectronics
- Electronics Manufacturing
- ESG



Capability

- Electrical, mechanical, firmware & software
- Board- to system-level

Ecosystem Alliance

- Strategic partners with Intel, Nvidia, Arm, Qualcomm
- Worldwide AI software partners
- Leading motor suppliers



Validation

- Aligned with regulatory labs to help support necessary agency approvals
- Humidity, Altitude, EMC, Temperature, Vibration, Salt spray, Shock tests

Smart Manufacturing Solutions

ADLINK offers comprehensive ready-to-deploy solutions for various automation control solutions to accelerate the implementation of Smart Manufacturing in industry

A Motion Control

- Centralized and distributed motion control to match performance and precision positioning

B Machine Vision


- Full spectrum of frame grabbers supporting digital and analog interfaces

C IO Sensing

- Comprehensive slave modules for the bridge connected to EtherCAT

L SOP Compliance

- Fab cleaning procedure management
- Hazmat offload safety management



Product Solutions



Powering the Semiconductor Manufacturing Process



High Efficiency, Precision IC Probe Testing


The electrical input of the silicon wafer measurement signals is invisible to the naked eye. To ensure the probe head accurately touches the wafer, simulation generates a real-time response based on the analog signal between the probe and the wafer.

Solution Features

- High-speed and high-precision Z-axis motion control function increases accuracy up to $0.1\mu\text{m}$
- No vibrating to execute subsequent testing, continuous route detection shortens operation time by 15-20%
- Exceptional compatibility and usability of machine components with unified PC-based interface


Customer Benefits

- Ensured timeliness, enhancing the over probe testing efficiency
- Lower damage ratio and cost of both dies and probe heads. Dies will accurately be tested and not damaged by the probe head.
- Reduced secondary development costs. APS SDK motion software delivers future-proof development.



Fab Clean SOP Compliance

High-precision semiconductor factories use air showers to remove surface-deposited particles from personnel prior to them entering a cleanroom. Using AI to detect whether an employee's behavior complies with SOP can reduce the amount of dust by 80% and improve production quality.



Technological Breakthrough for Laser Dicing


Advanced semiconductor's manufacturing processes are now sub-2nm, and still getting smaller with three-dimensional heterogeneous integration. Miniaturization of chips requires laser dicing equipment with higher precision, higher stability, higher integration, faster positioning, a simpler operating interface, easier speed planning, and instant trigger control feedback.

Solution Features

- 2D compensation support for cutting accuracy up to $0.1\mu\text{m}$
- Built-in speed planning, PID, and closed-loop motion control system minimize tracking errors
- APS SDK software with trajectory setting interface for chip cutting to quickly set and update future processes, reducing secondary development costs
- PC-based system for improved compatibility, more I/O options for different sensors, and synchronization control


Customer Benefits

- Efficient laser dicing through integrated visual alignment and motion control
- High stability for quick positioning, sensor match, laser intensity control, and laser power switch and adjust, shortening operating time by over 10% and saving up to 25-50%
- Automatically plan a graphic path, improve cutting speed and smoothness, and enhance overall productivity.




Intelligent Pump Monitoring

The intelligent pump monitoring solution provides more comprehensive monitoring than traditional monitoring systems and improves the operational reliability of the vacuum pumps used in semiconductor fabs by measuring vibrations to predict failures and prevent unplanned downtime.



Shaping the Future of Smart Manufacturing



High-Speed Automated LED Chip Sorting


Chip sizes have become increasingly smaller while the number of units that need to be tested has conversely grown exponentially. The solution significantly increases efficiency for quality inspections of chips, allowing end users to easily achieve rapid feedback response, striking an optimal balance between speed and accuracy.

Solution Features

- High speed video capture, simultaneous multiaxial control integration
- Fast and accurate positioning, rapid feedback response
- Exceptional compatibility and usability of machine components with unified PC-based interface

Customer Benefits

- Quickly classifies the die level that matches the required specifications
- Enhances the speed of motion control systems to keep up with production efficiency
- Overcomes the complexity of integration through multi-axis synchronous control




Guideway End Seal Defect Inspection

End seals are an important component of guideways. Due to the large quantity and small size of end seals, defect detection is not suitable for people. If using a rule-based AOI, it is difficult to define all the rules needed to detect the various defects that may arise, such as surface scratches, damage, and deformation. The ADLINK anomaly detection solution uses a single algorithm to cover all defect types. With this solution, image acquisition, AI model training, and an AI application are all achieved by one smart camera.

Solution Features

- All-in-one design can be directly applied to various fields
- Only a small amount of normal product data is needed to train the model for testing
- No programming skill or AI expertise required
- Handshake with other devices via DI/O



Customer Benefits

- Only normal product data is needed. Ideal for industries where defect data is not easy to collect
- One algorithm used to detect all defects, compared to rule based AOI
- Users can complete all preliminary procedures, from image capture and verification to set up and deploy the application in one week



2D Codes and Pick-place Solution


This solution supports 2D barcode readers without requiring a professional visual preprocessing background and can be used immediately after installation. It can efficiently decode QR-codes and Data Matrix codes without programming skill. Not only is decoding supported, this solution can also provide the 4-point coordinates and rotation angle of a 2D barcode. The 2D-code angle information can be used to confirm the orientation of the scanned component, and if misaligned, information can be sent to the next process to avoid improper assembly. 2D barcode coordinates can be used to inform PLC and robots of component orientation and how to grasp them.

Solution Features

- Provides pick and place systems with angle and position information
- Improves high decode-rate for QR & Data Matrix code (with AI JNX system)
- Increases 150% FOV over competitors
- Ready to use, no programming needed

Customer Benefits

- NEON 2D barcode reader reduces significant cost without a Vision license/tool
- 150% FOV lowers costs
- Compatibility with the C-mount lenses for post-assembly applications (8mm-35mm)




Accelerated Automatic Material Testing

An automatic material system usually consists of signal conditioning, transducer excitation, transducer measurement, LVDT measurement, and actuator control to a stepper motor or hydraulic system. The PCIe-91 series speeds up system integration for material testing developers by combining accurate load change measurement, displacement, and motor control.

Solution Features

- Onboard amplifier, four load cell inputs, 2.5/10 VDC, 1.0 to 4.0 mV/V, accurate up to 200,000 counts
- 4-channel general-purpose 24-bit analog inputs for high accuracy LVDT measurements
- Three pulse generator channels: one 3-axes AB phase encoder for step motor control, two 16-bit analog outputs for hydraulic systems control



Customer Benefits

- Quicker integration
- Higher accuracy with high-resolution measurements
- Supports various commonly used inputs and outputs

Featured Solutions

Improving Efficiency, Precision, Quality of Machine Automation

Machine automation is at the core of smart manufacturing, integrating motion, machine vision, and IO sensing to maximize efficiency, optimize visual inspection, and improve quality. As information technology (IT) and operations technology (OT) merge, ADLINK's software-defined edge controller brings highly connected efficiency and productivity to make the transformation possible.



Solution Highlights

Software-Defined EtherCAT Controller

New-generation EtherCAT solution integrates PC hardware and real-time software, bringing the flexibility of controller form factor selection and the guarantee of compatibility between motion controllers and subsystems.



Application Level Software

Reduce development time and complexity through application level ready API and driver framework for a wide variety of machine automation applications in motion and vision.



Motion Creator Pro 2



Multiple Camera Interface Standards

Achieve optimum results for a vision system and fulfill a wide range of imaging processing bandwidth and camera interface standards with extensive frame grabber selection.



One-Stop Integrated Solution

Simplify your system deployment with a highly integrated product portfolio including motion controllers, frame grabbers and IO sensing to meet and exceed customer requirements, supporting the setup of smart factories.



Featured Products

SuperCAT



Software defined EtherCAT motion controller

PCIe-833X series



16/32/64-axis PCIe EtherCAT Master Motion Controller

ECAT IO



EtherCAT IO Slave Module

SMR250/1000 series



Swarm-native AMR powered by SWARM CORE® for optimized intralogistics efficiency

PanKonix Series-HMI Panel PC & IIoT Gateway



Control/Gateway/Display All-in-One Industrial Panel PC and Control/Gateway Protocol Conversion

PCIe-10GPoE



2-ch PCI Express® 10 GigE Vision PoE+ Grabber

PCIe-U300 Series



4/8/12-ch PCI Express x4 Gen2 USB3 Vision Top Performing Frame Grabbers



Extreme Real-time Control

SuperCAT, the software-defined EtherCAT to realize fast response machine automation

ADLINK SuperCAT is a software defined EtherCAT motion controller able to support up to 128 synchronized axes and over 10,000 points simultaneously. To enable high-quality and high efficient production, SuperCAT supports up to 125µs control cycle to optimize synchronous I/O performance, especially in semiconductor and electronics manufacturing industries. With the supported APS function library, SuperCAT is able to generate multi-dimensional, highly synchronized, and event-triggered motion and I/O control of a wide range of third-party EtherCAT slaves.



Multi-axis Synchronization

Supports up to 128 axes synchronously to execute more motion functionalities



High Response Control

Shortens response time up to 125µs for high-speed applications



Space-saving and Flexible Configuration

No control card needed. Release more space for other functions and lower overall cost by 30%

Platform Selections: CAT-PAC Series



Intel Atom® Processor E3900 Family-Based Ultra Compact Embedded Platform with optimum I/O design for maximum connectivity.



9th Gen Intel® Core™ i7/i5/i3 & 8th Gen Celeron® processor-based expandable computer with flexible modular expansion



9th Gen Intel® Core™ i7/i5/i3 & 8th Gen Celeron® processor-based embedded fanless compact computer optimized for edge computing applications



Learn More ↑

A wide Selection of IO Sensing

ADLINK digital I/O cards are widely used in many industrial-grade applications, such as monitoring the status of devices in factories, environmental monitoring, process monitoring, industrial on/off control, and switch status sensing. In order to meet the maximum application flexibility of connecting devices, we provide TTL I/O, isolated I/O and power adapter output to support high-speed, high-current, high-density, isolation and circuit protection requirements, supporting up to 256 channels of data input and output.



Featured Products



PCIe-7853

Master-slave distributed motion and I/O master controller

- Connected I/O points: up to 2,016 points
- RJ45 jack for easy installation
- Software selectable transmission speed: 3/6/12 Mbps for HSL
- Non-volatile RAM onboard



HSL-DI16DO16-M-NN

16-ch discrete input 16-ch discrete output module

- Input voltage: ±40 V (Max)
- Output switching capacity: Single channel 500 mA; all channels 60 mA at 24VDC
- Photo couple isolation voltage: 2500 Vrms
- Input impedance: 4.7 KΩ



HSL-TB32-M-DIN

32-ch I/O terminal base

- Field I/O wiring connection for HSL I/O modules
- Spring terminal for easy field wiring
- Power and ground included for each signal channel
- Interlocking design for rugged installation
- Power LED indicator



PCIe-6208

8-CH 16-Bit PCI Express analog output card

- 4-CH TTL digital inputs and 4-CH TTL digital outputs
- Bipolar analog output range
- 8-CH voltage outputs
- 16-bit D/A resolution



PCIe-7396

96-CH high-driving DIO card

- Supports a 32-bit 5V PCI Express bus
- 96-CH digital TTL inputs/outputs
- High driving up to 48 mA (sink) and 15 mA (source)
- Emulates 4/2 industry standard 8255 PPI (mode 0)
- Ports are independently configurable as input or output



MNET-4XMO-(C)

Distributed 4-axis motion control module (with high-speed trigger function)

- Up to 256 axes on a single Motionnet network
- Transmission speed selectable: 2.5/5/10/20 Mbps
- Maximum wiring distance: up to 100 meters
- 4-axis pulse train output channels; frequency up to 9.9 MHz
- Encoder frequency up to 20 MHz under 4xAB feedback mode



PCIe-7856

Master-slave distributed motion and I/O master controller

- Up to 256 axes on a single Motionnet network
- Connected I/O points: up to 2,016 points
- Programmable timer interrupt
- Transmission speed: 3/6/12 Mbps for HSL ; 2.5/5/10/20 Mbps for Motionnet



NuDAM-6100 Series Modules supporting Modbus RTU protocol

- The NuDAM modules provide direct communications with a wide variety of sensors; perform signal conditioning, scaling, linearization and conversion; can acquire measurements of temperature, pressure, flow, voltage, current; and handle multiple digital signal types broadly used in IoT and other industrial applications, such as facility monitoring, environment monitoring, and industrial process control. The new ND-6117, ND-6124, ND-6150, and ND-6160 modules feature Modbus/RTU as the best remote data transmission protocol, which provides customers a comprehensive product offering.

Revolutionize Your Automation Control Process

Control/Gateway/Display All-in-One HMI Solution



The ADLINK PanKonix® Series HMI Panel PC is the all-in-one solution for industrial control, gateway, and display functions. Powered by the SuperCAT® software-defined motion controller, the PanKonix® Series offers cost-effective and easy integration, along with a customizable user interface that includes network-enablement, cloud connectivity, push notification, and simplified multi-IP management. Experience the future of industrial control with the ADLINK PanKonix® Series HMI Panel PC.

Full Control

Seamless motion control with application-ready functions



Easy Gateway

Real-time automatic data transcription and cloud connection



Clear Display

Intuitive customizable UI with smart operational functions



AUO Display+

From Automation to Swarm Autonomy

Optimizing production efficiency with autonomous mobile robots

In the age of the Internet of Things, it is critical for smart factories to have seamless device integration and communication. With factories having multiple automated systems, the challenge is how to effectively achieve greater efficiency through equipment autonomy; this is the goal of Swarm Autonomy. With AMR autonomous robots and a 5G private network, ADLINK is helping manufacturing industries upgrade their systems from automated to autonomous.



Easy Integration

Easy heterogeneous integration between cross-brand vehicles, devices and IT & OT systems



High Flexibility

Innovative fleet management system for dynamic environments



High OEE

Optimized intralogistics efficiency with effective communication, configuration and deployment

Swarm Ready Offerings



SMR Series

Compact, sturdy, and intelligent AMR for optimized intralogistics efficiency

- 1.5/1.0 m/s max speed with full load
- 8 hour full load operating time with 70-90 minute charging
- Optimized space utilization including navigation in 80/103 cm aisle width
- Top-Module Compatible

SWARM CORE®

Autonomy software for easy configuration, operation, and monitoring

- All-in-one robot, equipment controller
- Event-based dynamic rescheduling system

PanKonix Series - HMI Panel PC

Control/Gateway/Display All-in-One Industrial Panel PC

- Screen size: 10.1", 15.6", or 21.5"
- Frame type: Stand or Open Frame
- Processor: Intel® Core™ i3-7100U or higher
- Memory: 4GB or 8GB
- Resolution: 1280x800 or 1920x1080



Learn More ↑

PanKonix Series - IIoT Gateway

Control/Gateway Protocol Conversion

- Supports a variety of PLC protocols including OMRON, Mitsubishi, and Siemens
- Cloud service connectivity through OPCUA, MQTT, and RESTful API
- TI Sitara AM3352 ARM Cortex-A8 1GHz CPU
- 2x Ethernet Ports, 2x COM Ports
- Isolated Communication Port




Learn More ↑

Featured Solutions

Enabling AI Vision at the Edge

AI edge computing enhances production tasks like quality inspection, surface irregularity detection, and cargo label recognition by using machine learning and image processing to perform real-time adjustments, leading to improved stability, reduced latency and increased efficiency in operations, resulting in increased accuracy and reduced development time.



Solution Highlights

Optimized for Vision Applications

Tightly integrated hardware and software, already verified for compatibility, providing AI developers a convenient launchpad for their projects.



Worry-Free Reliability

CE/FCC/Safety verified to reduce EMC/ESD issues. Shock, vibration and temperature cycle validated for stability.



High AI Inference Compatibility

Supports leading AI inference engines such as ONNX and TensorRT for seamless connection between AI model training to inference.



No-code and Low-code AI PoC Development

Intuitive GUI for fast and easy AI inference pipeline development, 2 weeks to PoC



Featured Products

NEON-2000-JNX/JNO



NEON-2000-JT2-X



EOS-JNX-I



EOS-JNX-G



EVA Software



AI Camera Dev Kit





Edge AI Vision Platform

ADLINK AI Vision Solutions are ideal for visual inspection, object detection, automatic number plate recognition, and behavior monitoring, with all the intensive processing done on the device. Labor-intensive industries such as food sorting, logistics, packaging, and farming can all benefit. The various AI Vision Solutions perform product sorting and classification tasks, and quality assurance.


Ready to Go Edge AI Vision with All-in-One Camera

- Integrated MIPI camera module & drivers save integration effort, reducing cost
- CE/FCC/Safety verified to reduce EMC/ESD issues. Shock, vibration and temperature cycle validated for stability.
- With FPGA-based DI/O design, the NEON series AI Smart Camera provides accurate hardware triggering, and the USB Type-C hub reduces cable connections, making it ideally suited for machine vision applications in automated manufacturing.



Affordable, Fast, and Infinitely Expandable AI Prototyping

To address the AI Vision market and help developers with rapid testing and prototyping, ADLINK has created the AI Camera Development Kit, designed to provide engineers a prototyping platform to streamline industrial AI vision application development.



Ultra Reliable AI Vision System Designed for edge AI Applications

Born for AI Surveillance

EOS-JNX-I



Dedicated bandwidth of 1Gb per channel with 100m cable validation for high accuracy, high speed AI Vision applications



Active DO provides real-time alerts via trigger connected visual or audio warning device



EOS-JNX-G



100% ONVIF compliance and 1Gb uplink port for high NVR/Camera connectivity and reduced cabling




Special power design makes the video stream and PoE work continuously even if the EOS-JNX-I crashes or reboots.

Low-code/no-code EVA SDK Simplifies Edge AI Vision PoC

ADLINK AI vision platform supports EVA, ADLINK's edge vision analytics software, which serves as a unified platform for streamlining AI vision project deployment in a heterogeneous computing environment.

- Supports 10+ camera protocols and field-ready application plugins
- Supports TensorRT and OpenVINO AI inference engines
- No-code/low-code IDE AI development environment lowers thresholds
- Four weeks from PoC to mass deployment



Driving Innovation and Productivity with ADLINK's Data Acquisition Solution

PC-based test and measurement systems have been widely used in industrial equipment manufacturing, such as data acquisition, automated testing, and machine learning predictive maintenance. ADLINK continues to develop a variety of hardware and software technologies to improve the accuracy and efficiency of measurement capabilities.

Featured Solutions



Semiconductor



Electronic Manufacturing




Education and Research

Solution Highlights

Various Form Factors

Complete hardware selection from modular chassis and controllers with PXI, PXIe platform to DAQ devices in different form factors including PCIe cards, USB modules and DAQ computers.



Precise Acquisition

With Direct sensor connection and setting, ADLINK's DAQ modules enable flexible sampling with flexible digital and analog trigger functions.





Unified Software Support

ADLINK eliminates bottlenecks with the new Measurement, Automation, and Platform Suite (MAPS), an all-in-one software solution that can be used with ADLINK's DAQ and PXI modules.



Worry-Free Reliability

CE/FCC/Safety verified to reduce EMC/ESD issues. Shock, vibration and temperature cycle are validated for stability.



Featured Products

PCIe-91 series



16 Channels, Multiplexer, High Performance, Multifunction Data Acquisition Card

SDAQ-200 series



Programmable Smart DAQ with Voltage, Current Sound&Vibration Input

EMU-200



ARM-based Energy Management Gateway

PXES-2788



18/21-slot Gen3 PXIe Chassis with High Cooling Capacity & Power Supply

PXIe-39x7-ADP series




12th Gen Intel® Core™ i7/i5/i3 Processor-based PXIe Controller



Smart DAQ Programmable at the edge

New Gen Python Enabled DAQ with Easier Manageability

Due to the continuous expansion of factories and the more complex monitoring environment, ADLINK's innovative edge data acquisition system with Python programming can actively monitor, analyze and take action on the real-time status of key machines and components, and accelerate deployment, simplify configuration and management, thereby increasing overall productivity.



Programmable Arm CPU

Powerful integrated ARM processor ideal for edge computing needs



Customized Algorithm Capability

Users can deploy their own data analytics Apps via the DAQPilot software utility for edge analytics and control



Plug and Play

Users can add multiple devices making it easy to achieve mass deployment



PXI Express Platform Solving Complex Testing Challenges

The Best Balance of Functionality, Performance and Cost

As a leading provider in Test & Measurement market, ADLINK has devoted extensive field experience to the PXI platform. After decades years developing versatile PXI product portfolio for automation and testing, and as a sponsor member of the PXI System Alliance, ADLINK continues to expand PXI and PXI Express offerings with innovative products, meeting the unique needs of high-speed and high-bandwidth applications.



Interoperability

Compatible with standard modular instruments of the T&M industry.



High Performance

Based on the latest technology, incorporating powerful multicore processors, FPGAs, and more to speed up time to market




Scalable

PXI's architecture enables synchronized measurements across multiple modules or chassis, so you can add to your systems as requirements change

Abundant Bandwidth
PCI Express Bus

Electrical Signal Noise
Isolation/Reduction

Smart Fan Optimizes Balance of Cooling and Acoustic (noise reduction) performance



SDAQ-200 series



SDAQ-204

Vibration Input Module

4-CH Simultaneous AI, ± 10 V, 24-Bit, 128 KS/s, Support ICP type sensor

SDAQ-216

Voltage Input Module

16-CH Multifunction AI, ± 10 V, 16-Bit, 250 KS/s, 2 AO, 4 DIO


SDAQ-218

Current Input Module

8-CH Multifunction AI, 0-20mA, 16-Bit, 250KS/s, 2 AO, 4 DIO

DAQPilot

- Task-oriented and optimized SDK for typical DAQ applications with C/C++/C#/Python/LabVIEW
- Enables streaming of continuous time-series data via SDK
- Integrated management utility for device/iApp management
- Includes IDE to remotely develop iApps for edge data analytics
- Easy iApp mass deployment to remote devices with just one click



PXI Express Chassis

PXES-2788 / PXES-2788E

18-Slot / 21-Slot 3U 24GB/s High Power and Cooling PXI Express Chassis

PXES-2785

18-Slot 3U 24GB/s PXI Express Chassis

PXI Express Embedded Controller

PXle-39x7-ADP

12th Gen Intel® Core™ i7/i5/i3 Processor-based PXle Controller

PXI Express Remote Controller

PCIe-PXle-8638

PCIe to PXle Remote Controller, 4GB/s

PCIe-PXle-8565

PCIe to PXle Remote Controller, 250M/B