




Product Catalog

Thermoelectric Coolers





About Tark Thermal Solutions

Tark Thermal Solutions develops thermal management solutions for demanding applications across global medical, industrial, transportation and telecommunications markets. We manufacture one of the most diverse product portfolios in the industry ranging from active thermoelectric coolers and assemblies to temperature controllers and liquid cooling systems. Our engineers use advanced thermal modeling and management techniques to solve complex heat and temperature control problems. By offering a broad range of design, prototyping and in-house testing capabilities, we partner closely with our customers across the entire product development lifecycle to reduce risk and accelerate their time-to-market. Our global manufacturing and support resources help customers maximize productivity, uptime, performance and product quality. Tark Thermal Solutions is the optimum choice for standard or custom thermal solutions.

Tark Thermal Solutions partners with its customers to design custom thermal solutions for applications in many industries including:

- Medical Diagnostics
- Medical Imaging
- Battery Cooling
- Industrial Laser Systems
- Optoelectronics
- Analytical Instrumentation
- Semiconductor Fabrication
- Aerospace Defense
- Food & Beverage
- Automotive




Introduction to Thermoelectrics

Solid state heat pumps have been in existence since the discovery of the Peltier effect in 1834. The devices became commercially available several decades ago with the development of advanced semiconductor thermocouple materials in combination with ceramics substrates. Thermoelectric coolers are solid-state heat pumps that require a heat exchanger to dissipate heat utilizing the Peltier Effect. During operation, DC current flows through the thermoelectric cooler to create heat transfer and a temperature differential across the ceramic substrates, causing one side of the thermoelectric cooler to be cold, while the other side is hot. A standard single-stage thermoelectric cooler can achieve temperature differentials of up to 70°C.

A typical thermoelectric cooler's geometric footprint can vary from 2 x 2 mm's to 62 x 62 mm's and are light in weight. This makes thermoelectrics ideal for applications with tight geometric space constraints and low weight requirements when compared too much larger cooling technologies, such as conventional compressor-based systems. Thermoelectric coolers can also be used as a power generator to convert waste heat into usable output DC power.

Thermoelectrics are ideal for applications that require active cooling to below ambient and have cooling capacity requirements < 600 Watts. A design engineer should consider thermoelectric coolers when the system design criteria includes such factors as precise temperature control, high reliability, compact geometry constraints, low weight and environmental friendly requirements.



Benefits of Using Thermoelectrics

Thermoelectric coolers have several advantages over alternate cooling technologies:

- They have no moving parts, so the solid state construction results in high reliability and units can be mounted in any orientation.
- Thermoelectric coolers can cool devices down to well below ambient. Colder temperatures can be achieved, down to minus 100°C, by using a multistage thermoelectric cooler in a vacuum environment.
- Thermoelectrics are able to heat and cool by simply reversing the polarity, which changes the direction of heat transfer. This allows temperature control to be very precise, where up to ±0.01°C can be maintained under steady-state conditions.
- In heating mode, thermoelectric coolers are much more efficient than conventional resistant heaters because they generate heat from input power supplied plus additional heat generated by the heat pumping action.
- Devices are environmentally friendly because they use no CFC's and electrical noise is minimal.
- Thermoelectric coolers can be used as energy harvesters, turning waste heat into usable output DC power.

Product Portfolio

Tark Thermal Solutions designs and manufactures thermoelectric coolers which adhere to strict process control standards and pass/fail criteria, assuring our customers receive the best possible modules. Our extensive standard product portfolio covers a wide range of cooling capacities, temperature differentials, input power requirements and geometric footprints. Standard finishing options are available to accommodate alternate lead lengths, lapping thickness tolerances, and moisture protective sealants. Standard pre-tinning and solder constructions are available to accommodate solder-able mounting of the thermoelectric cooler to the heat exchanger, or processing of thermoelectric cooler through a reflow oven to solder onto an optoelectronic package.

Tark Thermal Solutions offers several thermoelectric cooler product families that can be classified by cooling capacity, temperature differential, form factor or thermal cycling capability. Reference perceptual map below as a general guide as to where each product family fits with regards to these attributes.

Thermoelectric Applications

Thermoelectric cooler assemblies are used in a wide range of applications to stabilize the temperature of sensitive electronic components or to cool devices and compartments below ambient.

Analytical

Temperature control is vital in analytical instrumentation equipment to enhance reliability and improve test results.

- Sample Storage Compartments
- Liquid Chromatography
- Incubators
- Molecular Diagnostics (PCR)

Medical

Temperature stabilization is required to obtain a high image resolution. Cooling reagent chambers below ambient is critical to extend life of reagents and keep replacement costs down. Rapid thermal cycling is crucial to speed up DNA amplification.

- Medical Diagnostics
- Medical Lasers
- Centrifuges

Industrial

Temperature stabilization is critical to maintain industrial lasers at peak performance and allows high end printing systems to produce high quality prints at high run rates.

- High Powered Projectors
- Kiosks
- Industrial Laser Systems
- Digital Color Printing Systems

Telecom

Cooling below ambient is necessary to extend life of batteries in wireless base stations. Temperature stabilization is required to maintain peak performance of laser diodes.

- Telecom Enclosures
- Battery Backup Systems
- Metrology Instrumentation
- Optical Transceivers

Transportation

Advancements in transportation technology such as smart headlights, and infotainment systems require thermal management solutions to protect the sensitive electronics and ensure long-life performance.


- Smart Lightning
- Heads-Up Displays
- Imaging Sensors

Rapid Prototyping Center




Since there are so many unique attributes that need to be ascertained for each application, often a customized thermoelectric cooler will yield a more optimal thermal solution. Tark Thermal Solutions offers strong engineering services with a global presence that supports on-site concept generation, thermal modeling, thermal design and rapid prototyping. We also offer validation test services to meet unique compliance standards for each industry, such as Telcordia, MIL-STDs or standards specific to unique application. Minimum order quantity (MOQ) applies for all custom thermoelectric cooler designs and validation testing.

CUSTOM THERMOELECTRIC COOLERS

- Patterning and Plating on Substrates
- Test Validation
- TE semiconductor Processing
- Lapping, Wiring and Sealing
- Tooling Fabrication
- Thermoelectric Cooler Assembly



OptoTEC™ MBX Series



-  TO Can
-  TOSA
-  Butterfly

The MBX Series of thermoelectric coolers is a NEW high performance thermoelectric cooler to support next generation optoelectronic applications. Features include:

- Ultra-Small form factor
- Protects electronics in high temperature environments that operate in excess of 80°C.
- Ideal for temperature stabilization in optoelectronic applications including laser diodes, optical transceivers, LiDAR, CMOS and Infrared Range (IR) sensors.

MBX Series

The MBX Series uses SbSn solder, enabling a maximum operating temperature of 120°C and a melting point of 232°C.

MFG PART NUMBER	DESCRIPTION	QCMAX (WATTS)	IMAX (AMPS)	VMAX (VOLTS)	ΔTMAX (°C)	DIM A (MM)	DIM B (MM)	DIM C (MM)	DIM D (MM)
387013090	MBX16-06-F2N-0101-GG-W0	0.7	1.6	0.77	81.8	1.5	1.1	1.5	0.8
387012171	MBX14-08-F2N-0101-GG-W0	0.8	1.3	1.03	81.8	1.9	1.5	1.5	0.8
387012172	MBX14-09-F1N-0101-GG-W0	0.9	1.3	1.16	81.8	1.8	1.5	1.5	0.7
387012173	MBX11-15-F2N-0202-GG-W0	1.2	1	1.94	81.8	2.4	1.8	2.1	0.8
387013091	MBX11-18-F2N-0202-GG-W0	1.4	1	2.32	81.8	2.7	2.0	2.0	0.9
387012175	MBX18-15-F2N-0202-GG-W0	2	1.8	1.94	81.8	2.6	1.9	2.3	0.9
387012176	MBX15-21-F2N-0302-GG-W0	2.2	1.4	2.71	81.8	3.4	2.8	2.4	0.9
387012181	MBX18-20-F2N-0203-GG-W0	2.7	1.8	2.58	81.8	3.5	3.0	2.6	0.9
387012182	MBX17-24-F2N-0402-GG-W0	2.9	1.6	3.1	81.8	4.2	3.5	2.6	1
387010765	MBX12-38-F2N-0502-GG-W0	3.2	1.1	4.9	81.8	5.1	4.4	2.8	1.1
387012183	MBX19-28-F2N-0303-GG-W0	3.8	1.8	3.61	81.8	3.7	3.1	3.6	0.9
387012184	MBX19-32-F2N-0403-GG-W0	4.3	1.8	4.13	81.8	4.4	3.7	3.7	1
387012185	MBX20-36-F2N-0403-GG-W0	5.2	1.9	4.65	81.8	4.8	4.0	3.6	0.9
387012186	MBX20-40-F2N-0503-GG-W0	5.7	1.9	5.16	81.8	5.5	4.8	3.9	1
387012187	MBX21-45-F2N-0505-GG-W0	6.8	2	5.81	81.8	5.1	5	5	1
387013092	MBX18-67-F2A-0904-GG-W0	9.6	1.9	8.65	81.8	9.2	8.5	4	1.3
387012190	MBX18-72-F2A-0606-GG-W0	9.9	1.8	9.29	81.8	6.8	6.1	6.1	1.4
387010764	MBX20-42-F2A-1206-GG-W0	6.3	2	5.42	81.8	12	10.1	6	2.1
387012191	MBX25-59-F2A-0605-GG-W0	8.9	2	7.62	81.8	6.2	5.7	5.2	1.2
387012192	MBX27-64-F2A-0904-GG-W0	14.2	2.9	8.26	81.8	9.1	8.4	4.3	1.2
387012193	MBX28-71-F1A-0606-GG-W0	16.5	3	9.16	81.8	6.5	6.5	6.5	1.2

1) QMax rated value at ΔT = 0°C, Imax and Vmax, Th = 27°C; 2) QMax rated value at ΔT = 0°C, Imax and Vmax, Th = 50°C; 3) Thickness for non-metallized versions only.

Series (Solder Construction)

MODEL	SOLDER TYPE	MELT TEMP
MBX	(SnSb) Tin Antimony	232°C
HBX	(AuSn) Gold Tin	280°C

Ceramic Materials

CERAMIC MATERIAL	THERMAL CONDUCTIVITY	OPTION
(ALO) Alum Oxide	24 W/mK	F2
(ALN) Alum Nitride	170 W/mK	F2N

Surface Finish Options

SOLDER TYPE	MELT TEMP	OPTION
Au plating (Hot/Cold Surface)		GG
Non-Metallized Hot and/or Cold face		11
Pre-tinning Hot and/or Cold face with 118°C InSn Solder	118°C	22
Pre-tinning Hot and/or Cold face with 138°C BiSn Solder	138°C	33

Lead Attachment

SOLDER TYPE	OPTION
Au plated pads	W0
Au plated Posts	WP

OptoTEC™ MSX Series



The MSX Series utilizes advanced ceramic materials, proprietary automation and next-generation thermoelectric materials to boost cooling capacity by as much as 10% and assure high process repeatability. Feature a higher thermal insulating barrier than standard thermoelectric coolers.

Ideal for imaging sensing applications including:

- Infrared (IR) Detectors
- Charge-Coupled Devices (CCD)
- Complementary Metal Oxide Semiconductors (CMOS)
- X-Ray Detectors

Optical TEAs




MSX multistage micro thermoelectric coolers are available as a standalone or integrated into an optical package called Optical TEAs. Tark Thermal Solutions has a proprietary bonding technique to adhere TECs to optical packages with minimal solder voiding. Solder types used are below melt temperatures of TEC solder construction and optical packaging is specified by the customer.



Surface Finish Options

SOLDER TYPE	MELT TEMP
SnInAg	206°C
BiSn	138°C
InSn	117°C

OptoTEC™ OTX/HTX Series



- High-performance thermoelectric cooler with advanced thermoelectric materials
- Miniature Form Factor
- Protects electronics in high temperature environments that operate in excess of 80°C.
- Ideal for temperature stabilization in optoelectronic applications including laser diodes, optical transceivers, LiDAR, CMOS and Infrared Range (IR) sensors.



OTX Series

The OTX Series uses SbSn solder, enabling a maximum operating temperature of 120°C and a melting point of 232°C.


MFG PART NUMBER	DESCRIPTION	QMAX (WATTS)	IMAX (AMPS)	VMAX (VOLTS)	ΔTMAX (°C)	DIM A (MM)	DIM B (MM)	DIM C (MM)	DIM D (MM)
387006791	OTX08-08-F0-0303-11-W2.25	0.4	0.8	0.9	72.9	4.9	3.3	-	2.6
387006650	OTX08-18-F0-0505-11-W2.25	1	0.8	2.1	72.9	6.5	4.9	-	2.7
387006795	OTX08-31-F1-0707-11-RT-W2.25	1.7	0.8	3.6	72.9	6.5	6.5	-	2.4
387006897	OTX19-23-F1N-0608-11-W2.25	3.1	1.9	2.7	72.9	6	8.2	-	1.7
387006839	OTX15-30-F2A-0610-11-W2.25	3.1	1.5	3.5	72.9	12.3	10.3	12.3	2
387006845	OTX15-31-F2A-0909-20-W2.25	3.3	1.5	3.6	72.9	8.8	8.8	11	2.8
387006798	OTX08-66-F0-1009-11-RT-W2.25	3.7	0.8	7.7	72.9	11.4	8.9	-	2.4
387006798	OTX08-66-F0-1009-11-RT-W2.25	3.7	0.8	7.7	72.9	11.4	8.9	-	2.4
387007103	OTX24-31-F1-1010-11-W2.25	5.4	2.5	3.6	72.9	10	10	-	2.5
387006832	OTX12-65-F2A-1312-11-W2.25	5.5	1.2	7.6	72.9	13.2	12.1	13.2	2.7
387006834	OTX12-65-F2A-1312-TB-W2.25	5.5	1.2	7.6	72.9	13.2	12.1	13.2	2.7
387006837	OTX12-66-F0-1211-11-W2.25	5.5	1.2	7.7	72.9	14.2	11.2	-	2.7
387006836	OTX12-66-F0-1211-TB-RT-W2.25	5.5	1.2	7.7	72.9	14.2	11.2	-	2.7
387006847	OTX15-65-F2A-1312-11-W2.25	6.8	1.5	7.6	72.9	13.2	12.1	13.2	2.4
387006891	OTX15-66-F0-1211-11-W2.25	6.9	1.5	7.7	72.9	14.2	11.2	-	2.4
387006893	OTX15-68-F1A-1313-11-W2.25	7.1	1.5	7.9	72.9	13.2	13.2	-	2.4
387006926	OTX20-65-F2A-1312-11-W2.25	9.1	2	7.6	72.9	13.2	12.1	13.2	2.2
387006927	OTX20-66-F0-1211-11-W2.25	9.2	2	7.7	72.9	14.2	11.2	-	2.2
387006928	OTX20-66-F0-1211-11-EP-W2.25	9.2	2	7.7	72.9	14.2	11.2	-	2.2
387006784	OTX20-68-F1A-1313-11-W2.25	9.5 W	2	7.9	72.9	13.2	13.2	-	2.2

HTX Series



The HTX Series uses AuSn solder, enabling a maximum operating temperature of 150°C and a melting point of 280°C.

MFG PART NUMBER	DESCRIPTION	QMAX (WATTS)	IMAX (AMPS)	VMAX (VOLTS)	ΔTMAX (°C)	DIM A (MM)	DIM B (MM)	DIM C (MM)	DIM D (MM)
387007106	HTX12-18-F2A-0606-11-RT-W2.25	1.6	1.2	2.3	81.6	6.1	6.2	7.2	2.7
387006534	HTX12-18-F2A-0606-GG-W2.25	1.6	1.2	2.3	81.6	6.1	6.2	7.2	3
387007113	HTX15-30-F2A-0610-11-W2.25	3.4	1.5	3.9	81.6	6.2	10.3	12.3	2
387007115	HTX15-31-F2A-0909-TB-W2.25	3.5	1.5	4	81.6	8.8	8.8	11	2.4
387007120	HTX20-31-F2A-0909-11-W2.25	4.6	2	4	81.6	8.8	8.8	11	2.2
387007108	HTX12-65-F2A-1312-11-W2.25	5.8	1.2	8.4	81.6	13.2	12.1	13.2	2.7
387007112	HTX12-65-F2A-1312-TB-RT-W2.25	5.8	1.2	8.4	81.6	13.2	12.1	13.2	2.7
387007117	HTX15-65-F2A-1312-TB-W2.25	7.3	1.5	8.4	81.6	13.2	12.1	13.2	2.4
387007122	HTX20-65-F2A-1312-11-W2.25	9.7	2	8.4	81.6	13.2	12.1	13.2	2.2
387007123	HTX20-65-F2A-1312-TB-W2.25	9.7	2	8.4	81.6	13.2	12.1	13.2	2.2

UltraTEC™ UTX Series






- High-Performance thermoelectric cooler with advanced thermoelectric materials.
- Feature a higher thermal insulating barrier than standard thermoelectric coolers.
- Ideal for demanding spot cooling in industrial lasers and laser projector applications.



MFG PART NUMBER	DESCRIPTION	QMAX (WATTS)	IMAX (AMPS)	VMAX (VOLTS)	ΔTMAX (°C)	DIM A (MM)	DIM B (MM)	DIM C (MM)	DIM D (MM)
387004721	UTX6-19-F1-4040-TA-W6	82.6	6.1	22.8	71.7	40	40	40	3.9
387004702	UTX6-24-F1-5555-TA-W6	100	6.1	27.6	71.7	55	55	55	3.9
387004705	UTX8-12-F2-2525-TA-W6	68.5	7.9	14.6	71.7	25	25	25	1.9
387004697	UTX8-12-F2-3030-TA-W6	68.5	7.9	14.6	71.7	30	30	34	2.6
387004726	UTX8-24-F1-5555-TA-W6	140.2	8.6	27.6	71.7	55	55	55	3.8
387004679	UTX8-200-F2-4040-TA-W6	116.4	8.6	22.9	71.7	40	40	44	3.8
387004724	UTX8-288-F2-5252-TA-W6	167.6	8.6	33	71.7	52	52	56	3.8
387004723	UTX9-28-F2-4040-TA-W6	196.0	10.0	33	71.7	40	40	44	2.8
387004680	UTX11-12-F2-3030-TA-W6	95.2	11	14.6	71.7	30	30	34	2.4
387004685	UTX15-12-F2-4040-TA-W6	125.7	14.6	14.6	71.7	40	40	44	2.8
387004719	UTX15-24-F2-5252-TA-W6	251.2	15.3	27.8	71.7	52	52	56	3.3
387004711	UTX15-200-F2-4040-TA-W6	207.6	15.3	22.9	71.7	40	40	44	3.3
387004692	UTX15-288-F2-5252-TA-W6	298.9	15.3	33	71.7	52	52	56	3.3

Notes: 1) QMax rated value at ΔT = 0°C, Imax and Vmax, Th = 27°C 2) QMax rated value at ΔT = 0°C, Imax and Vmax, Th = 50°C 3) Thickness for non-metallized versions only.



PowerCycling PCX Series



- High-performance thermoelectric cooler featuring a unique module construction to provide long life operation in thermal cycling applications.
- Advanced thermoelectric material boost cooling performance over standard product offerings.
- Tested to withstand rigorous cycle testing based on latest PCR industry test protocol.

MFG PART NUMBER	DESCRIPTION	QMAX (WATTS)	IMAX (AMPS)	VMAX (VOLTS)	ΔTMAX (°C)	DIM A (MM)	DIM B (MM)	DIM C (MM)	DIM D (MM)
387005667	PCX2-12-F1-3030-TA-RT-W6	21.5	2.5	14.9	73.6	30	30		4
387005673	PCX4-4-F1-1515-TA-RT-W6	13.5	4.1	5.7	73.6	15	15		2.8
387005674	PCX4-6-F1-2040-TA-RT-W6	16.8	3.9	7.4	73.6	20	40		4.2
387005514	PCX4-7-F1-2020-TA-RT-W6	19.4	4	8.3	73.6	20	20		3.5
387005671	PCX4-12-F1-3030-TA-W6	34.7	4	14.9	73.6	30	30		3.2
387005672	PCX4-139-F1-1850-TA-RT-W6	37.9	4	16.3	73.6	18	50		3.8
387005676	PCX5-16-F1-4040-TA-W6	54	4.9	18.8	73.6	40	40		3.7
387005677	PCX5.6-19-FIN-3030-TA-RT-W6	77.7	5.8	23.3	73.6	30	30		2.4
387005678	PCX6-12-F1-4040-TA-RT-W6	51.8	6	14.9	73.6	40	40		3.8
387005679	PCX6-24-F1-5555-TA-RT-W6	98.3	6	28.2	73.6	55	55		4.2
387005681	PCX6-28-F2-4040-TA-RT-W6	117.4	6	33.7	73.6	40	40	44	3.1
387005685	PCX7-16-F1-4040-TA-W6	77.3	7.1	18.8	73.6	40	40		3.3
387005513	PCX7-156-F2-1672-TA-RT-W6	76.5	7.2	18.3	73.6	16	72	76	3.3
387005683	PCX7-159-F1-1466-TA-RT-W6	78.6	7.3	18.6	73.6	14	66		3.1
387005686	PCX7.5-13-F1-4023-TA-RT-W6	68.4	7.7	15.3	73.6	40	23		2.8
387005515	PCX8-6-F1-2040-TA-RT-W6	37.4	8.8	7.4	73.6	20	40		3.3
387007231	PCX8-6-F1-3518-TA-RT-W6	37.4	8.8	7.4	73.6	35.5	18		3.4
387005700	PCX8-7-F2-3030-TA-RT-W6	42.2	8.8	8.3	73.6	30	30	34	3.3
387005696	PCX8-12-F1-4040-TA-W6	75.5	8.8	14.9	73.6	40	40		3.3
387008431	PCX8-12-F2-2525-TA-RT-W6	68.9	8	14.9	73.6	24.6	24.3	26.9	2
387005698	PCX8-152-F2-1773-TA-RT-W6	88.8	8.6	17.8	73.6	16.8	73.8	76.7	2.6
387005699	PCX8-176-F2-7528-TA-RT-W6	104.6	8.8	20.6	73.6	75	28	32	3.3
387005699	PCX9-3-F2-2525-TB-RT-W6	21.1	10	3.6	73.6	25.4	25.4	28.7	5
387008429	PCX10-223-F1-3172-TA-RT-W6	155.7	10.3	26.1	73.6	31	72		3.6
387005659	PCX11-12-F2-3030-TA-RT-W6	96.6	11.2	14.9	73.6	30	30	34	2.4
387005660	PCX11-191-F1-3553-TA-RT-W6	147.8	11.4	22.4	73.6	35	53		3.4
387005662	PCX12-139-F1-3550-TA-W6	118.6	12.6	16.3	73.6	35	50		3
387005516	PCX12-19-F1-4040-TA-RT-W6	165.7	12.3	23.3	73.6	40	40		2.9
387005663	PCX12-248-F1-5040-TA-RT-W6	206.5	12.3	29	73.6	50	40		2.9
387005665	PCX15.6-19-F1-4040-TA-RT-W6	215.2	16	23.3	73.6	40	40		2.7
387007227	PCX15-7-F1-4040-TA-RT-W6	78.4	16.3	8.3	73.6	40	40		4.7
387005664	PCX15-128-F2-4040-TA-RT-W6	135.3	15.6	15	73.6	40	40	44	3.3
387005669	PCX24-128-F2-5555-TA-RT-W6	207.9	24	15	73.6	55	55	59	4

Multistage MS Series






- Designed for large temperature differential applications.
- Custom designs available to meet unique cooling capacity or temp differential requirements.
- Ideal for CCD cameras, IR Detectors and industrial sensing instrumentation.

MFG PART NUMBER	DESCRIPTION	QMAX (WATTS)	IMAX (AMPS)	VMAX (VOLTS)	ΔTMAX (°C)	DIM A (MM)	DIM B (MM)	DIM C (MM)	DIM D (MM)	DIM E (MM)
9320001-301	MS2-010-06-06-11-11-11-W2	0.3	1.2	0.78	94	3.2	3.2	3.9	3.9	4.2
9320002-301	MS2-024-06-06-11-11-11-W2	0.8	1.2	1.8	91	4.1	4.1	6.1	6.1	4.6
9380001-301	MS2-065-04-04-11-11-11-W4	0.9	0.5	4.6	87	12	4	14	6	4.7
9340001-301	MS2-049-10-10-15-15-11-W8	3.1	2.3	3.5	89	11.5	11.5	15	15	6.6
9350001-301	MS2-049-14-14-15-15-11-W8	6.1	4.5	3.5	89	15	15	20	20	7.2
475089-301	MS2-068-14-14-15-15-11-W8	7.4	3.7	4.4	81	14.7	14.7	24	24	7.9
9340002-301	MS2-107-10-10-12-12-11-W8	8.6	2.9	8	91	22.6	22.6	22.6	22.6	6.25
16503-310	MS2-051-22-25-22-25-11-W8	10.3	6	3.4	82	26	26	30	30	10.9
475010-313	MS2-102-14-14-17-17-11-W8	11.6	4.4	8	94	20	20	30	30	7.5
9340003-301	MS2-190-10-10-12-12-11-W8	15.4	3	14.3	91	30	30	30	30	6.5
9350007-301	MS2-192-14-20-15-25-11-W8	24.3	5.1	14.7	91	40	40	40	40	8.1
16506-302	MS2-102-22-22-17-17-11-W8	27.9	10.6	8	94	30	30	44	44	9.1
9350006-301	MS2-192-14-20-11-18-11-W8	38	6.9	14.8	90	40	40	40	40	8.1
16068-302	MS3-052-10-17-11-W8	1.4	1.9	3.3	108	7.2	7.2	15	15	9.8
9360001-301	MS3-070-20-25-11-W8	3	6.1	5.5	122	14	8	36	36	16
9340004-301	MS3-231-10-15-11-W8	6.7	2	14.3	106	15	15	30	30	9.5
9350004-301	MS3-119-14-15-11-W8	6.7	4	7.5	107	15	15	30	30	10.4
9360002-301	MS3-119-20-15-11-W8	14	8.1	7.6	106	22	22	44	44	12.9
475024-303	MS4-108-10-20-11-W8	1.1	1.4	6.3	120	7.1	7.1	18	24	14.6
9340005-301	MS4-129-10-15-11-W8	1.8	1.8	7.3	120	8	8	23	23	12.5
9350005-301	MS4-115-14-15-11-W8	2.8	3.9	7.1	124	14.5	4.5	33	24	13.8
9340006-301	MS5-257-10-15-11-W8	2	1.7	13.5	129	8	8	30	30	15.4

Notes: 1) QMax rated value at ΔT = 0°C, Imax and Vmax, Th = 27°C 2) Thickness for non-metallized versions only.




HiTemp ETX Series



- High-Performance thermoelectric cooler with advanced thermoelectric materials and an enhanced module construction.
- Features a higher thermal insulating barrier than standard thermoelectric coolers.
- Protects electronics in high temperature environments that operate in excess of 80°C.
- Ideal for cooling in autonomous systems, machine vision and digital light processors.

MFG PART NUMBER	DESCRIPTION	QMAX (WATTS)	IMAX (AMPS)	VMAX (VOLTS)	ΔTMAX (°C)	DIM A (MM)	DIM B (MM)	DIM C (MM)	DIM D (MM)
387004952	ETX1.6-12-F2-3030-TA-RT-W6	15.7	1.6	16.6	83.2	30	30	34	4
387004961	ETX2.6-F1-1225-TA-RT-W6	10.2	2.1	8.2	83.2	12.5	25		3.2
387005318	ETX2-12-F1-2525-TA-W6	20.6	2.1	16.6	83.2	25	25		3.4
387004970	ETX2-12-F2-3030-TA-W6	22.6	2.3	16.6	83.2	30	30	34	3.4
387004960	ETX2.3-4-F1-1919-TA-RT-W6	8.7	2.3	6.4	83.2	19.4	19.4		3.58
387004964	ETX2.5-12-F1-3030-TA-RT-W6	24.1	2.5	16.6	83.2	30	30		4
387004969	ETX2.5-12-F1-4040-TA-RT-W6	24.1	2.5	16.6	83.2	40	40		4.2
387004959	ETX2.6-6-F1-1225-TA-W6	12.7	2.6	8.2	83.2	12.5	25		3.1
387005354	ETX2.6-12-F1-2525-TA-W6	25.5	2.6	16.6	83.2	25	25		3.1
387004923	ETX3-3-F2-1518-TA-W6	7.7	3.2	4.1	83.2	15	15	18	3.6
387004933	ETX3-48-F1-1212-GG-W6	11.3	3.1	6.3	83.2	12	12		2.38
387004968	ETX3-12-F2-3030-TA-RT-W6	31.4	3.2	16.6	83.2	30	30	34	3.58
387004942	ETX4-3-F1-1515-TA-RT-W6	9.5	4.0	4.1	83.2	15	15		3.2
387004946	ETX4-3-F1-2020-TA-RT-W6	9.2	3.9	4.1	83.2	20	20		4.7
387004956	ETX4-6-F2-2143-TA-RT-W6	18.5	3.8	8.2	83.2	20.6	38.4	43.2	3.81
387004962	ETX4-7-F1-2323-TA-W6	21.7	4.0	9.3	83.2	23	23		3.2
387004929	ETX4-7-F2-3030-TA-RT-W6	20.9	3.8	9.3	83.2	30	30	34	4.14
387004911	ETX4-12-F1-3030-TA-W6	38.8	4.0	16.6	83.2	30	30		3.2
387004915	ETX4-12-F1-4040-TA-RT-W6	37.8	3.9	16.6	83.2	40	40		4.8
387004924	ETX4-12-F1-3030-10-W6	38.8	4.0	16.6	83.2	30	30		3.2
387004936	ETX4-12-F2-3030-TA-RT-W6	38.8	4.0	16.6	83.2	30	30	34	3.2
387004938	ETX4-12-F2-4040-TA-RT-W6	37.3	3.8	16.6	83.2	40	40	44	4.14
387004949	ETX5-6-F1-2040-TA-RT-W6	25.1	5.2	8.2	83.2	20	40		3.6
387004943	ETX6-3-F1-2020-TA-RT-W6	14.5	6.1	4.1	83.2	20	20		3.2
387004966	ETX6-7-F2-3030-TA-RT-W6	33.2	6.1	9.3	83.2	30	30	34	3.81
387004917	ETX6-12-F1-4040-TA-RT-W6	59.4	6.1	16.6	83.2	40	40		3.81
387004947	ETX6-12-F1-3030-TA-W6	59.4	6.1	16.6	83.2	30	30		3.2
387004937	ETX6-19-F1-4040-TA-RT-W6	91.6	6.0	26.0	83.2	40	40		3.91
387004957	ETX7-3-F1-2020-TA-RT-W6	18.5	7.7	4.1	83.2	20	20		3.51
387004951	ETX7-16-F1-4040-TA-RT-W6	84.1	6.8	21.0	83.2	40	40		3.2
387004950	ETX8-7-F1-3030-TA-RT-W6	47.0	8.6	9.3	83.2	30	30		3.33
387004955	ETX8-7-F2-3030-TA-RT-W6	47.0	8.6	9.3	83.2	30	30	34	3.33
387004922	ETX8-12-F1-4040-TA-RT-W6	84	8.6	16.6	83.2	40	40		3.33
387004934	ETX8-12-F2-2525-TA-RT-W6	77.8	7.9	16.6	83.2	24.6	24.3	26.9	1.96
387004932	ETX8-28-F2-5252-TA-RT-W6	190.5	8.6	37.6	83.2	52	52	56	3.81
387004939	ETX9-3-F2-2525-TA-W6	23.6	9.9	4.1	83.2	25.4	25.4	28.7	5
387004963	ETX9-3-F1-3030-TA-RT-W6	22.1	9.2	4.1	83.2	30	30		5.59
387004944	ETX11-12-F1-4040-TA-RT-W6	109	11.0	16.6	83.2	40	40		3.5
387004931	ETX11-12-F2-3030-TA-RT-W6	108.2	11.0	16.6	83.2	30	30	34	2.41
387004958	ETX14-3-F1-3030-TA-RT-W6	33.8	14.1	4.1	83.2	30	30		4.57
387006544	ETX14-12-F1-6262-TA-W6	138	14.1	16.6	83.2	62	62		4.57
387004927	ETX15-12-F2-4040-TA-RT-W6	142.8	14.6	16.6	83.2	40	40	44	2.84
387004919	ETX15-24-F2-5252-TA-W6	269.4	14.5	31.5	83.2	52	52	56	3.3
387004921	ETX15-28-F2-5252-TA-RT-W6	321.9	14.5	37.6	83.2	52	52	56	3.3
387004930	ETX25-12-F1-6262-TA-W6	245.1	25.0	16.6	83.2	62	62		4.1

PolarTEC™ PT Series






- Porch style ceramic for improved lead attachment.
- Standard 4, 6 and 8 Amp configurations available.
- Designed for high volume production runs in consumer, food and beverage markets.

MFG PART NUMBER	DESCRIPTION	QMAX (WATTS)	IMAX (AMPS)	VMAX (VOLTS)	ΔTMAX (°C)	DIM A (MM)	DIM B (MM)	DIM C (MM)	DIM D (MM)
430097-507	PT4-7-F2-3030-TA-W6	17.8	3.8	7.8	70.5	30	30	34	4.1
430027-501	PT6-7-F2-3030-TA-W6	28.3	6.1	7.8	70.5	30	30	34	3.8
430026-503	PT4-12-F2-3030-TA-W6	33	4	13.9	70.5	30	30	34	3.2
430023-507	PT4-12-F2-4040-TA-W6	31.8	3.8	13.9	70.5	40	40	44	4.1
430052-501	PT6-12-F2-4040-TA-W6	50.6	6.1	13.9	70.5	40	40	44	3.8
7050045-502	PT8-12-F2-4040-TA-W6	71	8.6	13.9	70.5	40	40	44	3.3

Notes: 1) QMax rated value at ΔT = 0°C, I_{max} and V_{max}, Th = 50°C 2) QMax rated value at ΔT = 0°C, I_{max} and V_{max}, Th = 27°C 3) Thickness for non-metallized versions only.



CP Series




- Designed for high current, large heat pumping applications.
- Wide product breadth that covers many form factors, input power requirements and heat pumping capacities.
- Ideal for medical diagnostics, analytical instrumentation, photonics laser systems and battery cooling.

MFG PART NUMBER	DESCRIPTION	QMAX (WATTS)	IMAX (AMPS)	VMAX (VOLTS)	ΔTMAX (°C)	DIM A (MM)	DIM B (MM)	DIM C (MM)	DIM D (MM)
62910-510	CP08-127-05-L1-W4.5	21.7	2.6	13.9	70.5	25	25	25	3.1
66195-505	CP08-127-06-L1-W4.5	17.5	2.1	13.9	70.5	25	25	25	3.4
71035-505	CP08-31-06-L1-W4.5	4.3	2.1	3.4	70.5	12	12	12	3.4
71036-505	CP08-63-06-L1-W4.5	8.7	2.1	6.9	70.5	12	25	12	3.4
71212-502	CP085-127-06-L1-W4.5	19.2	2.3	13.9	70.5	30	30	30	3.6
56460-501	CP10-127-05-L1-W4.5	33	4	13.9	70.5	30	30	30	3.2
56310-503	CP10-127-06-L1-W4.5	25.5	3.1	13.9	70.5	30	30	30	3.6
71012-506	CP10-254-06-L1-W4.5	51	3.1	27.7	70.5	60	30	30	3.6
430801-504	CP10-31-05-L1-W4.5	8.1	4.0	3.4	70.5	15	15	15	3.2
63604-511	CP10-31-08-L1-W4.5	5.1	2.5	3.4	70.5	15	15	15	4
56430-501	CP10-63-05-L1-W4.5	16.4	4.0	6.9	70.5	15	30	15	3.2
43280-503	CP10-63-06-L1-W4.5	12.6	3.1	6.9	70.5	15	30		3.58
63595-501	CP10-63-08-L-W4.5	10.4	2.5	6.9	70.5	15	30		3.9
44440-501	CP10-71-05-L1-W4.5	18.5	4.0	7.8	70.5	23	23	23	3.2
430436-504	CP10-71-06-L1-W4.5	14.2	3.1	7.8	70.5	23	23	23	3.6
430922-501	CP10-131-04-L1-TOW-W4.5	52.1	6.1	14.3	70.5	40	23		3
430848-502	CP12-161-04-L1-W4.5	76.3	7.3	17.6	70.5	40	40	40	3.3
430848-504	CP12-161-06-L1-W4.5	47.7	4.5	17.6	70.5	40	40	40	3.6
56910-502	CP14-127-045-L1-W4.5	71.3	8.6	13.9	70.5	40	40	40	3.3
56760-505	CP14-127-06-L1-W4.5	49.3	6	13.9	70.5	40	40	40	3.8
56610-502	CP14-127-10-L1-W4.5	32.2	3.9	13.9	70.5	40	40	40	4.7
44530-501	CP14-17-10-L1-W4.5	4.3	3.9	1.9	70.5	15	15	15	4.7
430875-503	CP14-199-045-L1-W4.5	111.8	8.6	21.7	70.5	40	40	40	3.3
430874-503	CP14-199-06-L1-W4.5	77.3	6.0	21.7	70.5	40	40	40	3.81
56550-501	CP14-31-10-L1-W4.5	7.9	3.9	3.4	70.5	20	20	20	4.7
56860-501	CP14-35-045-L1-W4.5	19.7	8.6	3.8	70.5	15	30	15	3.3
56890-503	CP14-71-045-L1-W4.5	39.9	8.6	7.8	70.5	30	30	30	3.3
430705-503	CP14-71-06-L1-W4.5	27.6	6.0	7.8	70.5	30	30	30	3.8
56590-502	CP14-71-10-L1-W4.5	18.0	3.9	7.8	70.5	30	30	30	4.7
66100-501	CP2-127-06-L1-W4.5	117.8	14.2	13.9	70.5	62	62	62	4.6
64979-501	CP2-127-10-L1-W4.5	76.9	9.3	13.9	70.5	62	62	62	5.6
57125-501	CP2-31-06-L1-W4.5	28.8	14.2	3.4	70.5	30	30	30	4.6
56995-501	CP2-31-10-L1-W4.5	18.8	9.3	3.4	70.5	30	30	30	5.6
57180-501	CP2-71-06-L1-W4.5	65.9	14.2	7.8	70.5	44	44	44	4.6
57040-500	CP2-71-10-L1-W4.5	43.0	9.3	7.8	70.5	44	44	44	4.6

Annular Series



SH SERIES



RH SERIES

- Features center hole for transmission of light, wires, probes or mounting hardware.
- Round or square hole configurations available.
- Rapid prototyping available to accommodate unique shape requirements.

MFG PART NUMBER	DESCRIPTION	QMAX (WATTS)	IMAX (AMPS)	VMAX (VOLTS)	ΔTMAX (°C)	DIM A (MM)	DIM B (MM)	DIM C (MM)	DIM D (MM)	DIM E (MM)
71062-514	RH14-14-10-L1-W4.5	3.5	3.9	1.5	70.5	26	26	26	4.7	14
71063-505	RH14-14-06-L1-W4.5	5.4	6	1.5	70.5	26	26	26	3.8	14
66156-505	RH14-32-06-L1-W4.5	12.4	6	3.5	70.5	44	55	55	3.8	27
430058-508	SH08-28-05-L1-W4.5	4.8	2.6	3.1	70.5	14.7	10.3	14.7	3.1	4.4
430511-504	SH10-23-06-L1-W4.5	4.6	3.1	2.5	70.5	15	15	15	3.6	7.2
71049-501	SH10-95-06-L-W4.5	19.1	3.1	10.4	70.5	30	30	30	3.6	14.5
430474-501	SH10-125-05-L1-W4.5	32.5	4	13.7	70.5	30	30	30	3.2	3.6
71092-501	SH14-15-06-L-W4.5	5.8	6	1.6	70.5	14	14	14	3.8	5.1
71061-504	SH14-125-10-L1-W4.5	31.7	3.9	13.7	70.5	40	40	40	4.7	4.7
430478-502	SH14-125-06-L1-W4.5	48.5	6	13.7	70.5	40	40	40	3.8	4.7
71020-505	SH14-125-045-L1-W4.5	70.3	8.6	13.7	70.5	40	40	40	3.3	4.7

Notes: 1) QMax rated value at ΔT = 0°C, Imax and Vmax, Th = 27°C 2) Thickness for non-metallized versions only.

Finishing Options

SURFACE FINISH OPTIONS	CP	OPTOTEC OTX/HTX	HITEMP ETX	POWER CYCLING PCX	ULTRATEC UTX	MULTISTAGE	ANNULAR SH/RH
Metallized Hot/Cold Surface	MM	00	10	-	00	00	MM
Non-Metallized Hot and/or Cold face	L	11	11	11	11	11	L
Pre-tinning Hot and/or Cold face with 118°C InSn Solder	TT	22	-	-	22	22	TT
Pre-tinning Hot and/or Cold face with 138°C BiSn Solder	-	33	-	-	-	-	-
Au plating (Hot/Cold Surface)	-	GG	-	-	GG	-	-



Example: CP10-127-05TL = Pre-tinned Hot Face (118°C InSn), Non-Metallized Cold Face. Note: Metallization and pretinning are not recommended for module sizes larger than 12 x 12 mm's. Consult datasheet for module thicknesses for each surface finishing option. Contact Tark Thermal Solutions for finishing options for Multistage Modules.

THICKNESS TOLERANCE OPTIONS	CP	OPTOTEC OTX/HTX	HITEMP ETX	POWER CYCLING PCX	ULTRATEC UTX	MULTISTAGE	ANNULAR SH/RH
+/- 0.001" (0.025 mm)	L1	TA	TA	TA	TA	-	TA
+/- 0.0005" (0.013 mm)	L2	TB	TB	TB	TB	-	TB



Example: CP10-127-05-L2 = thickness is 3.2 mm +/- 0.013 mm. Contact Tark Thermal Solutions for thickness options for Multistage Modules.

MOISTURE PROTECTION OPTIONS	CP	OPTOTEC OTX/HTX	HITEMP ETX	POWER CYCLING PCX	ULTRATEC UTX	MULTISTAGE	ANNULAR SH/RH
RTV perimeter seal, Color: Translucent or White	RT	RT	RT	RT	RT	RT	RT
Epoxy perimeter seal, Color: Black	EP	EP	EP	EP	EP	EP	EP



Example: CP10-127-05-L2-RT = RTV silicone perimeter seal Silicone (RTV) is an all purpose sealant that exhibits good sealing characteristics and retains its elastomeric properties over a wide temperature range, -60 to 200°C. The sealant is non-corrosive to many chemicals and exhibits good electrical properties with low thermal conductivity. Epoxy (EP) is an effective barrier to moisture that exhibits a useable temperature range of -40 to 130°C. When cured the material is completely uni-cellular and therefore the moisture absorption is negligible. The material exhibits a low dielectric constant, low coefficient of thermal expansion and low shrinkage.

WIRE OPTIONS	CP	OPTOTEC OTX/HTX	HITEMP ETX	POWER CYCLING PCX	ULTRATEC UTX	MULTISTAGE	ANNULAR SH/RH
Custom lead length # in inches, (S denotes special requirement)	W#	W#	W#	W#	W#	W#	W#



Example: CP10-127-05-L2-W8 = Wire length is 8" (203 mm). Reference datasheet for standard lead length, wire type and insulation sleeving. Consult with Tark Thermal Solutions for wire bondable posts or thru hole mount.



TTS-CAT-THERMOELECTRIC-COOLERS 081525

Any information furnished by Tark Thermal Solutions and its agents, whether in specifications, data sheets, product catalogues or otherwise, is believed to be (but is not warranted as being) accurate and reliable, is provided for information only and does not form part of any contract with Tark Thermal Solutions. All specifications are subject to change without notice. Tark Thermal Solutions assumes no responsibility and disclaims all liability for losses or damages resulting from use of or reliance on this information. All Tark Thermal Solutions products are sold subject to the Tark Thermal Solutions Terms and Conditions of sale (including Tark Thermal Solutions' limited warranty) in effect from time to time, a copy of which will be furnished upon request.

© Copyright 2019-2025 Tark Thermal Solutions, Inc.